

Ditch No. 16

EXHIBIT 2.

# VIEWERS' REPORT

—IN—

## DITCH PROCEEDINGS.

"D"

Ditch No. 16

Specifications,

No. 680.—Pioneer Press Co., St. Paul, Minn.

Filed April 26<sup>th</sup> 1892

J. W. Putnam  
County Auditor

*[Faint, illegible handwritten text, likely bleed-through from the reverse side of the page.]*

*[Faint handwritten text, possibly a date or signature.]*

EXHIBIT 2 OF VIEWERS' REPORT IN DITCH PROCEEDINGS.

Showing Time and Manner in which same must be done. Ditch No. ....

SECTION	TIME WITHIN WHICH WORK MUST BE DONE	MANNER IN WHICH WORK MUST BE DONE	MATERIALS USED	COST OF MATERIALS AND WORK
Stake No. 0 TO Stake No. 122	is November 1st 1892	<p>The earth from the ditch is to be thrown back at least two feet from the side of the same.</p> <p>When there is good soil it may be cut out in strips not less than 14 in in width and laid upside down one foot from the edge of the ditch, and all material taken out shall be thrown beyond it.</p> <p>Any old deal or board or other ditch within six feet of line of ditch may be filled with the material taken out of new ditch.</p> <p>A new culvert is to be made at Station 52+25 of 2 in flank not less than 16 feet in length, making an opening or water way of 2 feet on the bottom and same width at top as the ditch</p>	2 in Flank	\$ 15 00