

Dated 57

Contract
Specification



Filed this 2nd day
of November, 1916
H. H. Rasmussen
County Auditor.
K. C. P. Pipefitters

7223-7226

FILED Oct. 19, 1917

Theo. A. E. Nelson
Clerk of Circuit Court, Anoka County, Minn.

C O N T R A C T A N D S P E C I F I C A T I O N S

O F
C O U N T Y D I T C H N O. 57.

A N O X A C O U N T Y.

CONTRACT AND SPECIFICATIONS

IN RE

County Ditch No. 57 of Anoka County, Minnesota.

THIS AGREEMENT made and entered into this 13th day of November A. D. 1916, between the County of Anoka, in the State of Minnesota, party of the first part, and W. R. Ewing Inc. of Chicago Ill, party of the second part:

WITNESSETH, That for and in consideration of the payments to be made by the said party of the first part at the times and in the manner as hereinafter mentioned, the said party of the second part covenants and agrees at his own sole cost and expense to build, construct, and complete in the most skillful and workmanlike manner all of County Ditch, Number Fifty Seven (57), of Anoka County, Minnesota, and all its branches, laterals, and construction work in accordance with the plans and specifications comprising the report of the civil Engineer appointed in the proceedings known as County Ditch, Number Fifty Seven (57), which said report, plans, and specifications are hereby referred to and made a part hereof, as well as such other, further and supplemental plans and specifications as shall be hereafter be made by the said Engineer, and also in accordance with the specifications herein set forth for the sum of Nineteen

Thousand

Dollars (\$ 19000.00), as

given in my bid submitted for the said work on the 25th day of Oct A. D. 1916, the said work being the construction of County Ditch Number Fifty Seven (57), Anoka County Minnesota, in the said County; and it is agreed that the work shall be done within the time as hereinafter specified and in the manner herein specified and in accordance with the report of the Civil Engineer appointed in said proceeding, plans, and specifications and profiles of said ditch, which are on file in the office of the Auditor of Anoka County, Minnesota, and in accordance with the laws of the state of

Minnesota relative to the construction of public ditches in the said state.

AND IT IS FURTHER AGREED, That the said party of the second part shall commence work within 150 days from date and shall complete the above described work on or before the 1st day of Jan A. D. 1910.

AND IT IS FURTHER AGREED, That the said party of the second part will furnish all materials, tools, labor, and appliances necessary for the construction of said work in the manner and within the time as set forth in this agreement.

AND IT IS FURTHER AGREED, That no claim for extra work or alterations shall under any circumstances, be allowed or considered, unless the same shall have been done in pursuance of the written order of the said engineer, and all materials and work, whether herein specified or ordered in addition hereto, shall be measured and estimated upon the terms and conditions as may be prescribed by this contract and the said Engineer.

AND IT IS FURTHER AGREED, That all the work herein specified shall be done and prosecuted under the direction of and acceptably to the said Engineer, and the said Engineer may from time to time condemn and reject any materials used or proposed to be used by said party of the second part, or any sub-contractor under him, which shall fail to conform to this contract and the specifications herein set forth, and any materials so condemned and rejected shall be forthwith replaced by other materials conforming to the requirements hereof.

AND IT IS FURTHER AGREED, That as the work progresses the engineer, with the consent of the County Auditor of the above named County, may alter or change the plans, specifications, or the manner of conducting the work as circumstances may require, but it is agreed that no change will be made that will substantially impair the usefulness of any part of the ditch, or substantially alter its original character, or increase its total cost by more than Ten (10) per cent of the original contract price. And, any charges so made shall be done only on the written order of the said Engineer.

AND IT IS FURTHER AGREED, that any decision

order, or estimate rendered by the said engineer shall be conclusive upon the said party of the second part hereto.

AND IT IS FURTHER AGREED, That the Laws of the State of Minnesota, pertaining to the construction of public ditches, and all matters relating to the payment thereof, and the conditions thereof, whether set forth in this contract or otherwise, are made a part hereof and control the parties hereto if not mentioned herein, as fully as if the same were specifically set forth herein.

AND IT IS FURTHER AGREED: That the time shall be the essence of this agreement, and should the party of the second part fail to complete the work as hereinbefore described in the manner herein described, or within the time as herein set forth, or according to the terms of this agreement, then the said party of the second part shall forfeit to the said County of Anoka, the sum of Ten Dollars (\$10.00) for each and every day that the said work remains in an unfinished condition after the time above specified.

T E R M S.

County Commissioners. The term "County Commissioners" wherever used in this agreement is intended to designate a majority of the members of the Board of County Commissioners of the Counties of Washington and Anoka, in the State of Minnesota.

Contractor. The term "Contractor" wherever used in this agreement is intended to designate the party or parties who may contract with the County for the construction of any part of this work.

Engineer. The term "Engineer" wherever used in this agreement is intended to designate the Civil Engineer, who has been appointed Commissioners by the County of Anoka County for the survey and superintendence of this work.

Plans. The plans, reports, specifications, and the General Laws of the state of Minnesota relative to the construction

of public ditches must be considered in submitting bids on this work and for the construction of the same.

Claims
and
Liens.

The Contractor will be required, and here-by agrees to save and hold the County harmless against all claims and liens for labor or materials furnished, during or under this contract and will, if required, furnish satisfactory proof that all such claims have been paid.

Estimates.

The making of estimates shall not be construed as an acceptance of any portion of the work or materials, but the contractor shall be liable to all the conditions of these specifications and his agreement until the job is completed and accepted.

General

S P E C I F I C A T I O N S .

Description.

This work shall consist of furnishing all materials, tools, labor and appliances, and building complete in every detail County Ditch No. Fifty Seven (57) of Anoka County, Minnesota, to the satisfaction of the County Commissioners of Anoka County, and the Engineer, and in compliance with the plans and report of such on file and of record in the office of the Auditor of the said County, and these specifications.

Time.

Work shall commence on or before the
13th day of April A. D. 1917,
and shall be pushed with due diligence until its completion, which completion shall occur before the
1st day of Jan A. D. 1918

Highways.

The contractor will give notice to the Township Supervisors, at least one week before he crosses any public highway with an open ditch, so that a temporary bridge may be prepared.

Clearing
and
Grubbing.

The contractor shall clear the part of the right of way to be occupied by the ditch, from all trees, underbrush, roots and stumps to a width of three (3) feet on each side of the top of the finished ditch and its branches. Such trees, underbrush, to be clipped of its branches, removed and piled outside the earth

taken from the prism of the ditch and its branches, and shall be and remain the property of the owner of the land on which said trees, etc., are found.

Opening.

Where the ditch is designated to be an open ditch, the top shall be opened sufficiently to secure a completed ditch of the required width even though the opening has to be made wider than the width stated in the report of the engineer.

**Entrances
of
water courses.**

All downstream ends of cut offs in the old creek or ditches and the entrances of all water courses into the ditch shall be left open.

Material

Deposited.

From open ditch, all material shall be removed from the prism of the ditch and deposited on either side thereof unless otherwise directed by the engineer, and evenly spread to a uniform thickness and to a width of Twenty (20) feet from the bank of the ditch.

In a covered trench the materials shall be piled on either side of the ditch and when the work is completed, and upon direction of the engineer, it shall be used to refill the trench. All surplus earth and suitable material shall be deposited on the road bed if the ditch is within the limits of any traveled layed out highway.

Along Road.

Where an open ditch follows parallel and within Four (4) rods of the center line of a traveled or legally established road, the material that is taken from the ditch shall be distributed to a uniform depth on the center line of the said road and to a width of not less than six (6) feet from the center on either side, so as to form a turnpike along the center line of the said road to a length equal to the length of said ditch along said highway.

Crosses Road.

Where the line of the ditch crosses a traveled or legally established road, the material from the ditch will be deposited in such a manner as the engineer may direct.

Highways.

The contractor will give notice to the Township Supervisors, at least one week before he crosses any public highway with an open ditch, so that a temporary bridge may be prepared.

Berm.

Where the material from the ditch is deposited as a spoil bank no earth or other material shall be left on the side of the ditch within three (3) feet of either side of the completed ditch. This space of three (3) feet shall be, when the ditch is completed, free from earth or any material or roots or stump..

Old Ditches.

Where the bank of this ditch runs within Twenty (20) feet or less of a bank of any old ditch or creek, the material from the new ditch shall be deposited in the old ditch or creek until sufficient earth has been deposited therein to completely fill the same.

Bridges.

The bridging of the roads where the ditch crosses a road will be done by the Board of supervisors of the town in which the crossing is situated, unless otherwise designated, and then will be built in accordance with the plans in said engineer's report.

Railroads.

The contractor, at his own expense, must make all arrangements for crossing the Great Northern Right of Way, as the same now crosses the proposed ditch. This expense shall be included in the contract price.

**Bridges
and
Obstructions.**

Where the line of the proposed ditch passes through a bridge of permanent construction, over a public highway and it is necessary for the contractor to leave the line of the proposed ditch and go around the bridge, he shall, at his own expense, dig through the road right of way under the direction of the Engineer. The ditch so dug shall be filled up immediately and the road and land adjoining shall be left in as good condition as found. The proposed ditch under the bridge and on both sides which are not accessible to the contractor's dredge shall be excavated by hand.

Wooden bridges on the line of the proposed ditch shall be removed by the contractor at his own expense, and the material piled on the side of the road. All expenses connected with the removal or passage of bridges shall be included in the contract price.

Staking.

The ditch and its branches has been staked by placing numbered stakes at each one hundred (100) feet and by placing a larger pole where the line of the ditch changes. These stakes are on the center line of the proposed ditch and its branches and should be closely followed in the construction of the same.

Excavation.

The ditch and its branches will be excavated to the depth, the width on top, the width on the bottom and have the banks of the slope as given and set forth in the report of the engineer, on file in the office of the Auditor of the said County. The bottom between each One Hundred (100) foot station will be made smooth and straight, and the banks will have a uniform slope of One (1) to One (1) between each of said points.

Levels have been taken at the uneven points between One Hundred (100) feet stations, and quantities estimated for such unevenness so that the contractor will receive payment for each cubic yard removed.

Open Ditches.

The general form of the open ditches shall be of the required depth and having the side slopes One (1) to One (1) between the stations and the ditch will have the same slope of the sides and shall be sufficient width on top to secure that slope.

AND IT IS FURTHER AGREED, That the payment of Nineteen Thousand Dollars (\$ 19000.00), for the construction of said ditch, branches, laterals, and other construction incident thereto will be made by the said party of the first

part in accordance with and at the time established by the Laws of the State of Minnesota relative to the drainage of lands by the Counties and Courts of the State of Minnesota.

IN WITNESS WHEREOF, The said parties to this agreement have hereunto set their hands and seals the day and year first above written.

IN PRESENCE OF

* W P Cassell
Jannie B. Lenfest

E H
Le H. Lush

W H Bradley (Seal)
Chairman Board of C. Commissioners of Anoka Co., Minn.
and W H Bradley (Seal)
C. Judge of Lands C. Minn.
Jannie Lenfest (Seal)
W R Ewing Jr. (Seal)
by W R Ewing Jr. (Seal)

(Seal)

Attachment

Contract
Specieless
S.P.

Filed this 21st day
of November 1916
in the County Court
County Auditor,
by C. A. Phillips.

7223-7226

FILED Oct. 19, 1917
Theodore E. Wilson
State of General Court, Boston, Mass.