


# MINNESOTA DEPARTMENT OF TRANSPORTATION

## CITY OF BLAINE, ANOKA COUNTY, MINNESOTA


CONSTRUCTION PLAN FOR

GRADING, BITUMINOUS PAVING, CONCRETE CURB & GUTTER, ADA IMPROVEMENTS, AND SIGNAL SYSTEM

PLOTTED/REVISED: 7/29/2022 12:24:01 PM




PROJECT LOCATION  
COUNTY: ANOKA  
DISTRICT: METRO



PROJECT LOCATION  
SECTION: 1, 2  
TOWNSHIP: 31 N  
RANGE: 23 W

LOCATED ON CSAH 17 (LEXINGTON AVE NE) AT 131ST AVE NE (MSAS 141)



| PLAN REVISIONS |           |             |
|----------------|-----------|-------------|
| DATE           | SHEET NO. | APPROVED BY |
|                |           |             |
|                |           |             |
|                |           |             |
|                |           |             |
|                |           |             |

### EXCAVATION NOTICE SYSTEM

A CALL TO GOPHER STATE ONE CALL (651-454-0002) IS REQUIRED A MINIMUM OF 48 HOURS PRIOR TO PERFORMING ANY EXCAVATION.

### UTILITY INFORMATION

THE SUBSURFACE UTILITY INFORMATION IN THIS PLAN IS UTILITY QUALITY LEVEL D. THIS UTILITY QUALITY LEVEL WAS DETERMINED ACCORDING TO THE GUIDELINES OF CI/ASCE 38-02, ENTITLED "STANDARD GUIDELINES FOR THE COLLECTION AND DEPICTION OF EXISTING SUBSURFACE UTILITY DATA."

GOPHER ONE CALL TICKET NUMBER(S):  
221150968, 221150970

PATH & FILENAME: K:\019869-000\Cad\Plan\19869-000-C-TITLE-PLAN.dgn

### DESIGN DESIGNATION

| CSAH 17<br>(LEXINGTON AVE NE) |                       | 131ST AVE NE<br>(MSAS 141) |  |
|-------------------------------|-----------------------|----------------------------|--|
| GROSS LENGTH                  | 585.65' = 0.111 MILES | 300.03' = 0.057 MILES      |  |
| BRIDGES-LENGTH                | NA                    | NA                         |  |
| EXCEPTIONS-LENGTH             | NA                    | NA                         |  |
| NET LENGTH                    | 585.65' = 0.111 MILES | 300.03' = 0.057 MILES      |  |
| R VALUE                       | NA                    | 50                         |  |
| CURRENT ADT (2022)            | 13,400                | 250                        |  |
| FUTURE ADT (2042)             | 25,400                | 300                        |  |
| D (DIRECTIONAL DISTR.)        | 50 / 50               | 50 / 50                    |  |
| HEAVY COMMERCIAL              | 3.83%                 | 3.84%                      |  |
| ESALS                         | NA                    | 30,000                     |  |
| DESIGN SPEED                  | 55 MPH                | 30 MPH                     |  |
| BASED ON SIGHT DISTANCE       | STOPPING              | STOPPING                   |  |
| HEIGHT OF EYE / OBJECT        | 3.5' / 2.0'           | 3.5' / 2.0'                |  |
| FUNCTIONAL CLASS              | MINOR ARTERIAL        | LOCAL                      |  |
| NO. OF TRAFFIC LANES          | 4                     | 2                          |  |
| NO. OF PARKING LANES          | 0                     | 0                          |  |
| SHOULDER WIDTH                | 8'                    | NA                         |  |
| TON DESIGN                    | 10                    | 10                         |  |
| DESIGN SPEED NOT ACHIEVED AT  | NA                    | NA                         |  |

### GOVERNING SPECIFICATIONS

THE 2020 EDITION OF THE MINNESOTA DEPARTMENT OF TRANSPORTATION "STANDARD SPECIFICATIONS FOR CONSTRUCTION" SHALL GOVERN.

THE CITY OF BLAINE STANDARD SPECIFICATIONS SHALL GOVERN.

ALL TRAFFIC CONTROL DEVICES SHALL CONFORM TO THE LATEST EDITION OF THE MINNESOTA MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES, INCLUDING THE LATEST EDITION OF THE FIELD MANUAL FOR TEMPORARY TRAFFIC CONTROL ZONE LAYOUTS.

### PLAN SHEET INDEX

| SHEET NO. | DESCRIPTION                                 |
|-----------|---|
| 1         | TITLE SHEET                                 |
| 2         | GENERAL LAYOUT                              |
| 3         | STATEMENT OF ESTIMATED QUANTITIES           |
| 4 - 5     | CONSTRUCTION NOTES & STANDARD PLATES        |
| 6 - 7     | Typical Sections                            |
| 8         | MISCELLANEOUS DETAILS                       |
| 9 - 20    | STANDARD PLANS                              |
| 21 - 26   | CONSTRUCTION STAGING & TRAFFIC CONTROL PLAN |
| 27 - 28   | ALIGNMENT PLAN & TABULATION                 |
| 29        | INPLACE TOPOGRAPHY & REMOVALS               |
| 30 - 32   | STREET & DRAINAGE PLAN                      |
| 33        | TURF ESTABLISHMENT & EROSION CONTROL        |
| 34 - 35   | SIGNING & STRIPING PLAN                     |
| 36 - 52   | TRAFFIC CONTROL SIGNAL SYSTEM               |
| 53        | CSAH 17 CROSS SECTIONS                      |

THIS PLAN CONTAINS 53 SHEETS

ALL APPLICABLE FEDERAL, STATE, AND LOCAL LAWS AND ORDINANCES WILL BE COMPLIED WITH IN THE CONSTRUCTION OF THIS PROJECT.



DESIGN ENGINEER: I HEREBY CERTIFY THAT THIS PLAN WAS PREPARED BY ME OR UNDER MY DIRECT SUPERVISION, AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MINNESOTA.

NICHOLAS E. HENTGES, PE.

PRINTED NAME

44620

LICENSE NO.

APPROVED: CITY OF

BLAINE ENGINEER

APPROVED: ANOKA

COUNTY ENGINEER

I HEREBY CERTIFY THAT THE FINAL FIELD REVISIONS, IF ANY, OF THE PLAN WERE MADE BY ME OR UNDER MY DIRECT SUPERVISION AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MINNESOTA.

PRINTED NAME

LICENSE NO.



WSB PROJECT  
019869-000

SHEET  
1  
OF  
53  
SHEETS

## CSAH 17

PLOTTED/REVISED: 7/29/2022 12:24:03 PM

PATH &amp; FILENAME: K:\019869-000\Cad\Plan\19869-000-C-GENL-LAYT.dgn



## SHEET INDEX

|   |    |
|---|----|
| ALIGNMENT PLAN                          | 27 |
| INPLACE TOPOGRAPHY & REMOVAL PLAN       | 29 |
| STREET, DRAINAGE, SITE RESTORATION PLAN | 30 |

## GENERAL LAYOUT

SHEET  
2  
OF  
53  
SHEETS

CITY OF BLAINE, MN  
LEXINGTON AVENUE NE AT  
131ST AVENUE NE  
INTERSECTION IMPROVEMENTS

WSB PROJECT NO.:  
019869-000

SCALE: DESIGN BY:  
AS SHOWN AJF  
PLAN BY: CHECK BY:  
AJF NEH

| REVISIONS |      |             |
|-----------|------|-------------|
| NO.       | DATE | DESCRIPTION |
|           |      |             |
|           |      |             |
|           |      |             |

I HEREBY CERTIFY THAT THIS PLAN, SPECIFICATION, OR REPORT WAS PREPARED BY ME OR UNDER MY DIRECT SUPERVISION AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MINNESOTA.

NICHOLAS E. HENTGES, PE  
DATE: 7/29/2022 LIC. NO: 44620

DRAFT

| ITEM NUMBER | DESCRIPTION                                   | NOTES | UNIT     | PROJECT TOTAL      | DEVELOPER / CITY SHARED | DEVELOPER          | CITY OF BLAINE     |
|-------------|---|-------|----------|--------------------|-------------------------|--------------------|--------------------|
|             |   |       |          | ESTIMATED QUANTITY | ESTIMATED QUANTITY      | ESTIMATED QUANTITY | ESTIMATED QUANTITY |
| 2021.501    | MOBILIZATION                                  |       | LUMP SUM | 1                  | 0.71                    | 0.17               | 0.11               |
| 2104.502    | REMOVE LIGHTING UNIT                          |       | EACH     | 1                  |                         |                    | 1                  |
| 2104.502    | REMOVE CASTING                                |       | EACH     | 2                  |                         | 2                  |                    |
| 2104.502    | REMOVE SIGN                                   |       | EACH     | 2                  |                         |                    | 2                  |
| 2104.502    | REMOVE HANHOLE                                |       | EACH     | 1                  |                         | 1                  |                    |
| 2104.502    | REMOVE LIGHT FOUNDATION                       |       | EACH     | 1                  |                         |                    | 1                  |
| 2104.502    | REMOVE MAIL BOX SUPRT                         |       | EACH     | 1                  |                         | 1                  |                    |
| 2104.502    | SALVAGE CASTING                               |       | EACH     | 2                  |                         |                    | 2                  |
| 2104.503    | SAWING BIT PAVEMENT (FULL DEPTH)              |       | LIN FT   | 664                |                         | 500                | 164                |
| 2104.503    | REMOVE CURB AND GUTTER                        |       | LIN FT   | 626                |                         | 500                | 126                |
| 2104.504    | REMOVE BITUMINOUS PAVEMENT                    |       | SQ YD    | 92                 |                         |                    | 92                 |
| 2104.518    | REMOVE BITUMINOUS WALK                        |       | SQ FT    | 392                |                         |                    | 392                |
| 2104.518    | REMOVE CONCRETE WALK                          |       | SQ FT    | 292                |                         |                    | 292                |
| 2106.507    | EXCAVATION - COMMON                           |       | CU YD    | 700                |                         | 400                | 300                |
| 2106.507    | EXCAVATION - SUBGRADE                         |       | CU YD    | 175                |                         |                    | 175                |
| 2106.507    | COMMON EMBANKMENT (CV)                        |       | CU YD    | 100                |                         | 50                 | 50                 |
| 2106.507    | SELECT GRANULAR EMBANKMENT (CV)               |       | CU YD    | 175                |                         |                    | 175                |
| 2112.604    | SUBGRADE PREPARATION                          | (P)   | SQ YD    | 1583               |                         | 668                | 915                |
| 2123.610    | STREET SWEEPER (WITH PICKUP BROOM)            |       | HOUR     | 30                 |                         | 15                 | 15                 |
| 2130.523    | WATER   | (1)   | MGAL     | 30                 |                         | 15                 | 15                 |
| 2118.509    | AGGREGATE SURFACING CLASS 2                   |       | TON      | 47                 |                         |                    | 47                 |
| 2211.509    | AGGREGATE BASE CLASS 5                        |       | TON      | 509                |                         | 254                | 255                |
| 2231.509    | BITUMINOUS PATCHING MIXTURE                   |       | TON      | 15                 |                         |                    | 15                 |
| 2232.504    | MILL BITUMINOUS SURFACE (1.5")                |       | SQ YD    | 668                |                         | 368                | 300                |
| 2301.602    | DRILL & GROUT REINF BAR (EPOXY COATED)        |       | EACH     | 75                 | 75                      |                    |                    |
| 2357.506    | BITUMINOUS MATERIAL FOR TACK COAT             |       | GALLON   | 140                |                         | 97                 | 43                 |
| 2360.509    | TYPE SP 9.5 WEARING COURSE MIXTURE (3,C)      |       | TON      | 69                 |                         |                    | 69                 |
| 2360.509    | TYPE SP 12.5 NON WEARING COURSE MIXTURE (3,B) |       | TON      | 100                |                         | 100                |                    |
| 2360.509    | TYPE SP 12.5 NON WEARING COURSE MIXTURE (3,C) |       | TON      | 55                 |                         |                    | 55                 |
| 2360.509    | TYPE SP 12.5 WEARING COURSE MIX (3,F)         |       | TON      | 120                |                         | 120                |                    |
| 2503.503    | 15" RC PIPE SEWER DES 3006 CL V               |       | LIN FT   | 16                 |                         | 16                 |                    |
| 2506.502    | CASTING ASSEMBLY                              |       | EACH     | 4                  |                         | 4                  |                    |
| 2506.502    | INSTALL CASTING                               |       | EACH     | 2                  |                         |                    | 2                  |
| 2506.503    | CONSTRUCT DRAINAGE STRUCTURE DESIGN H         |       | LIN FT   | 7                  |                         | 7                  |                    |
| 2506.602    | CONNECT INTO EXISTING DRAINAGE STRUCTURE      |       | EACH     | 2                  |                         | 2                  |                    |
| 2521.518    | 6" CONCRETE WALK                              |       | SQ FT    | 1426               | 853                     | 154                | 419                |
| 2531.503    | CONCRETE CURB & GUTTER DESIGN B424            |       | LIN FT   | 633                |                         | 507                | 126                |
| 2531.618    | TRUNCATED DOMES                               |       | SQ FT    | 140                | 140                     |                    |                    |
| 2563.601    | TRAFFIC CONTROL                               |       | LUMP SUM | 1                  | 0.71                    | 0.17               | 0.11               |
| 2563.613    | PORTABLE CHANGEABLE MESSAGE SIGN              |       | UNIT DAY | 14                 |                         | 14                 |                    |
| 2564.518    | SIGN PANELS TYPE C                            |       | SQ FT    | 30                 |                         | 22                 | 8                  |
| 2565.501    | EMERGENCY VEHICLE PREEMPTION SYSTEM           |       | LUMP SUM | 1                  | 1                       |                    |                    |
| 2565.516    | TRAFFIC CONTROL SIGNAL SYSTEM                 |       | SYSTEM   | 1                  | 1                       |                    |                    |
| 2573.502    | STORM DRAIN INLET PROTECTION                  |       | EACH     | 11                 |                         | 4                  | 7                  |
| 2573.502    | CULVERT END CONTROLS                          |       | EACH     | 1                  |                         |                    | 1                  |
| 2573.503    | SILT FENCE, TYPE MS                           |       | LIN FT   | 222                |                         |                    | 222                |
| 2573.503    | SEDIMENT CONTROL LOG TYPE COMPOST             |       | LIN FT   | 569                |                         | 400                | 169                |
| 2574.505    | SOIL BED PREPARATION                          |       | ACRE     | 0.3                |                         | 0.2                | 0.1                |
| 2574.507    | COMMON TOPSOIL BORROW                         |       | CU YD    | 122                |                         | 70                 | 52                 |
| 2574.508    | FERTILIZER TYPE 3                             |       | POUND    | 105                |                         | 70                 | 35                 |
| 2575.504    | ROLLED EROSION PREVENTION CATEGORY 20         |       | SQ YD    | 792                |                         | 269                | 523                |
| 2575.508    | SEED MIXTURE 25-131                           |       | POUND    | 66                 |                         | 44                 | 22                 |
| 2575.523    | RAPID STABILIZATION METHOD 3                  |       | MGAL     | 3                  |                         | 2                  | 1                  |
| 2581.503    | REMOVABLE PREFORM PAVEMENT MARKING TAPE       | (3)   | LIN FT   | 841                |                         | 715                | 126                |
| 2582.503    | 4" SOLID LINE MULTI COMP                      |       | LIN FT   | 912                |                         | 788                | 124                |
| 2582.503    | 4" DBLE SOLID LINE MULTI COMP                 |       | LIN FT   | 136                |                         | 12                 | 124                |
| 2582.503    | 24" SOLID LINE PREF THERMO                    |       | LIN FT   | 107                | 107                     |                    |                    |
| 2582.518    | PAVT MSSG PREF THERMO                         |       | SQ FT    | 109                |                         | 62                 | 47                 |
| 2582.518    | CROSSWALK PREF THERMO                         |       | SQ FT    | 900                | 900                     |                    |                    |

**NOTES**

(1) TO BE USED FOR DUST CONTROL AS DIRECTED BY THE ENGINEER.  
 (2) TO BE USED AS DIRECTED BY THE ENGINEER.  
 (3) 4" WHITE  
 (P) PLAN QUANTITY

CITY OF BLAINE, MN  
 LEXINGTON AVENUE NE AT  
 131ST AVENUE NE  
 INTERSECTION IMPROVEMENTS

STATEMENT OF  
 ESTIMATED  
 QUANTITIES

SHEET  
 3  
 OF  
 53  
 SHEETS

WSB PROJECT NO.:  
 019869-000

SCALE: DESIGN BY:  
 AS SHOWN AJF  
 PLAN BY: CHECK BY:  
 AJF NEH

| REVISIONS | NO. | DATE | DESCRIPTION |
|-----------|-----|------|-------------|
|           |     |      |             |
|           |     |      |             |
|           |     |      |             |

I HEREBY CERTIFY THAT THIS PLAN, SPECIFICATION,  
 OR REPORT WAS PREPARED BY ME OR UNDER MY  
 DIRECT SUPERVISION AND THAT I AM A DULY  
 LICENSED PROFESSIONAL ENGINEER UNDER THE  
 LAWS OF THE STATE OF MINNESOTA.

NICHOLAS E. HENTGES, PE  
 DATE: 7/29/2022  
 LIC. NO: 44620

**SOILS & CONSTRUCTION NOTES**

- GRADING GRADE IS DEFINED AS THE BOTTOM OF THE PROPOSED AGGREGATE LAYER. SUITABLE GRADING MATERIAL IS DEFINED AS ANY ON SITE MINERAL SOIL NOT DEFINED AS UNSUITABLE.
- SELECT GRADING MATERIAL SHALL CONSIST OF ALL MINERAL SOILS ENCOUNTERED WITH THE EXCEPTION OF TOPSOIL, DEBRIS, ORGANIC MATERIAL, AND OTHER UNSUITABLE SOILS.
- SLOPE DRESSING ON THE PROJECT IS DEFINED AS THE TOPSOIL OR OTHER SOIL PLACED DURING CONSTRUCTION TO PROVIDE A MEDIUM FOR ESTABLISHING TURF. INPLACE SLOPE DRESSING GENERALLY CONSISTS OF SILTY SAND (SM) WHICH WAS DARK BROWN, MOIST, AND HAD TRACES OF GRAVEL.
- STRIP ALL INPLACE SLOPE DRESSING (TOPSOIL) WHERE PRESENT IN AREAS TO BE DISTURBED BY CONSTRUCTION AND REUSE AS SLOPE DRESSING.
- UNSUITABLE SOILS ARE DEFINED AS MARL, SILT, SILTY LOAM, PEAT, MUCK, TOPSOIL AND OTHER ORGANIC SOILS WHICH DO NOT MEET OR ARE NOT MANUFACTURED TO MEET ANY OF THE DEFINED CATEGORIES, AND ARE THEREFORE NOT REUSABLE. UNSUITABLE MATERIAL MAY NOT BE PLACED WITHIN A 1(V):1.5(H) SLOPE DOWNWARD AND OUTWARD FROM THE GRADING EMBANKMENT PI OR ABOVE THE ELEVATION OF THE BOTTOM OF THE SELECT GRANULAR SUBGRADE CORRECTION MATERIAL. ALL MATERIAL IS SUBJECT TO THE DISCRETION OF THE ENGINEER.
- UNLESS OTHERWISE SPECIFICALLY ALLOWED OR REQUIRED BY THE CONTRACT, BITUMINOUS AND CONCRETE ITEMS DISTURBED BY CONSTRUCTION SHALL BECOME THE PROPERTY OF THE CONTRACTOR AND SHALL BE RECYCLED TO THE EXTENT ALLOWED IN BASE AND SURFACING ITEMS OR DISPOSED OF OUTSIDE OF THE RIGHT-OF-WAY IN ACCORDANCE WITH SPEC 2104.3D3.
- OBTAIN COMPACTION ON PERMANENT GRADING PORTIONS OF CONSTRUCTION IN ACCORDANCE WITH THE "QUALITY COMPACTION METHOD" REQUIREMENTS.
- OBTAIN COMPACTION OF GRADING PORTIONS OF TEMPORARY CONSTRUCTION IN ACCORDANCE WITH THE "QUALITY COMPACTION METHOD" REQUIREMENTS.
- NO FLY ASH, LIME, OR CEMENT STABILIZATION OF THE SUBGRADE SOILS WILL BE ALLOWED PER MNDOT.
- COMPACTION OF THE AGGREGATE BASE LAYERS SHALL BE OBTAINED IN ACCORDANCE WITH THE SPECIFIED DENSITY COMPACTION METHOD.
- ANY TRAFFIC LANES USED DURING CONSTRUCTION ADJACENT TO EXCAVATIONS MUST BE DELINEATED TO KEEP VEHICLES A SAFE DISTANCE AWAY FROM THE EXCAVATIONS, THE DELINEATION SHOULD COINCIDE WITH POINTS ESTABLISHED BY A 1(V):2(H) OR FLATTER SLOPE BETWEEN THE EDGE OF THE TRAFFIC SURFACE AND TEH NEAR EDGE OF THE EXCAVATION BOTTOM.
- DISPOSITION OF EXCAVATED MATERIAL SHALL BE IN ACCORDANCE WITH SPEC 2106.
- WHERE CONNECTING TO INPLACE ROADWAYS AT THE TERMINI OF THE PROPOSED NEW CONSTRUCTION, CUT VERTICALLY TO TEH BOTTOM OF THE INPLACE SURFACING OR TO THE BOTTOM OF THE NEW SURFACING DESIGN, WHICHEVER IS DEEPER; THAN AT A 1(V):20(H) TAPER TO THE BOTTOM OF THE SUBGRADE EXCAVATION.
- PROVIDE A SAWCUT TO ENSURE A UNIFORM JOINT WHEN PLACING NEW PAVEMENT ADJACENT TO INPLACE PAVEMENT. SAWCUTTING OF CONCRETE WALK AND CURB & GUTTER IS INCIDENTAL.
- THE BITUMINOUS TACK COAT MATERIAL SHALL CONSIST OF EMULSIFIED ASPHALT (CSS-1 OR CSS-AH) AND BE APPLIED BETWEEN COURSES AND TO MILLED SURFACES. THE TACK COAT SHALL HAVE WATER ADDED AT A RATE OF 30-40 PERCENT OF THE VOLUME OF THE EMULSION. THE TACK COAT MATERIAL SHALL BE APPLIED AT A UNIFORM RATE OF 0.03 TO 0.05 GAL PER SQUARE YARD BETWEEN NEW BITUMINOUS LAYERS AND AND AT A RATE OF 0.07 TO 0.09 GAL PER SQUARE YARD OVER A MILLED BITUMINOUS SURFACE. THESE APPLICATION RATES ARE FOR UNDILUTED EMULSION (AS SUPPLIED FROM THE REFINERY).
- THE BITUMINOUS MIXTURE SHALL MEET THE REQUIREMENTS OF MNDOT SPECIFICATION 2360.
- THE INFORMATION SHOWN ON THESE DRAWING CONCERNING TYPE AND LOCATION OF PRIVATE UTILITIES IS NOT GUARANTEED TO BE ACCURATE OR ALL-INCLUSIVE. THE CONTRACTOR IS RESPONSIBLE FOR MAKING THEIR OWN DETERMINATIONS AS TO THE TYPE AND LOCATION OF PRIVATE UTILITIES AS MAY BE NECESSARY TO AVOID DAMAGE THERETO. CONTRACTOR TO CALL GOPHER STATE ONE CALL A MINIMUM OF 48 HOURS PRIOR TO EXCAVATION.
- TEMPORARY EROSION CONTROL - TEMPORARY EROSION CONTROL DEVICES AND THEIR SUGGESTED LOCATIONS HAVE BEEN SHOWN IN THE PLANS ALONG WITH PAY ITEMS FOR THEIR USE. THIS DOES NOT HOWEVER RELIEVE THE CONTRACTOR FROM THE RESPONSIBILITY TO CONDUCT CONSTRUCTION IN A MANNER THAT WILL CONTROL EROSION. RESPONSIBILITY FOR CONTROLLING EROSION AND MAINTENANCE OF EROSION CONTROL AS SET IN MNDOT SPECIFICATIONS: 1717, 1803, 2101, 2106, 2575 AND IS AMEND BY THE SPECIAL PROVISIONS.
- ALL TRAFFIC CONTROL DEVICES SHALL CONFORM TO THE LATEST EDITION OF THE MINNESOTA MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES, INCLUDING THE FIELD MANUAL.
- THE CONSTRUCTION LIMITS SHOWN IN THE PLANS REPRESENT THE POINT OF INTERSECTION BETWEEN THE REQUIRED FILL OR CUT SLOPE AND THE EXISTING GROUND LINE AS DEPICTED ON THE CROSS SECTIONS. THE CONSTRUCTION LIMITS DO NOT INCLUDE AREAS REQUIRED FOR SLOPE ROUNDING.

THE FOLLOWING STANDARD PLATES, APPROVED BY THE FEDERAL HIGHWAY ADMINISTRATION, SHALL APPLY ON THIS PROJECT

**MNDOT STANDARD PLATES**

| PLATE NO. | DESCRIPTION   |
|-----------|---|
| 4026A     | CONCRETE ENCASED CONCRETE ADJUSTING RINGS   |
| 4108F     | ADJUSTING RINGS FOR CATCH BASINS AND MANHOLES   |
| 7100H     | CONCRETE CURB AND GUTTER (DESIGN B AND DESIGN V)  |
| 7111J     | INSTALLATION OF CATCH BASIN CASTINGS (CONCRETE CURB AND GUTTER)   |
| 8000K     | TEMPORARY CHANNELIZERS (3 SHEETS)   |
| 8111E     | TRAFFIC SIGNAL BRACKETING (PEDESTAL MOUNTED) (3 SHEETS)   |
| 8112I     | PEDESTAL FOUNDATION (TRAFFIC CONTROL SIGNALS)   |
| 8119C     | GROUND MOUNTED CABINET FOUNDATION   |
| 8122F     | PEDESTAL AND PEDESTAL BASE (FOR TRAFFIC CONTROL SIGNALS SUPPORT) (2 SHEETS)                               |
| 8123G     | POLE AND MAST ARM - LUMINAIRES AND TRAFFIC LIGHTS ASSEMBLY (FOR ALL POLE TYPES) (2 SHEETS)                |
| 8126L     | POLE FOUNDATION (PA90 AND PA100)  |
| 8129A     | SHIM AND WASHER (TRAFFIC CONTROL SIGNALS AND ROADWAY LIGHTING)  |
| 8132B     | PREFORMED RIGID PVC CONDUIT LOOP DETECTOR - LAYOUT DETAILS, LAYOUT NOTES, TYPICAL INSTALLATION (3 SHEETS) |

SEE SHEET 36 FOR ADDITIONAL STANDARD PLATES APPLICABLE TO THIS PROJECT.

**CITY OF BLAINE STANDARD PLATES**

| PLATE NO. | DESCRIPTION                      |
|-----------|----------------------------------|
| ST-6      | CONCRETE C&G                     |
| ST-10     | RURAL SECTION ROAD               |
| ST-11     | RURAL SECTION DRIVEWAY & CULVERT |
| ST-12     | TYPICAL SIDEWALK                 |
| ST-13     | OFF ROAD TRAIL TYPICAL SECTION   |

**UTILITY NOTES**

- THE CONTRACTOR SHALL BE RESPONSIBLE TO COORDINATE WITH THE UTILITY COMPANIES. CALL GOPHER STATE ONE CALL AT LEAST 48 HOURS PRIOR TO EXCAVATION OR CONSTRUCTION.

| THE FOLLOWING IS A LIST OF UTILITY COMPANIES INVOLVED IN THIS PROJECT: |
|--|
| ANOKA COUNTY   |
| ARVIG  |
| CENTERPOINT ENERGY   |
| LUMEN  |
| CITY OF BLAINE   |
| COMCAST  |
| CONNEXUS ENERGY  |
| MCI  |
| XCEL ENERGY  |

**CITY OF BLAINE, MN**  
**LEXINGTON AVENUE NE**  
**131ST AVENUE NE**  
**INTERSECTION IMPROVEMENTS**

**CONSTRUCTION NOTES & STANDARD PLATES**

SHEET  
4  
OF  
53  
SHEETS

I HEREBY CERTIFY THAT THIS PLAN, SPECIFICATION, OR REPORT WAS PREPARED BY ME OR UNDER MY DIRECT SUPERVISION AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MINNESOTA.

NICHOLAS E. HENTGES, PE

DATE: 7/29/2022

LIC. NO: 44620

## REVISIONS

| NO. | DATE | DESCRIPTION |
|-----|------|-------------|
|     |      |             |

I HEREBY CERTIFY THAT THIS PLAN SPECIFICATION, OR REPORT WAS PREPARED BY ME OR UNDER MY DIRECT SUPERVISION AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MINNESOTA.





NICHOLAS E. HENTGES, PE

LIC. NO.: 44620


DATE: 7/29/2022

CITY OF BLAINE, MN  
LEXINGTON AVENUE NE AT  
131ST AVENUE NE  
INTERSECTION IMPROVEMENTSCONSTRUCTION  
NOTES  
&  
STANDARD  
PLATES







PLOTTED/REV/SED: 7/29/2022 12:24:20 PM



PATH &amp; FILENAME: K:\019869-000\Cad\Plan\19869-000-C-PLTS-DETL-02.dwg



| NO. | DATE | DESCRIPTION |
|-----|------|-------------|
|     |      |             |
|     |      |             |
|     |      |             |

CITY OF BLAINE, MN  
LEXINGTON AVENUE NE AT  
131ST AVENUE NE  
INTERSECTION IMPROVEMENTS

| REVISIONS | DESCRIPTION |
|-----------|-------------|
|           |             |

I HEREBY CERTIFY THAT THIS PLAN, SPECIFICATION, OR REPORT WAS PREPARED BY ME OR UNDER MY DIRECT SUPERVISION AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MINNESOTA.

DATE: 7/29/2022

LIC. NO: 44620


NICHOLAS E. HENTGES, PE

# CITY OF BLAINE, MN

## LEXINGTON AVENUE NE AT 131ST AVENUE NE INTERSECTION IMPROVEMENTS


PLOTTED/REV/SED: 7/29/2022 12:24:26 PM

PATH &amp; FILENAME: K:\019869-000\Cad\Plan\19869-000-C-TYPS-DETL.dwg




PROPOSED TYPICAL SECTION 3 - 131ST AVENUE NE

STA 199+10 TO STA 199+69.49




PROPOSED TYPICAL SECTION 1 - 131ST AVENUE NE

STA 197+82.29 TO STA 199+69.49



EXISTING TYPICAL SECTION 2 - CSAH 17

NORTH OF 131ST AVE NE



EXISTING TYPICAL SECTION 1 - CSAH 17

STA 0+40.88 TO STA 6+26.53

## NOTES

① AGGREGATE SURFACING FROM STA 197+82.29 TO STA 198+11, SURFACE ROADWAY WITH 6.0" OF AGGREGATE SURFACING CLASS 2. BEGIN INSET A AT STA 198+11

② MILL BITUMINOUS SURFACE (1.5"), PLACE 1.5" TYPE SP 12.5 WEARING COURSE MIXTURE SPWEB340F BEGINNING STA 119+16

## GENERAL NOTES

1. PREPARATION OF THE EXISTING SUBGRADE SHALL BE IN ACCORDANCE WITH MNDOT SPECIFICATIONS AND SHALL BE INCIDENTAL.
2. UNLESS OTHERWISE SPECIFIED, THE SUBGRADE CROSS SLOPE WILL BE THE SAME AS THE FINISHED SLOPE.
3. ALL UNSUITABLE MATERIAL SHALL BE REMOVED FROM THE ROADWAY.
4. ALL EDGE DIMENSIONS ARE FACE TO FACE OF CURB OR TO THE EDGE OF THE PAVEMENT UNLESS OTHERWISE NOTED.
5. COMMON TOPSOIL SHALL BE INCLUDED IN THE COMMON EMBANKMENT (CV).
6. ALL EMBANKMENT MATERIAL SHALL BE APPROVED BY THE ENGINEER. ALL CONCRETE AND BITUMINOUS REMOVALS MUST BE DISPOSED OF OFF-SITE. REMOVAL AND DISPOSAL OF EXCESS MATERIAL SHALL BE INCIDENTAL.
7. 2' CLEAR ZONE SHALL BE PROVIDED ON EACH SIDE OF THE TRAIL.
8. UNLESS OTHERWISE NOTED, AGGREGATE BASE FOR PEDESTRIAN FACILITIES SHALL EXTEND 12" BEYOND THE CONCRETE OR BITUMINOUS SURFACING.

TYPICAL  
SECTIONS

SCALE: DESIGN BY:  
AS SHOWN AJF  
PLAN BY: CHECK BY:  
AJF NEH

## REVISIONS

| NO. | DATE | DESCRIPTION |
|-----|------|-------------|
|     |      |             |
|     |      |             |
|     |      |             |
|     |      |             |

I HEREBY CERTIFY THAT THIS PLAN, SPECIFICATION,  
OR REPORT WAS PREPARED BY ME OR UNDER MY  
DIRECT SUPERVISION AND THAT I AM A DULY  
LICENSED PROFESSIONAL ENGINEER UNDER THE  
LAWS OF THE STATE OF MINNESOTA.

DATE: 7/29/2022 LIC. NO: 44620


CITY OF BLAINE, MN  
LEXINGTON AVENUE NE AT  
131ST AVENUE NE  
INTERSECTION IMPROVEMENTS

## MISCELLANEOUS DETAILS

SHEET  
8  
OF  
53  
SHEETS

PLOTTED/REVISED: 7/29/2022 12:24:26 PM

PATH &amp; FILENAME: K:\019869-000\Cad\Plan\19869-000-C-M\SC-DETL-01.dwg




FOR OTHER DIMENSIONS SEE STANDARD PLATE NO. 7100 AND CITY STANDARD PLATE ST-6

PAYMENT SHALL BE MADE AS THE CURB &amp; GUTTER TYPE B424 BY THE FOOT

## CURB TRANSITION (B424 TO D312)

NO SCALE



FOR OTHER DIMENSIONS SEE STANDARD PLATE NO. 7100

PAYMENT SHALL BE MADE AS THE CURB &amp; GUTTER TYPE B424 BY THE FOOT

## CURB TRANSITION TO 0" HEIGHT


NO SCALE




12:24:27 PM

29/2022


PLOTTED/REVISED:




## COMBINED DIRECTIONAL



## DIRECTIONAL RAMP WALKABLE FLARE




IF NON-CONCRETE BLVD. IS  
CONSTRUCTED AND IS LESS THAN CURB  
IN WIDTH AT TOP OF CURB  
TRANSITION, PAVE CONCRETE RAMP  
WIDTH TO ADJACENT BACK OF CURB.




DETECTABLE WARNING PLACEMENT WHEN  
SETBACK CRITERIA IS EXCEEDED (1)

ONE-WAY DIRECTIONAL WITH DETECTABLE  
WARNING AT BACK OF CURB




CURB FOR DIRECTIONAL RAMPS (14)



### SEMI-DIRECTIONAL RAMP ③④

3' DOME SETBACK, 4' LONG RAMP AND  
PUSH BUTTON 9' FROM THE BACK OF CURB  
PRIMARILY USED FOR APS APPLICATIONS  
WHERE THE PAR DOES NOT CONTINUE PASS  
THE PUSH BUTTON (DEAD-END SIDEWALK)















REVISION:  
APPROVED: 11-04-2021  
  
JEFFREY PERKINS  
OPERATIONS DIVISION




STANDARD PLAN 5-297 250

APPROVED: 11-04-2018  
REVISED:

## PEDESTRIAN CURB RAMP DETAILS



COMBINED DIRECTIONAL ⑩  
(COMPOUND RADIUS)

|   |
|---|
| REVISION:   |
| APPROVED: 11-04-2021  |
|  |
| JEFFREY PERKINS<br>OPERATIONS DIVISION  |



|                         |          |
|-------------------------|----------|
| STANDARD PLAN 5-297.250 | 3 OF 6   |
| APPROVED: 11-04-2021    | REVISED: |




  
THOMAS TYRBICKI  
STATE DESIGN ENGINEER

## PEDESTRIAN CURB RAMP DETAILS


### PAVEMENT TREATMENT OPTIONS IN FRONT OF CURB & GUTTER FOR USE ON CURB RAMP RETROFITS

#### NOTES:

- POSITIVE FLOW LINE DRAINAGE SHALL BE MAINTAINED THROUGH THE PEDESTRIAN ACCESS ROUTE (PAR) AT A 2% MAXIMUM.
- NO PONDING SHALL BE PRESENT IN THE PAR.
- ANY VERTICAL LIP THAT OCCURS AT THE FLOW LINE SHALL NOT BE GREATER THAN 1/4 INCH.
- ① FOR USE AT CURB CUTS WHERE THE PEDESTRIAN'S PATH OF TRAVEL IS ASSUMED PERPENDICULAR TO THE GUTTER FLOW LINE. RAMP TYPES INCLUDE: PERPENDICULAR, TIERED PERPENDICULAR, PARALLEL, AND DIAGONAL RAMPS.
- ② FOR USE AT CURB RAMPS WHERE THE PEDESTRIAN'S PATH OF TRAVEL IS ASSUMED NON PERPENDICULAR TO THE GUTTER FLOW LINE. RAMP TYPES INCLUDE: FANS & DEPRESSED CORNERS.
- ③ BEGIN GUTTER SLOPE TRANSITION 10' OUTSIDE OF ALL CURB RAMPS.
- ④ THERE SHALL BE NO VERTICAL DISCONTINUITIES GREATER THAN 1/4".
- ⑤ ELEVATION CHANGE TAKES PLACE FROM THE EXISTING TO NEW FRONT OF GUTTER. PATCH IS USED TO MATCH THE NEW GUTTER FACE INTO THE EXISTING ROADWAY.
- ⑥ VARIABLE WIDTH FOR DIRECTIONAL CURB APPLICATIONS. SEE SHEET 2 FOR DIRECTIONAL CURB SLOPE REQUIREMENTS.
- ⑦ TOP FRONT OF GUTTER SHALL BE CONSTRUCTED FLUSH WITH PROPOSED ADJACENT PAVEMENT ELEVATION. TOP 1.5" OF THE GUTTER FACE MUST BE A FORMED EDGE. PAR GUTTER SHALL NOT BE OVERLAD.
- ⑧ SHOULD BE USED AT VERTICALLY CONSTRAINED AREAS WHEN AT A DRAINAGE HIGH POINT OR SUPER ELEVATED ROADWAY SEGMENTS.
- ⑨ DRILL AND GROUT NO. 4 EPOXY-COATED 18" LONG TIE BARS AT 30" CENTER TO CENTER INTO EXISTING CONCRETE PAVEMENT 1" MINIMUM FROM ALL JOINTS.
- ⑩ HELPS PROVIDE TWO SEPARATE RAMPS, REDUCES THE DOME SETBACK LENGTH AND MINIMIZES DIRECTIONAL CURB. THIS RADIUS DESIGN CLOSELY FOLLOWS THE TURNING VEHICLE PATH WHILE OPTIMIZING CURB RAMP LENGTH.
- ⑪ CURB EXTENSIONS SHOULD BE USED IN VERTICALLY CONSTRAINED AREAS, USUALLY IN DOWNTOWN ROADWAY SEGMENTS WHERE ON-STREET PARKING IS AVAILABLE. CURB EXTENSIONS SHOULD BE CONSIDERED FOR APS INTERSECTIONS WHERE SPACE IS LIMITED. PUSH BUTTONS MUST MEET APS CRITERIA AS DESCRIBED IN THE PUSH BUTTON LOCATION DETAIL SHEET.


PAVED FLARES  
ADJACENT TO WALKABLE SURFACEPAVED FLARES  
ADJACENT TO NON-WALKABLE SURFACE

GRADED FLARES




RETURNED CURB (4)


TYPICAL SIDE TREATMENT OPTIONS (3) (10)



3" MINIMUM CURB HEIGHT, 4" PREFERRED  
(MEASURED AT FRONT FACE OF CURB)  
FOR A MIN. 6" LENGTH (MEASURED ALONG FLOW LINE)




DETECTABLE EDGE WITH (7)  
CURB AND GUTTER

RADIAL DETECTABLE WARNING



RECTANGULAR DETECTABLE WARNING

## DETECTABLE EDGE WITHOUT CURB AND GUTTER

PEDESTRIAN APPROACH  
NOSE DETAIL  
(FOR RETURNED CURB  
SIDE TREATMENT)

## NOTES:

INTERMEDIATE CURB HEIGHTS TAPER SHALL RISE AT 8-10% TO A MINIMUM 3 INCH CURB HEIGHT. INCREASE CURB TAPER LENGTH AT LESS THAN 8% OR REDUCE INTERMEDIATE CURB HEIGHT TO 2+ INCHES IF NECESSARY TO MATCH ADJACENT BOULEVARD OR SIDEWALK GRADES.

SEE STANDARD PLATE 7038 AND THIS SHEET FOR ADDITIONAL DETAILS ON DETECTABLE WARNING.

A WALKABLE SURFACE IS DEFINED AS A PAVED SURFACE ADJACENT TO A CURB RAMP WITHOUT RAISED OBSTACLES THAT COULD MISTAKENLY BE TRaversed BY A USER WHO IS VISUALLY IMPAIRED.

CONCRETE FLARE LENGTHS ADJACENT TO NON-WALKABLE SURFACES SHOULD BE LESS THAN 8' LONG MEASURED ALONG THE RAMPS FROM THE BACK OF CURB.

- ① 0" CURB HEIGHT. SEE INSET A ON SHEET 3 OF 6.
- ② FULL CURB HEIGHT.
- ③ SIDE TREATMENTS ARE APPLICABLE TO ALL RAMP TYPES AND SHOULD BE IMPLEMENTED AS NEEDED AS FIELD CONDITIONS DICTATE. THE ENGINEER SHALL DETERMINE THE RAMP SIDE TREATMENTS BASED ON MAINTENANCE OF BOTH ROADWAY AND SIDEWALK, ADJACENT PROPERTY CONSIDERATIONS, AND MITIGATING CONSTRUCTION IMPACTS.
- ④ TYPICALLY USED FOR MEDIANs AND ISLANDs.
- ⑤ WHEN NO CONCRETE FLARES ARE PROPOSED, THE CONCRETE WALK SHALL BE FORMED AND CONSTRUCTED PERPENDICULAR TO THE EDGE OF ROADWAY. MAINTAIN 3" MAX. BETWEEN EDGE OF DOMES AND EDGE OF CONCRETE.
- ⑥ IF NO CURB AND GUTTER IS PLACED IN RURAL SECTIONS, DETECTABLE WARNINGS SHALL BE PLACED 1' FROM THE EDGE OF BITUMINOUS ROADWAY AND/OR BITUMINOUS SHARED-USE PATH TO PROVIDE VISUAL CONTRAST.
- ⑦ ALL CONSTRUCTED CURBS MUST HAVE A CONTINUOUS DETECTABLE EDGE FOR THE VISUALLY IMPAIRED. THIS DETECTABLE EDGE REQUIRES DETECTABLE WARNINGS WHEREVER THERE IS ZERO-INCH HIGH CURB. CURB TAPERS ARE CONSIDERED A DETECTABLE EDGE WHEN THE TAPER STARTS WITHIN 3" OF THE EDGE OF THE DETECTABLE WARNINGS, AND UNIFORMLY RISES TO A 3-INCH MINIMUM CURB HEIGHT. ANY CURB NOT PART OF A CURB TAPER AND LESS THAN 3 INCHES IN HEIGHT IS NOT CONSIDERED A DETECTABLE EDGE AND THEREFORE IS NOT COMPLIANT WITH ACCESSIBILITY STANDARDS.
- ⑧ DRILL AND GROUT 1 - NO. 4 12" LONG REINFORCEMENT BAR (EPOXY COATED) WITH 3" MIN. COVER. REINFORCEMENT BARS ARE NOT NEEDED IF THE APPROACH NOSE IS POURED INTEGRAL WITH THE V CURB.
- ⑨ DRILL AND GROUT 2 - NO. 4 12" LONG REINFORCEMENT BARS (EPOXY COATED) WITH 3" MIN. COVER. REINFORCEMENT BARS ARE NOT NEEDED IF THE APPROACH NOSE IS POURED INTEGRAL WITH THE CURB AND GUTTER.
- ⑩ SIDE TREATMENT EXAMPLES SHOWN ARE WHEN THE INITIAL LANDING IS APPROXIMATELY LEVEL WITH THE FULL HEIGHT CURB (I.E. 6' LONG RAMP FOR 6" HIGH CURB). WHEN THE INITIAL LANDING IS MORE THAN 1" BELOW FULL HEIGHT CURB REFER TO SHEETS 1 & 2 TO MODIFY THE CURB HEIGHT TAPERS AND MAINTAIN POSITIVE BOULEVARD DRAINAGE. CONSTRUCT THESE TAPERS AT 0"-3" AT 8-10%, THEN LESS THAN 5% FROM 3" CURB TO FULL CURB HEIGHT.
- ⑪ NEAREST EDGE OF DETECTABLE WARNING SURFACES SHALL BE PLACED 12' MINIMUM TO 15' MAXIMUM FROM THE NEAREST RAIL. FOR SKewed RAILWAYS IN NO INSTANCE SHALL THE DETECTABLE WARNING BE CLOSER THAN 12' MEASURED PERPENDICULAR TO THE NEAREST RAIL.
- ⑫ WHEN PEDESTRIAN GATES ARE PROVIDED, DETECTABLE WARNING SURFACES SHALL BE PLACED ON THE SIDE OF THE GATES OPPOSITE THE RAIL, 2' FROM THE APPROACHING SIDE OF THE GATE ARM. THIS CRITERIA GOVERS OVER NOTE (11).
- ⑬ CROSSING SURFACE SHALL EXTEND 2' MINIMUM PAST THE OUTSIDE EDGE OF WALK OR SHARED-USE PATH.
- ⑭ 3' FOR MEDIANs AND SPLITTER ISLANDs. NOSE CAN BE REDUCED TO 2' ON FREE RIGHT ISLANDs.
- ⑮ SIDEWALK TO BE PLACED 8.75' MIN. FROM THE FACE OF CURB/PROJECTED FACE OF CURB. THIS ENSURES MIN. CLEARANCE BETWEEN THE SIDEWALK AND GATE ARM COUNTERWEIGHT SUPPORTs.
- ⑯ CONSTRUCT WITH EXPANSION MATERIAL PER MNDOT SPECIFICATION 3702 TYPES A-E. EXPANSION MATERIAL SHALL MATCH FULL HEIGHT OF ADJACENT CONCRETE.


|                      |   |
|----------------------|---|
| REVISION:            |   |
| APPROVED: 11-04-2021 | Jeffrey Perkins<br>JEFFREY PERKINS<br>OPERATIONS DIVISION |




STANDARD PLAN 5-297.250 4 OF 6

APPROVED: 11-04-2021  
REVISED: *Tom S.*


## PEDESTRIAN CURB RAMP DETAILS



V CURB ADJACENT TO LANDSCAPE  
CURB WITHIN SIDEWALK LIMITS




V CURB ADJACENT TO LANDSCAPE  
CURB OUTSIDE SIDEWALK LIMITS




V CURB INTERSECTION


| CONCRETE CURB DESIGN V |              |
|------------------------|--------------|
| CURB HEIGHT H          | CURB WIDTH W |
| < 6"                   | 4"           |
| ≥ 6"                   | 6"           |




V CURB ADJACENT TO BUILDING  
OR BARRIER




TRANSITION PANEL (4) (5)




INSET A




PLAN VIEW



PLAN VIEW



SIGNAL PEDESTAL & PUSH BUTTON (V-CURB)



SECTION A-A

PUSH BUTTON STATION (V-CURB)

#### NOTES:

A WALKABLE FLARE IS AN 8-10% CONCRETE FLARE THAT IS REQUIRED WHEN THE FLARE IS ADJACENT TO A WALKABLE SURFACE, OR WHEN THE PEDESTRIAN PATH OF TRAVEL OF A PUSH BUTTON TRAVERSES THE FLARE.

ALL V CURB CONTRACTION JOINTS SHALL MATCH CONCRETE WALK JOINTS.

WHERE RIGHT-OF-WAY ALLOWS, USE OF V CURB SHOULD BE MINIMIZED. GRADING ADJACENT TURF OR SLOPING ADJACENT PAVEMENT IS PREFERRED.

V CURB SHALL BE PLACED OUTSIDE THE SIDEWALK LIMITS WHEN RIGHT OF WAY ALLOWS.

V CURB NEXT TO BUILDING SHALL BE A 4" WIDTH AND SHALL MATCH PREVIOUS TOP OF SIDEWALK ELEVATIONS.

(1) END TAPER AT TRANSITION SECTION SHALL MATCH INPLACE SIDEWALK GRADES.

(2) ALL V CURB SHALL MATCH BOTTOM OF ADJACENT WALK.

(3) CONSTRUCT USING APPROVED EXPANSION MATERIAL PER MNDOT TYPE A-E EXPANSION. LEAVE A MINIMUM 1/2" TOP GAP AND SEAL WITH MNDOT APPROVED SILICONE PER MNDOT SPEC 3722.

(4) THE MAX. RATE OF CROSS SLOPE TRANSITIONING IS 1' LINEAR FOOT OF SIDEWALK PER HALF PERCENT CROSS SLOPE. WHEN PAR WIDTH IS GREATER THAN 6' OR THE RUNNING SLOPE IS GREATER THAN 5%, DOUBLE THE CALCULATED TRANSITION LENGTH.

(5) TRANSITION PANELS ARE TO ONLY BE USED AFTER THE RAMP, OR IF NEEDED, LANDING ARE AT THE FULL CURB HEIGHT (TYPICAL SECTION).

(6) EXISTING CROSS SLOPE GREATER THAN 2.0%.

#### LEGEND

THESE LONGITUDINAL SLOPE RANGES SHALL BE THE STARTING POINT. IF SITE CONDITIONS WARRANT, LONGITUDINAL SLOPES UP TO 8.3% OR FLATTER ARE ALLOWED.

(S) INDICATES PEDESTRIAN RAMP - SLOPE SHALL BE BETWEEN 5.0% MINIMUM AND 8.3% MAXIMUM IN THE DIRECTION SHOWN AND THE CROSS SLOPE SHALL NOT EXCEED 2.0%.

(L) LANDING AREA - 4' X 4' MIN. (5' X 5' MIN. PREFERRED) DIMENSIONS AND MAX 2.0% SLOPE IN ALL DIRECTIONS. LANDING SHALL BE FULL WIDTH OF INCOMING PARS.



(T) TRANSITION PANEL(S) - TO BE USED FOR TRANSITIONING THE CROSS-SLOPE OF A RAMP TO THE EXISTING WALK CROSS-SLOPE. RATE OF TRANSITION SHOULD BE 0.5% PER 1 LINEAR FOOT OF WALK. SEE THIS SHEET FOR ADDITIONAL INFORMATION.

|  |
|--|
| REVISION:                              |
| APPROVED: 11-04-2021                   |
|  |
| JEFF D. PERKINS<br>OPERATIONS DIVISION |








|                         |   |
|-------------------------|---|
| STANDARD PLAN 5-297.250 | 5 OF 6                                      |
| APPROVED: 11-04-2021    | REVISED:                                    |
|                         | THOMAS S. TYRBICKI<br>STATE DESIGN ENGINEER |


#### PEDESTRIAN CURB RAMP DETAILS




CURB LINE AND ROAD CROSSING ADJUSTMENTS

EXPANSION MATERIAL PLACEMENT  
FOR CONCRETE ROADWAYSCURB LINE REINFORCEMENT ④  
PLACEMENT ON BITUMINOUS ROADWAYSSECTION VIEW A-A  
THICKENED SECTION  
THROUGH CURB RAMP FLARES

FLOW LINE PROFILE "TABLE" - TWIN PERPENDICULARS



FLOW LINE PROFILE "TABLE" - FAN



FLOW LINE PROFILE RAISE - TWIN PERPENDICULARS



FLOW LINE PROFILE RAISE - FAN

## GENERAL NOTES:

"TABLING" OF CROSSWALKS MEANS MAINTAINING LESS THAN 2% CROSS SLOPE WITHIN A CROSSWALK, IS REQUIRED WHEN A ROADWAY IS IN A STOP OR YIELD CONDITION AND THE PROJECT SCOPE ALLOWS.

RECONSTRUCTION PROJECTS: ON FULL PAVEMENT REPLACEMENT PROJECTS "TABLING" OF ENTIRE CROSSWALK SHALL OCCUR WHEN FEASIBLE.


MILL & OVERLAY PROJECTS: "TABLING" OF FLOW LINES, IN FRONT OF THE PEDESTRIAN RAMP, IS REQUIRED WHEN THE EXISTING FLOW LINE IS GREATER THAN 2%. WARPING OF THE BITUMINOUS PAVEMENT CAN NOT EXTEND INTO THE THROUGH LANE. TABLE THE FLOW LINE TO 2% OR AS MUCH AS POSSIBLE WHILE ADHERING TO THE FOLLOWING CRITERIA:

- 1) 1.0% MIN. CROSS-SLOPE OF THE ROAD
- 2) 5.0% MAX. CROSS-SLOPE OF THE ROAD
- 3) "TABLE" FLOW LINE UP TO 4% CHANGE FROM EXISTING SLOPE IN FRONT OF PEDESTRIAN RAMP
- 4) UP TO 2% CHANGE IN FLOW LINE FROM EXISTING SLOPE BEYOND THE PEDESTRIAN CURB RAMP

STAND-ALONE ADA RETROFITS: FOLLOW MILL & OVERLAY CRITERIA ABOVE HOWEVER ALL PAVEMENT WARPING IS DONE WITH BITUMINOUS PATCHING ON BITUMINOUS ROADWAYS AND FULL-DEPTH APRON REPLACEMENT ON CONCRETE ROADWAYS.

RAISING OF CURB LINES SHOULD OCCUR IN VERTICALLY CONSTRAINED AREAS. RAISE THE CURB LINES ENOUGH TO ALLOW COMPLIANT RAMPS OR AS MUCH AS POSSIBLE WHILE ADHERING TO THE FOLLOWING CRITERIA:

- 1) 1.0% MIN. AND 5.0% MAXIMUM CROSS-SLOPE OF THE ROAD
- 2) 1.0% MIN. FLOW LINE (ON EITHER SIDE OF PEDESTRIAN RAMP) TO MAINTAIN POSITIVE DRAINAGE
- 3) 5.0% RECOMMENDED MAX. FLOW LINE
- 4) LONGITUDINAL THROUGH LANE ROADWAY TAPERS SHOULD BE 1" VERTICAL PER 15' HORIZONTAL

|   |
|---|
| REVISION:   |
| APPROVED: 11-04-2021  |
|  |
| JEFF D. PEL<br>OPERATIONS DIVISION  |





STANDARD PLAN 5-297.250

6 OF 6


APPROVED: 11-04-2021  
REVISED:THOMAS TYRICKI  
STATE DESIGN ENGINEER

PEDESTRIAN CURB RAMP DETAILS


SHEET 14 OF 53 SHEETS




CURB AND GUTTER REINFORCEMENT ③



CURB RAMP REINFORCEMENT DETAILS ②④




SEPARATE LANDING POUR REINFORCEMENT ①②




## NOTES:


- ① TO ENSURE RAMPS AND LANDINGS ARE PROPERLY CONSTRUCTED, ALL INITIAL LANDINGS AT A TOP OF A RAMPED SURFACE (RUNNING SLOPE GREATER THAN 2%) SHALL BE FORMED AND PLACED SEPARATELY IN AN INDEPENDENT CONCRETE POUR. FOLLOW SIDEWALK REINFORCEMENT DETAILS ON THIS SHEET FOR ALL SEPARATELY POURED INITIAL LANDINGS.
- ② DRILL AND GROUT NO. 4 12" LONG REINFORCEMENT BARS (EPOXY COATED) AT 36" MAXIMUM CENTER TO CENTER MINIMUM 12" SPACING FROM CONSTRUCTION JOINTS. BARS TO BE ADJUSTED TO MATCH RAMP GRADE. BARS TO BE PAID BY EACH.
- ③ DRILL AND GROUT 2 - NO. 4 X 12" LONG (6" EMBEDDED) REINFORCEMENT BARS (EPOXY COATED). REINFORCEMENT REQUIRED FOR ALL CONSTRUCTION JOINTS. BARS TO BE PAID BY EACH.
- ④ THIS CURB LINE REINFORCEMENT DETAIL SHALL BE USED ON BITUMINOUS ROADWAYS. FOR CONCRETE ROADWAYS, SEE NOTE 6.
- ⑤ CONSTRUCT WITH EXPANSION MATERIAL PER MNDOT SPECIFICATION 3702 TYPES A-E. EXPANSION MATERIAL SHALL MATCH FULL HEIGHT OF ADJACENT CONCRETE.
- ⑥ USE AN APPROVED TYPE F (1/4 INCH THICK) SEPARATION MATERIAL. SEPARATION MATERIAL SHALL MATCH FULL HEIGHT DIMENSION OF ADJACENT CONCRETE.




CONTOURING ROAD CUTS




ROUNDING SHOULDERS AND BACKSLOPES




SHAPING FOR DRAINAGE ALONG THE TOE OF FILL SLOPES





SHAPING AND TOPSOILING INSLOPES




SHAPING ADJACENT TO CURBS WHEN SOD IS PLACED




PLAN VIEW

SODDED DITCH CROSS SECTION  
WHERE FRONT OR BACK SLOPE IS FLAT (LESS THAN 1/2''/FT.),  
FIRST NOTCH DITCH AND THEN PROVIDE ROUNDING.


SODDED DITCH DETAILS



PLAN VIEW



SECTION A-A



SODDED FLUME DETAILS

|  |  |
|--|--|
| REVISION:  |  |
| APPROVED: 2-28-2017                              |  |
| <i>John Elvin</i><br>CHIEF ENVIRONMENTAL OFFICER |  |

## NOTES:

SEE SPEC. 2575.3 FOR ADDITIONAL INFORMATION.  
① CONSTRUCT TAPER AS DIRECTED BY THE ENGINEER.







STANDARD PLAN 5-297.404


1 OF 3

APPROVED: 2-28-2017  
REVISED:


PERMANENT EROSION CONTROL  
ALONG ROADWAYS, DITCHES AND FLUMES



### BLANKET STAPLE PATTERN





DITCH BLANKET STAPLE DETAIL



### NOTES:

- ① USE CHECK SLOT DETAIL (NO ALTERNATES).
- ② PLACE DOUBLE ROW OF STAPLES STAGGERED 4" APART AND 4" ON CENTER.
- ③ USE 6" X 6" TRENCH TO PLACE BLANKET. PLACE SINGLE ROW OF STAPLES ON TOP AND TRENCH SIDES AT 12" SPACING. BACKFILL TRENCH WITH SOIL AND TAMP.
- ④ PLACE SINGLE ROW OF STAPLES AT 12" SPACING.
- ⑤ USE STAPLE CHECK FOR CHANNEL SLOPES LESS THAN 2.5% GRADE AT 100' INTERVALS. PLACE DOUBLE ROW OF STAPLES STAGGERED 4" APART AND AT 4" SPACING.
- ⑥ USE BLANKET CHECKS FOR THE FOLLOWING SLOPES:  
2.5% - 3% 100' INTERVALS  
32-5% 50' INTERVALS  
5% - 7% 25' INTERVALS
- ⑦ CRITICAL POINTS SHALL BE SECURED WITH PROPER STAPLE PATTERNS.



**GENERAL BLANKET INSTALLATION REQUIREMENTS**  
REPP = ROLLED EROSION PREVENTION PRODUCT.  
PREPARE SOIL AS PER SPECIFICATION 2574.  
LAY PARALLEL OR PERPENDICULAR TO THE DIRECTION OF WATER FLOW.  
OVERLAP ADJACENT STRIP EDGES A MINIMUM OF 4".  
OVERLAP BLANKET 6" (MINIMUM) AT EACH END. OVERLAP BOTTOM END OF UPPER BLANKET OVER TOP END OF LOWER BLANKET. STAPLE ALONG OVERLAP EVERY 1.5".  
THE UPPERMOST BLANKET OF ALL SLOPE APPLICATIONS MUST START IN A CHECK SLOT. IF SLOPE LENGTH (L) IS 100' OR GREATER, INSERT BLANKET INTO A CHECK SLOT  $\frac{1}{3}$  FROM THE BOTTOM OF THE SLOPE.

|   |
|---|
| REVISION:   |
| APPROVED: JANUARY 8, 2020   |
| <br>MARNI KARNOWSKI<br>CHIEF ENVIRONMENTAL OFFICER |





STANDARD PLAN 5-297.404

3 OF 3




  
THOMAS TYRBICKI  
STATE DESIGN ENGINEER

APPROVED: 1-8-2020  
REVISED:


**PERMANENT EROSION CONTROL**  
**REPP (BLANKET) STAPLE PATTERN FOR SLOPES**



### SEDIMENT CONTROL LOGS



### FILTER BERMS



### NOTES:

REPP = ROLLED EROSION PREVENTION PRODUCT.

SEE SPECS. 2573, 3149, 3874, 3882, 3885, 3886, AND 3897.

① SPACE BETWEEN STAKES SHALL BE A MAXIMUM OF 1' FOR DITCH CHECKS OR 2' FOR OTHER APPLICATIONS.

② PLACE STAKES AS NEEDED TO PREVENT MOVEMENT OF SEDIMENT CONTROL LOGS PLACED ON SLOPES OR AS NEEDED DUE TO OTHER FACTORS. STAKES SHALL BE INCIDENTAL.

③ TO BE USED FOR CRITICAL PERIMETER CONTROL AREAS WHERE STANDING WATER OCCURS (6" MAXIMUM DEPTH). BALES SHALL CONSIST OF TYPE 1 MULCH OF APPROXIMATELY 14" X 18" X 36" LONG. BALES SHALL BE PLACED ON EDGE AND BUTTED TIGHT TO ADJACENT BALES.


④ INSTEAD OF TRENCHING, PLACE BALE ON THE REPP (BLANKET) AND WRAP BLANKET AROUND THE BALE. PLACE STAKE THROUGH BALE AND BLANKET.

|   |
|---|
| REVISION:   |
| APPROVED: JANUARY 8, 2020   |
| <br>MARNI KARNOWSKI<br>CHIEF ENVIRONMENTAL OFFICER |




|   |          |
|---|----------|
| STANDARD PLAN 5-297.405   | 2 OF 8   |
| APPROVED: 1-8-2020  | REVISED: |
| <br>THOMAS TYRBICKI<br>STATE DESIGN ENGINEER |          |



TEMPORARY SEDIMENT CONTROL  
FILTER BERMS, SEDIMENT CONTROL LOGS, AND BALE BARRIERS




ROCK DITCH CHECKS  
FILTER BERMS TYPE 3 (ROCK WEEPER) OR FILTER TYPE 5 (ROCK) ③  
FOR USE ON ROUGH-GRADED AREAS  
ONLY FOR USE OUTSIDE CLEAR ZONE ②



DITCH CHECK SPACING  
FOR ALL FILTER BERM TYPES



SEDIMENT CONTROL LOG TYPE REPP (BLANKET) SYSTEM ④



SEDIMENT CONTROL LOG TYPE WOOD FIBER, OR TYPE COMPOST ⑤  
FOR USE ON ROUGH GRADED AREAS

NOTES:

REPP = ROLLED EROSION PREVENTION PRODUCT.

SEE SPECS. 2573, 3601, 3733, 3885, 3886 & 3889.

FOR DITCH CHECKS, PLACE SEDIMENT CONTROL LOG PERPENDICULAR TO FLOW AND IN A CRESCENT SHAPE WITH THE ENDS FACING UPSTREAM.

APPROXIMATE SPACING BETWEEN EACH DITCH CHECK SHOULD BE DETERMINED FROM THE FOLLOWING SPACING FORMULA:

$$\text{APPROXIMATE SPACING OF DITCH CHECKS (FT.)} = Y = \frac{\text{DITCH CHECK HEIGHT (FT.)}}{\% \text{ CHANNEL SLOPE}} \times 100$$

① POINT "A" MUST BE A MINIMUM OF 6" HIGHER THAN POINT "B" TO ENSURE THAT WATER FLOWS OVER THE DIKE AND NOT AROUND THE ENDS.

② ROCK DITCH CHECKS PLACED WITHIN THE CLEAR ZONE ARE TO BE 18" OR LESS IN HEIGHT. A 1:6 APPROACH AND DEPARTURE SLOPE SHALL BE PROVIDED.

③ DITCH GRADE 3% - 5%, MAX. FLOW VELOCITY 12 FT./SEC.

④ DITCH GRADE 1.5% - 3%, MAX. FLOW VELOCITY 4.5 FT./SEC.

⑤ DITCH GRADE 1.5% - 3%, MAX. FLOW VELOCITY 1.5 FT./SEC.

|   |
|---|
| REVISION:   |
| APPROVED: JANUARY 8, 2020   |
| <br>MARNI KARNOWSKI<br>CHIEF ENVIRONMENTAL OFFICER |




STANDARD PLAN 5-297.405

3 OF 8


APPROVED: 1-8-2020  
REVISED:  
  
THOMAS TYRBICKI  
STATE DESIGN ENGINEER

TEMPORARY SEDIMENT CONTROL  
DITCH CHECK




FILTER BAG INSERT ③





(CAN BE INSTALLED IN ANY INLET TYPE WITH OR WITHOUT A CURB BOX)



ROCK LOG/COMPOST LOG




TUBE RISER

SECTION  
(UP POSITION)SECTION  
(DOWN POSITION)

SEDIMENT CONTROL INLET HAT

NOTE:  
THE SEDIMENT CONTROL BARRIER SHALL BE A METAL OR PLASTIC/POLYETHYLENE RISER SIZED TO FIT INSIDE THE CATCH BASIN/MANHOLE; HAVE PERFORATIONS TO ALLOW FOR WATER INFILTRATION; HAVE AN OVERFLOW OPENING, FLANGES AND A LID/COVER.

SILT FENCE RING AND ROCK FILTER BERM  
USE WHERE INLET DRAINS IN AN AREA WITH SLOPES AT 1:3 OR LESS

NOTES:  
SEE SPECS. 2573, 3137, & 3886.

DEVICES MUST BE ADJUSTED ACCORDINGLY AS TO NOT CAUSE FLOODING ON ROADWAY THAT WOULD IMPEDE TRAFFIC FLOW.

- ① ALL GEOTEXTILE USED FOR INLET PROTECTION SHALL BE MONOFILAMENT IN BOTH DIRECTIONS, MEETING SPEC. 3886.
- ② FINISHED SIZE, INCLUDING POCKETS WHERE REQUIRED SHALL EXTEND A MINIMUM OF 10 INCHES AROUND THE PERIMETER TO FACILITATE MAINTENANCE OR REMOVAL.
- ③ INSTALLATION NOTES:  
DO NOT PLACE FILTER BAG INSERT IN INLETS SHALLOWER THAN 30 INCHES, MEASURED FROM THE BOTTOM OF THE INLET TO THE TOP OF THE GRATE. THE PLACED BAG SHALL HAVE A MINIMUM SIDE CLEARANCE OF 3 INCHES BETWEEN THE INLET WALLS AND THE BAG, MEASURED AT THE BOTTOM OF THE OVERFLOW HOLES. WHERE NECESSARY THE CONTRACTOR SHALL CLINCH THE BAG, USING PLASTIC ZIP TIES, TO ACHIEVE THE 3 INCH SIDE CLEARANCE.
- ④ FLAP POCKETS SHALL BE LARGE ENOUGH TO ACCEPT WOOD 2 INCH X 4 INCH OR USE A ROCK SOCK OR SAND BAGS IN PLACE OF THE FLAP POCKETS.
- ⑤ SOCK HEIGHT MUST NOT BE SO HIGH AS TO SLOW DOWN WATER FILTRATION TO CAUSE FLOODING OF THE ROADWAY.
- ⑥ GEOTEXTILE SOCK BETWEEN 4-10 FEET LONG AND 4-6 INCH DIAMETER. SEAM TO BE JOINED BY TWO ROWS OF STITCHING WITH A PLASTIC MESH BACKING OR PROVIDE A HEAT BONDED SEAM (OR APPROVED EQUIVALENT). FILL ROCK LOG WITH OPEN GRADED AGGREGATE CONSISTING OF SOUND DURABLE PARTICLES OF COARSE AGGREGATE CONFORMING TO SPEC. 3137 TABLE 3137-1; CA-3 GRADATION.

|                             |  |  |  |
|-----------------------------|--|--|--|
| REVISION:                   |  |  |  |
| APPROVED: 2-28-2017         |  |  |  |
|                             |  |  |  |
| CHIEF ENVIRONMENTAL OFFICER |  |  |  |





STANDARD PLAN 5-297.405

4 OF 8

APPROVED: 2-28-2017  
REVISED:

TEMPORARY SEDIMENT CONTROL  
STORM DRAIN INLET PROTECTION

**J-HOOK INSTALLATION**


|                     |                    |
|---------------------|--------------------|
| REVISION:           |                    |
| APPROVED: 2-28-2017 | <i>John E. ...</i> |

**STANDARD PLAN 5-297.405****6 OF 8**

*Tom S...*  
STATE DESIGN ENGINEER

APPROVED: 2-28-2017  
REVISED:**TEMPORARY SEDIMENT CONTROL**  
**SILT FENCE**

SHEET 20 OF 53 SHEETS

**LOCATION AT TOE OF ROADWAY EMBANKMENT****NOTES:**

SEE SPECS. 2573, 3149 &amp; 3886.

- ① COARSE FILTER AGGREGATE (SPEC. 3149) SHALL BE INCIDENTAL.
- ② TO PROTECT AREAS FROM SHEET FLOW. MAXIMUM CONTRIBUTING AREA: 1 ACRE.
- ③ TO PROTECT AREAS FROM SHEET FLOW. MAXIMUM CONTRIBUTING AREA: 0.25 ACRE.
- ④ WATER COURSE FLOW VELOCITY: STANDING. CONTRIBUTING SLOPE AREA: 1/2 ACRE.
- ⑤ WATER COURSE FLOW VELOCITY: 1 TO 7 FT./SEC. CONTRIBUTING SLOPE AREA: 1. ACRE.
- ⑥ WATER COURSE FLOW VELOCITY: 8 TO 15 FT./SEC. CONTRIBUTING SLOPE AREA: 3 ACRES.

| NOTES & GUIDELINES  |  | PAVEMENT MARKING SYMBOLS AND MATERIALS LEGEND   | TRAFFIC CONTROL INDEX |           |             |             |                                       |    |                         |    |  |    |  |    |  |    |                                  |
|---|--|---|-----------------------|-----------|-------------|-------------|---------------------------------------|----|-------------------------|----|--|----|--|----|--|----|----------------------------------|
| <b>GENERAL INFORMATION:</b>   |  | <p>1. ALL DISTANCES ARE APPROXIMATE.</p> <p>2. WHEN WORK IS BEING PERFORMED WITHIN 6 FEET OF CSAH 17 TRAFFIC THE CONTRACTOR SHALL PROVIDE A SHORT TERM LANE CLOSURE. LANE CLOSURES ON CSAH 17 WILL NOT BE ALLOWED 6AM TO 9AM SOUTHBOUND AND 3PM TO 6PM NORTHBOUND.</p> <p>3. LONGITUDINAL DROPOFFS SHALL BE PROTECTED AS REQUIRED IN THE "MINNESOTA TEMPORARY TRAFFIC CONTROL FIELD MANUAL".</p> <p>4. IF THE CONTRACTOR DECIDES TO PERFORM THE CONSTRUCTION WORK IN A SEQUENCE OTHER THAN SHOWN IN THIS TRAFFIC CONTROL PLAN THE CONTRACTOR SHALL PROVIDE COMPLETE REVISED TRAFFIC CONTROL PLANS TO BE APPROVED BY THE ENGINEER.</p>   |                       |           |             |             |                                       |    |                         |    |  |    |  |    |  |    |                                  |
| <b>SIGNING:</b>   |  | <p>1. ALL TEMPORARY SIGNS ARE REQUIRED TO BE CRASHWORTHY PER THE AASHTO MANUAL FOR ASSESSING SAFETY HARDWARE 2016 (MASH-2016). TEMPORARY SIGN STRUCTURES THAT ARE CRASHWORTHY UNDER THE NATIONAL COOPERATIVE HIGHWAY RESEARCH PROGRAM REPORT 350 (NCHRP-350) MAY BE USED PROVIDED THE DEVICES WERE ACQUIRED BY THE CONTRACTOR PRIOR TO DECEMBER 31ST, 2019. THE MINNESOTA TYPE "C" AND "D" BRACED LEG U-CHANNEL (KNEE BRACE) SIGN SUPPORT IS NOT ALLOWED.</p> <p>2. THE CONTRACTOR SHALL COORDINATE THE INSTALLATION OF THE FINAL SIGNS TO ASSURE THAT THE FINAL SIGNS ARE PLACED AS NEEDED, OR PROVIDE TEMPORARY SIGNING UNTIL THE FINAL SIGNING IS PLACED.</p> <p>3. WHEN MULTIPLE GROUND MOUNTED SIGN STRUCTURES ARE PLACED ADJACENT TO EACH OTHER THERE SHOULD BE NO MORE THAN 2 POSTS WITHIN 84" OF EACH OTHER. WHEN THIS SPACING CAN NOT BE MAINTAINED, THEN SIGN STRUCTURES SHALL BE OFFSET, AND STAGGERED WITH A MINIMUM OF 4' BETWEEN SIGN STRUCTURES BOTH LATERALLY AND LONGITUDINALLY. EXAMPLE SHOWS DETOUR SIGNAGE, BUT THIS REQUIREMENT APPLIES TO ALL SIGNAGE.</p> <p>4. WHEN A SIGN OR BARRICADE IS ORIENTED SUCH THAT VISIBILITY TO ROAD USERS INCLUDING BIKES AND PEDESTRIANS IS REDUCED ENOUGH TO CAUSE A HAZARD, DELINEATE THE SIGN/BARRICADE WITH APPROPRIATE DEVICES.</p> <p>5. TEMPORARY SIGNS SHALL BE PLACED SUCH THAT OBSTACLES DO NOT BLOCK THEM FROM BEING VIEWED BY APPROACHING ROAD USERS. OBSTACLES MAY INCLUDE, BUT ARE NOT LIMITED TO, LIGHT POLES, TREES, SIGNS, AND BUILDINGS.</p> <p>6. TEMPORARY SIGNS SHALL BE PLACED AND ORIENTED APPROXIMATELY AS SHOWN IN THE PLAN, AT RIGHT ANGLES TO DIRECTION OF AND FACING THE TRAFFIC THEY ARE INTENDED TO SERVE, UNLESS OTHERWISE SPECIFIED.</p> <p>7. LONGITUDINAL DROPOFFS SHALL BE SIGNED AS SHOWN IN THE "MINNESOTA TEMPORARY TRAFFIC CONTROL FIELD MANUAL" PAGES (6K-aj) THRU (6K-al) UNLESS OTHERWISE SPECIFIED IN THESE PLANS.</p> <p>8. AFTER REMOVAL OF SIGN AND/OR SIGN BASE, BACK FILL, COMPACT, AND LEVEL SOIL TO MATCH SURROUNDING SOIL.</p> |                       |           |             |             |                                       |    |                         |    |  |    |  |    |  |    |                                  |
| <b>PAVEMENT MARKING:</b>  |  | <p>1. MASK OR REMOVE ANY CONFLICTING PAVEMENT MARKINGS AS SHOWN IN THE PLAN OR APPROVED BY THE ENGINEER.</p> <p>2. ALL TEMPORARY PAVEMENT MARKINGS SHALL BE WET REFLECTIVE. ALL PAVEMENT MARKINGS IN TAPERS AND TRANSITIONS SHALL BE 6" IN WIDTH.</p> <p>3. SEE 2582 IN THE SPECIAL PROVISIONS FOR PAVEMENT MARKING SPOTTING RESPONSIBILITIES.</p>  |                       |           |             |             |                                       |    |                         |    |  |    |  |    |  |    |                                  |
| <b>CONSTRUCTION INFORMATION SIGNING:</b>  |  | <p>1. THE CONTRACTOR SHALL USE CONSTRUCTION INFORMATION SIGNING AS SHOWN IN THE PLAN WHICH ARE TO BE USED AS FOLLOWS:</p> <p>PLACE THE G20-X1 ADVANCE WORK NOTICE SIGN(S) 7 DAYS PRIOR TO THE PLANNED CLOSURE DATE.</p> <p>IF CONSTRUCTION INFORMATION SIGNING IS NO LONGER VISIBLE TO THE MOTORING PUBLIC ONCE WORK BEGINS, MOVE SAID SIGNING TO A SITE IN ADVANCE OF THE WORK ZONE OR CLOSURE AS SHOWN IN THE PLAN OR APPROVED BY THE ENGINEER.</p>   |                       |           |             |             |                                       |    |                         |    |  |    |  |    |  |    |                                  |
| PLOTTED/REVISED: 7/29/2022 12:24:32 PM<br>PATH & FILENAME: K:\019869-000\Cad\Plan\19869-000-C-TRAF-TITL.dgn<br>UPDATED 12/20/2021 |  | <p><b>PAVEMENT MARKING SYMBOLS AND MATERIALS LEGEND</b></p> <p><b>STRIPING KEY</b></p> <p>— SOLID LINE PAVEMENT MARKING WITH TEMPORARY RAISED PAVEMENT MARKERS AT 10' SPACES</p> <p>— BROKEN LINE-40' CYCLE (10' LINE, 30' GAP)</p> <p><b>BOX-REMOVABLE PREFORMED PLASTIC MARKING</b></p> <p>1ST DIGIT WIDTH: 4", 8", ETC.</p> <p>2ND DIGIT PATTERN: S - SOLID, B - BROKEN, T - DOTTED, D - DOUBLE SOLID, K - DOUBLE BROKEN, H - DOUBLE DOTTED</p> <p>3RD DIGIT COLOR: W - WHITE, Y - YELLOW, B - BLACK</p> <p>EXAMPLE: 4SW = 4" SOLID LINE WHITE REMOVABLE PREFORMED PLASTIC MARKING</p>   |                       |           |             |             |                                       |    |                         |    |  |    |  |    |  |    |                                  |
|   |  | <p><b>TRAFFIC CONTROL INDEX</b></p> <table border="1"> <thead> <tr> <th>SHEET NO.</th> <th>DESCRIPTION</th> </tr> </thead> <tbody> <tr> <td>21</td> <td>TEMPORARY TRAFFIC CONTROL TITLE SHEET</td> </tr> <tr> <td>22</td> <td>SIGN TABULATION</td> </tr> <tr> <td>23</td> <td>ANOKA COUNTY HIGHWAY DEPARTMENT SIGN DETAILS</td> </tr> <tr> <td>24</td> <td>ANOKA COUNTY HIGHWAY DEPARTMENT SIGN PLACEMENT</td> </tr> <tr> <td>25</td> <td>ANOKA COUNTY HIGHWAY DEPARTMENT TEMPORARY SIGN COVERING</td> </tr> <tr> <td>26</td> <td>STAGE 1</td> </tr> </tbody> </table>  |                       | SHEET NO. | DESCRIPTION | 21          | TEMPORARY TRAFFIC CONTROL TITLE SHEET | 22 | SIGN TABULATION         | 23 | ANOKA COUNTY HIGHWAY DEPARTMENT SIGN DETAILS | 24 | ANOKA COUNTY HIGHWAY DEPARTMENT SIGN PLACEMENT | 25 | ANOKA COUNTY HIGHWAY DEPARTMENT TEMPORARY SIGN COVERING      | 26 | STAGE 1                          |
| SHEET NO.   | DESCRIPTION  |   |                       |           |             |             |                                       |    |                         |    |  |    |  |    |  |    |                                  |
| 21  | TEMPORARY TRAFFIC CONTROL TITLE SHEET                        |   |                       |           |             |             |                                       |    |                         |    |  |    |  |    |  |    |                                  |
| 22  | SIGN TABULATION  |   |                       |           |             |             |                                       |    |                         |    |  |    |  |    |  |    |                                  |
| 23  | ANOKA COUNTY HIGHWAY DEPARTMENT SIGN DETAILS                 |   |                       |           |             |             |                                       |    |                         |    |  |    |  |    |  |    |                                  |
| 24  | ANOKA COUNTY HIGHWAY DEPARTMENT SIGN PLACEMENT               |   |                       |           |             |             |                                       |    |                         |    |  |    |  |    |  |    |                                  |
| 25  | ANOKA COUNTY HIGHWAY DEPARTMENT TEMPORARY SIGN COVERING      |   |                       |           |             |             |                                       |    |                         |    |  |    |  |    |  |    |                                  |
| 26  | STAGE 1  |   |                       |           |             |             |                                       |    |                         |    |  |    |  |    |  |    |                                  |
|   |  | <p><b>TRAFFIC CONTROL DEVICES &amp; SYMBOLS LEGEND</b></p> <table border="1"> <thead> <tr> <th>SYMBOL</th> <th>DESCRIPTION</th> </tr> </thead> <tbody> <tr> <td></td> <td>AREA CLOSED TO TRAFFIC / WORK AREA</td> </tr> <tr> <td></td> <td>CONSTRUCT UNDER TRAFFIC</td> </tr> <tr> <td></td> <td>TRAFFIC CONTROL SIGN</td> </tr> <tr> <td></td> <td>TYPE III BARRICADE =</td> </tr> <tr> <td></td> <td>FLASHING ARROW BOARD TYPE C = (4'X8' UNLESS OTHERWISE NOTED)</td> </tr> <tr> <td></td> <td>DRUM-LIKE CHANNELIZER (TYPE B) =</td> </tr> </tbody> </table>   |                       | SYMBOL    | DESCRIPTION |             | AREA CLOSED TO TRAFFIC / WORK AREA    |    | CONSTRUCT UNDER TRAFFIC |    | TRAFFIC CONTROL SIGN                         |    | TYPE III BARRICADE =                           |    | FLASHING ARROW BOARD TYPE C = (4'X8' UNLESS OTHERWISE NOTED) |    | DRUM-LIKE CHANNELIZER (TYPE B) = |
| SYMBOL  | DESCRIPTION  |   |                       |           |             |             |                                       |    |                         |    |  |    |  |    |  |    |                                  |
|   | AREA CLOSED TO TRAFFIC / WORK AREA                           |   |                       |           |             |             |                                       |    |                         |    |  |    |  |    |  |    |                                  |
|   | CONSTRUCT UNDER TRAFFIC                                      |   |                       |           |             |             |                                       |    |                         |    |  |    |  |    |  |    |                                  |
|   | TRAFFIC CONTROL SIGN   |   |                       |           |             |             |                                       |    |                         |    |  |    |  |    |  |    |                                  |
|   | TYPE III BARRICADE =   |   |                       |           |             |             |                                       |    |                         |    |  |    |  |    |  |    |                                  |
|   | FLASHING ARROW BOARD TYPE C = (4'X8' UNLESS OTHERWISE NOTED) |   |                       |           |             |             |                                       |    |                         |    |  |    |  |    |  |    |                                  |
|   | DRUM-LIKE CHANNELIZER (TYPE B) =                             |   |                       |           |             |             |                                       |    |                         |    |  |    |  |    |  |    |                                  |
|   |  | <p><b>CITY OF BLAINE, MN</b></p> <p><b>LEXINGTON AVENUE NE AT 131ST AVENUE NE</b></p> <p><b>INTERSECTION IMPROVEMENTS</b></p> <p><b>CONSTRUCTION STAGING &amp; TRAFFIC CONTROL</b></p>  |                       |           |             |             |                                       |    |                         |    |  |    |  |    |  |    |                                  |
|   |  | <p>REVISIONS</p> <table border="1"> <thead> <tr> <th>NO.</th> <th>DATE</th> <th>DESCRIPTION</th> </tr> </thead> <tbody> <tr> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> </tr> </tbody> </table> <p>HEREBY CERTIFY THAT THIS PLAN, SPECIFICATION, DIRECT SUPERVISION AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MINNESOTA.</p> <p>NICHOLAS E. HENTGES, PE<br/>DATE: 7/29/2022 LIC. NO: 44620</p>  |                       | NO.       | DATE        | DESCRIPTION |                                       |    |                         |    |  |    |  |    |  |    |                                  |
| NO.   | DATE   | DESCRIPTION   |                       |           |             |             |                                       |    |                         |    |  |    |  |    |  |    |                                  |
|   |  |   |                       |           |             |             |                                       |    |                         |    |  |    |  |    |  |    |                                  |
|   |  |   |                       |           |             |             |                                       |    |                         |    |  |    |  |    |  |    |                                  |
|   |  |   |                       |           |             |             |                                       |    |                         |    |  |    |  |    |  |    |                                  |
|   |  | <p>SHEET<br/>21<br/>OF<br/>53<br/>SHEETS</p>  |                       |           |             |             |                                       |    |                         |    |  |    |  |    |  |    |                                  |

| REVISIONS |      |
|-----------|------|
| NO.       | DATE |
|           |      |
|           |      |
|           |      |

I HEREBY CERTIFY THAT THIS PLAN, SPECIFICATION,  
OR REPORT WAS PREPARED BY ME OR UNDER MY  
DIRECT SUPERVISION AND THAT I AM A DULY  
LICENSED PROFESSIONAL ENGINEER UNDER THE  
LAWS OF THE STATE OF MINNESOTA.

NICHOLAS E. HENTGES, PE  
LIC. NO: 44620  
DATE: 7/29/2022

## CITY OF BLAINE, MN LEXINGTON AVENUE NE AT 131ST AVENUE NE INTERSECTION IMPROVEMENTS

### CONSTRUCTION STAGING & TRAFFIC CONTROL


SHEET  
22  
OF  
53  
SHEETS

#### GENERAL NOTES:


1. SIGN STRUCTURE TABULATIONS INDICATE SQUARE TUBE GROUND MOUNTED SIGN STRUCTURES THAT ARE MASH-16 COMPLIANT.
2. USE PRODUCTS FROM THE BASES FOR SQUARE TUBE SIGN STRUCTURES APPROVED/QUALIFIED PRODUCTS LIST FOR THE INDICATED SQUARE TUBE RISER POST SIZE. PLACE PER THE MANUFACTURER'S SPECIFICATIONS.
3. ALUMINUM STRINGERS SHALL BE USED FOR SIGNS 36 INCHES AND WIDER. SEE MANUFACTURER'S SPECIFICATIONS FOR SQUARE TUBE MOUNTING DETAILS. STRINGERS ON SINGLE POST ASSEMBLIES ARE REQUIRED TO BE AT LEAST 9 INCHES IN FROM THE EDGE OF THE SIGN.
4. UNLESS OTHERWISE INDICATED, USE 2-1/2 INCH RISER POSTS FOR GROUND MOUNTED SIGN STRUCTURES.

CITY OF BLAINE, MN  
LEXINGTON AVENUE NE  
131ST AVENUE NE  
INTERSECTION IMPROVEMENTS

PLOTTED/REV/ED: 7/29/2022 12:24:34 PM




LATERAL BRACE OR STRINGER  
SPICE DETAIL (EXPLODED VIEW)




A-FRAME BRACKET


(STEEL MN/DOT 3306 GALVANIZED PER MN/DOT 3394)




SECTION A-A




SECTION B-B



KNEE BRACE SPLICE




TYPICAL "A-FRAME" INSTALLATION  
TYPE "D" SIGNS



TYPICAL INSTALLATION 36" AND LARGER  
TYPE "C" SIGNS

ANOKA COUNTY HIGHWAY DEPARTMENT SIGN DETAILS



TYPICAL MOUNTING

(1) OFFSET STUB POST 1' TOWARD ROADWAY  
RELATIVE TO VERTICAL POST.

TYPE C & D SIGN  
STRUCTURAL DETAILS

CONSTRUCTION  
STAGING  
&  
TRAFFIC  
CONTROL

| NO. | DATE | DESCRIPTION |
|-----|------|-------------|
|     |      |             |
|     |      |             |
|     |      |             |
|     |      |             |



## CITY OF BLAINE, MN

## LEXINGTON AVENUE NE AT


## 131ST AVENUE NE

## INTERSECTION IMPROVEMENTS


### CONSTRUCTION STAGING & TRAFFIC CONTROL




### GROUND POST MOUNT SIGN INSTALLATION TYPICAL



### ISLAND MOUNT BREAK-AWAY SIGN INSTALLATION TYPICAL



### ISLAND MOUNT BREAK-AWAY SIGN SIGN INSTALLATION TYPICAL KEEP RIGHT/CLUSTER



## REVISIONS


NO. DATE

DESCRIPTION

I HEREBY CERTIFY THAT THIS PLAN SPECIFICATION,  
OR REPORT WAS PREPARED BY ME OR UNDER MY  
DIRECT SUPERVISION AND THAT I AM A DULY  
LICENSED PROFESSIONAL ENGINEER UNDER THE  
LAWS OF THE STATE OF MINNESOTA.

NICHOLAS E. HENTGES, PE

LIC. NO.: 44620

OVERLAY ASSEMBLY STEPS FOR COVERING COMPLETE OR PORTION OF EXTRUDED SIGN PANEL:

- 1) DRILL 1/4" HOLES ON THE SHEET ALUMINUM OVERLAYS IN ACCORDANCE WITH THE HOLE SPACING ON THE DIAGRAM. OUTSIDE HOLES SHALL NOT BE SPACED MORE THAN 24" APART.
- 2) ATTACH PLASTIC SPACER(S) (1/4" MIN THICKNESS, 3/8" I.D. AND 7/8" O.D.) WITH DOUBLE FACED TAPE, CENTERED BEHIND EACH DRILLED HOLE.
- 3) POSITION THE FIRST OVERLAY PANEL'S BOTTOM EDGE FLUSH WITH THE BOTTOM OF THE INPLACE EXTRUDED SIGN PANEL AND THE OVERLAY PANEL'S LOWER LEFT EDGE FLUSH WITH THE LOWER LEFT EDGE OF THE BOTTOM INPLACE EXTRUDED PANEL SECTION.
- 4) DRILL ALL OF THE OUTSIDE HOLES THROUGH THE INPLACE EXTRUDED SIGN PANEL AND ATTACH THE OVERLAY PANEL WITH SHEET METAL SCREWS.
- 5) DRILL THE INNER HOLES THROUGH THE INPLACE EXTRUDED SIGN PANEL AND ATTACH WITH SHEET METAL SCREWS AS SPECIFIED IN STEP 4 ABOVE.
- 6) ABUT THE NEXT OVERLAY PANEL TO THE FIRST ATTACHED OVERLAY PANEL AND PERFORM THE SAME WORK AS SPECIFIED IN STEPS 4 AND 5 ABOVE.
- 7) PLACE EACH ADDITIONAL OVERLAY PANEL AS SPECIFIED IN STEP 6 ABOVE.

NOTES FOR COVERING COMPLETE OR PORTION OF EXTRUDED SIGN PANEL:

- 1) THE CENTER SHEET METAL SCREWS SHALL BE SPACED AT 1/2 OF THE PANELS WIDTH.
- 2) IF THE SHEET ALUMINUM PANEL IS GREATER THAN 48" WIDE, THE SHEET METAL SCREWS SPACING SHALL BE NO GREATER THAN 24". IF THE SHEET ALUMINUM PANEL IS LESS THAN 24" WIDE, THERE SHALL BE NO INNER HOLES.
- 3) VERTICAL SPACING FOR THE MOUNTING HOLES IS 50% OF THE PANEL HEIGHT. IF THE PANEL IS LESS THAN 24" HIGH, THERE SHALL BE NO INNER HOLES.
- 4) HORIZONTAL SPACING FOR MOUNTING HOLES SHALL NOT BE LESS THAN 15" NOR MORE THAN 24".

GENERAL NOTES:

SIGN PANEL OVERLAYS SHALL BE MADE OF A RIGID MATERIAL. (SHEET ALUMINUM, PLYWOOD, CORRUGATED PLASTIC, OR OTHER MATERIAL AS APPROVED BY THE ENGINEER). THE INSTALLATION SHALL ALLOW ADEQUATE AIR FLOW BETWEEN THE OVERLAY PANEL AND THE INPLACE SIGN PANEL BY PROVIDING A MINIMUM SPACING OF 1/4" (1" MAXIMUM).

IF SHEET METAL SCREWS ARE USED WITH CORRUGATED PLASTIC, FENDER WASHERS SHALL BE PLACED BETWEEN SCREWS AND PANEL OVERLAY.

SPACERS SHALL BE A MATERIAL THAT WILL NOT HARM THE SIGN SHEETING FACE (SUCH AS PLASTIC OR RUBBER).

ALL COVERING MATERIAL, MOUNTING HARDWARE AND FASTENERS SHALL BE REMOVED WHEN PANEL OVERLAY IS REMOVED.

SIGN PANEL OVERLAYS USED TO COVER ALL OR PART OF A SIGN SHALL BE THE SAME COLOR AS THE BACKGROUND COLOR OF THE SIGN TO BE COVERED AND SHALL COVER ALL OF THE SIGN OR MESSAGE TO BE COVERED UNLESS SHOWN OTHERWISE IN THE PLAN.

TAPE SHALL NOT BE APPLIED TO THE SIGN SHEETING SURFACE. PRE-MASK OR APPLICATION TAPE SHALL BE REMOVED PRIOR TO EXPOSURE TO SUNLIGHT.

OVERLAY ASSEMBLY COVERING TYPE C OR D SIGN PANEL:

A RIGID OPAQUE PANEL OVERLAY, THE OVERLAY PANEL SHOULD BE APPROXIMATELY THE SAME SIZE AS THE SIGN PANEL SUCH THAT THE SIGN MESSAGE IS COMPLETELY COVERED

INPLACE SIGN


A SPACER IS REQUIRED IN ALL 4 CORNERS TO PROVIDE AIR FLOW GAP BETWEEN THE SIGN FACE AND OVERLAY PANEL

SPACERS SHALL ALLOW BETWEEN 1/4" TO 1" GAP AND BE A MATERIAL THAT WILL NOT HARM THE SIGN SHEETING FACE

ALL FASTENERS (SUCH AS bolts, HOOKS OR SCREWS) SHALL NOT TOUCH THE SIGN SHEETING FACE

THE OVERLAY PANEL SHALL BE ATTACHED TO THE SIGN STRUCTURE SUCH THAT IT WILL NOT MOVE DUE TO WIND

BOTTOM OF HANDLE SHALL BE SECURED TO PREVENT MOVEMENT. BOLT ON HANDLE SHALL BE ATTACHED TO OVERLAY PANEL AS TO NOT DAMAGE INPLACE SIGN PANEL.



CITY OF BLAINE, MN  
LEXINGTON AVENUE NE AT  
131ST AVENUE NE  
INTERSECTION IMPROVEMENTS

CONSTRUCTION  
STAGING  
&  
TRAFFIC  
CONTROL



## REVISIONS

NO. DATE

DESCRIPTION

NICHOLAS E. HENTGES, PE


LIC. NO: 44620

DATE: 7/29/2022

LIC. NO: 44620

CITY OF BLAINE, MN  
LEXINGTON AVENUE NE AT  
131ST AVENUE NE  
INTERSECTION IMPROVEMENTS

## ALIGNMENT PLAN



HORIZONTAL CONTROL FOR THIS PLAN IS  
ANOKA COUNTY COORDINATE SYSTEM,  
NAD 83 (1996 ADJUSTMENT)


## LEGEND

XXXX POINT NUMBER (POINT DETAILS FOUND  
ON ALIGNMENT TABULATION SHEETS)

## CSAH 17

PLOTTED/REVISED: 7/29/2022 12:24:37 PM

PATH &amp; FILENAME: K:\019869-000\Cad\Plan\19869-000-C-ALGN-PLAN.dgn



| REVISIONS |      |
|-----------|------|
| NO.       | DATE |
|           |      |
|           |      |
|           |      |

I HEREBY CERTIFY THAT THIS PLAN, SPECIFICATION,  
OR REPORT WAS PREPARED BY ME OR UNDER MY  
DIRECT SUPERVISION AND THAT I AM A DULY  
LICENSED PROFESSIONAL ENGINEER UNDER THE  
LAWS OF THE STATE OF MINNESOTA.

NICHOLAS E. HENTGES, PE  
DATE: 7/29/2022 LIC. NO: 44620

CITY OF BLAINE, MN  
LEXINGTON AVENUE NE AT  
131ST AVENUE NE  
INTERSECTION IMPROVEMENTS

## ALIGNMENT PLAN


## ALIGNMENT TABULATION

| POINT NUMBER           | POINT | STATION    |                  |               |            |          |          | COORDINATES |             | BEARING           |
|------------------------|-------|------------|------------------|---------------|------------|----------|----------|-------------|-------------|-------------------|
|                        |       |            | DELTA            | DEGREE        | RADIUS     | TANGENT  | LENGTH   | X           | Y           |                   |
| <b>CSAH 17</b>         |       |            |                  |               |            |          |          |             |             |                   |
| 1000                   | POT   | 0+00.00    |                  |               |            |          |          | 526,737.492 | 162,299.549 |                   |
| 1001                   | POT   | 7+00.00    |                  |               |            |          |          | 526,735.781 | 162,999.547 |                   |
| <b>131ST AVENUE NE</b> |       |            |                  |               |            |          |          |             |             |                   |
| 1002                   | PC    | 197+02.355 |                  |               |            |          |          | 526,438.510 | 162,863.552 | S 89° 07' 35.1" E |
|                        | PI    | 198+40.534 | 2° 51' 48.1" LT  | 1° 02' 10.8"  | 5,528.752' | 138.179' | 276.300' | 526,576.673 | 162,861.446 | PI                |
|                        | CC    |            |                  |               |            |          |          | 526,522.803 | 168,391.662 |                   |
| 1003                   | PT    | 199+78.655 |                  |               |            |          |          | 526,714.769 | 162,866.243 | N 88° 00' 36.8" E |
| 1004                   | PC    | 202+75.956 |                  |               |            |          |          | 527,011.997 | 162,859.705 | S 88° 44' 23.0" E |
|                        | PI    | 203+65.460 | 20° 17' 52.4" LT | 11° 27' 33.0" | 500,000'   | 89.504'  | 177.132' | 527,101.480 | 162,857.736 | PI                |
|                        | CC    |            |                  |               |            |          |          | 527,022.994 | 163,359.584 |                   |
| 1005                   | PT    | 204+53.089 |                  |               |            |          |          | 527,186.089 | 162,886.931 | N 70° 57' 44.6" E |
| 1006                   | POT   | 206+23.34  |                  |               |            |          |          | 527,347.030 | 162,942.466 |                   |

# CSAH 17

PLOTTED/REVISED: 7/29/2022 12:24:39 PM

PATH & FILENAME: K:\019869-000\Cad\Plan\19869-000-C-DEM-O-PLAN.dwg



| LEGEND    |   |
|-----------|---|
| - T-BUR   | BURIED FIBER OPTIC LINE                       |
| - P-BUR   | BURIED POWER LINE                             |
| - SIG-BUR | BURIED SIGNAL LINE                            |
| - T-BUR   | BURIED TELEPHONE LINE                         |
| - TV-BUR  | BURIED TELEVISION LINE                        |
| - OHP     | OVERHEAD POWER LINE                           |
| - OHU     | OVERHEAD UTILITY LINE                         |
| - <<      | SANITARY SEWER                                |
| - <       | STORM SEWER                                   |
| - G       | UNDERGROUND GAS MAIN / SERVICE                |
| —         | UTILITY IN CONDUIT                            |
| —         | WATER MAIN                                    |
| — — —     | CULVERT                                       |
| □         | CABINET                                       |
| □         | CATCH BASIN                                   |
| □         | HANDHOLE                                      |
| □         | HYDRANT                                       |
| □         | LIGHT POLE                                    |
| □         | MANHOLE                                       |
| □         | PIPE APRON                                    |
| □         | POWER / UTILITY POLE                          |
| □         | SIGN STRUCTURE                                |
| □         | SIGNAL POLE                                   |
| □         | UTILITY PEDESTAL                              |
| □         | VALVE   |
| □         | VEGETATION                                    |
| □         | FENCE   |
| —         | REMOVE BITUMINOUS PAVEMENT                    |
| —         | REMOVE BITUMINOUS WALK                        |
| —         | REMOVE CONCRETE WALK                          |
| —         | MILL BITUMINOUS SURFACE (1.5")                |
| —         | REMOVE CONCRETE CURB & GUTTER                 |
| — — —     | GRADING LIMITS (APPROX.)                      |
| (A)       | SAWING BITUMINOUS PAVEMENT (FULL DEPTH)       |
| (B)       | REMOVE HANDHOLE                               |
| (C)       | SALVAGE CASTING ASSEMBLY                      |
| (G)       | REMOVE LIGHTING UNIT, REMOVE LIGHT FOUNDATION |

CITY OF BLAINE, MN  
LEXINGTON AVENUE NE AT  
131ST AVENUE NE  
INTERSECTION IMPROVEMENTS

I HEREBY CERTIFY THAT THIS PLAN SPECIFICATION, DIRECT SUPERVISION AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MINNESOTA.

SHEET  
29  
OF  
53  
SHEETS

WSB PROJECT NO.:  
019869-000

SCALE: DESIGN BY:  
AS SHOWN AJF  
PLAN BY: CHECK BY:  
AJF NEH


wsb

DATE: 7/29/2022 LIC. NO: 44620


# CSAH 17

PLOTTED/REVISED: 7/29/2022 12:24:41 PM

PATH & FILENAME: K:\019869-000\Cad\Plan\019869-000-C-CONS-PLAN-01.dgn



| RADIUS POINT | CENTER    |           | RADIUS |
|--------------|-----------|-----------|--------|
|              | X         | Y         |        |
| R01          | 526561.86 | 162834.05 | 10'    |
| R02          | 526597.85 | 162834.42 | 10'    |
| R03          | 526661.87 | 162915.68 | 30'    |
| R04          | 526667.41 | 162815.78 | 30'    |
| R05          | 526817.31 | 162813.98 | 30'    |
| R06          | 526810.87 | 162926.14 | 30'    |




CITY OF BLAINE, MN  
LEXINGTON AVENUE NE AT  
131ST AVENUE NE  
INTERSECTION IMPROVEMENTS


SHEET  
30  
OF  
53  
SHEETS

**wsb**  
WSB PROJECT NO.: 019869-000  
SCALE: AS SHOWN DESIGN BY: AJF  
PLAN BY: CHECK BY: AJF NEH

# 131ST AVENUE NE PROFILE



## STORM SEWER PROFILES



wsb

WSB PROJECT NO.: 019869-000

SCALE: DESIGN BY:

AS SHOWN

PLAN BY: CHECK BY:

| REVISIONS | NO. | DATE | DESCRIPTION |
|-----------|-----|------|-------------|
|           |     |      |             |


I HEREBY CERTIFY THAT THIS PLAN, SPECIFICATION, DIRECT SUPERVISION AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MINNESOTA.

DATE: 7/29/2022 LIC. NO.:

CSAH 17 at 131st Avenue NE

PLOTTED/REVISED: 7/29/2022 12:24:43 PM

PATH & FILENAME: K:\019869-000\Cad\Plan\19869-000-C-CONS-DETL-01.dgn



**LEXINGTON AVENUE NE AT  
131ST AVENUE NE  
INTERSECTION IMPROVEMENTS**

## LEGEND

| PEDESTRIAN PUSH BUTTON STATION |   |
|--------------------------------|---|
| HP / LP                        | LOCALIZED HIGH / LOW POINT  |
|                                | CONTROL POINTS AT GUTTER FLOW LINE  |
|                                | TRUNCATED DOMES (SEE STANDARD PLATE 7038)   |
|                                | CATCH BASIN   |
| X"                             | CURB HEIGHT   |
|                                | LANDING AREA - 4' X 4' MIN. DIMENSIONS<br>AND MAX 2.0% SLOPE IN ALL DIRECTIONS.   |
|                                | INDICATES PEDESTRIAN RAMP - SLOPE SHALL<br>BE BETWEEN 5.0% MINIMUM AND 8.3% MAXIMUM<br>IN THE DIRECTION SHOWN AND CROSS SLOPE<br>SHALL NOT EXCEED 2.0%. |
|                                | INDICATES PEDESTRIAN RAMP - SLOPE SHALL<br>BE GREATER THAN 2.0% AND LESS THAN 5.0%<br>IN THE DIRECTION SHOWN AND CROSS SLOPE<br>SHALL NOT EXCEED 2.0%.  |
|                                | DRAINAGE FLOW ARROW   |

## GENERAL NOTES

- MAINTAIN A MINIMUM 4' WIDE PEDESTRIAN ACCESS ROUTE OBSTRUCTION TO OBSTRUCTION AND/OR OBSTRUCTION TO FAR EDGE OF WALK.
- THE CROSS SLOPE OF THE PEDESTRIAN ACCESS ROUTE SHALL NOT EXCEED 0.020 FT/FT

**SHEET  
32  
OF  
53  
SHEETS**

WSB PROJECT NO.:  
019869-000

LE: DESIGN BY:  
S SHOWN AJF  
N BY: CHECK BY:  
AJF NEH


I HEREBY CERTIFY THAT THIS PLAN, SPECIFICATION, OR REPORT WAS PREPARED BY ME OR UNDER MY DIRECT SUPERVISION AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MINNESOTA.

DATE: \_\_\_\_\_

# CSAH 17

PLOTTED/REV/SED: 7/29/2022 12:24:44 PM

PATH & FILENAME: K:\019869-000\Cad\Plan\19869-000-C-EROS-PLAN.dwg



| LEGEND |   |
|--------|---|
|        | TEMPORARY:<br>RAPID STABILIZATION METHOD 3  |
|        | PERMANENT:<br>ROLLED EROSION PREVENTION CATEGORY 20<br>SEED MIX 25-131 (220 LBS/ACRE)<br>FERTILIZER TYPE 3 (350 LBS/ACRE) |
| →      | SURFACE FLOW DIRECTION  |
| □      | INLET PROTECTION  |
| — BR — | SEDIMENT CONTROL LOG TYPE COMPOST   |
| — MS — | SILT FENCE, TYPE MS   |
| — - -  | CONSTRUCTION LIMITS   |

I HEREBY CERTIFY THAT THIS PLAN SPECIFICATION, DIRECT SUPERVISION AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MINNESOTA.

DATE: 7/29/2022 LIC. NO: 44620

NICHOLAS E. HENTGES, PE


## CITY OF BLAINE, MN LEXINGTON AVENUE NE AT 131ST AVENUE NE INTERSECTION IMPROVEMENTS

### TURF ESTABLISHMENT & EROSION CONTROL

SHEET  
33  
OF  
53  
SHEETS

WSB PROJECT NO.:  
019869-000

SCALE: DESIGN BY:  
AS SHOWN AJF  
PLAN BY: CHECK BY:  
AJF NEH




## REVISIONS

| NO. | DATE | DESCRIPTION |
|-----|------|-------------|
|     |      |             |

I HEREBY CERTIFY THAT THIS PLAN SPECIFICATION, DIRECT SUPERVISION AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MINNESOTA.

DATE: 7/29/2022

LIC. NO.: 40945



## SIGN AND DELINEATOR / MARKER

| SIGN NUMBER | PANEL       |                  | SIZE (W x H) | MOUNTING HEIGHT | SUPPORT |      | REMOVE SIGN | SIGN |
|-------------|-------------|------------------|--------------|-----------------|---------|------|-------------|------|
|             | PANEL CODE  | LEGEND           |              |                 | INCH    | FEET |             |      |
| S-1         | R3-8AD      | L-TR             | 36 x 30      | 7               | U-SOIL  | 1    |             | 7.50 |
| S-2         | R6-1R       | ONE WAY RIGHT    |              | x               |         |      |             |      |
|             | R1-1        | STOP             |              | x               |         |      |             |      |
| S-3         |             | 131ST AVE        |              | x               |         |      |             |      |
| S-4         | R5-1        | LEXINGTON AVE NE | x            |                 |         |      |             |      |
| S-5         | R2-1        | DO NOT ENTER     | 30 x 30      | 7               | U-CONC  | 1    |             | 6.25 |
| S-6         | R3-7R (MOD) | SPEED LIMIT 55   | 24 x 30      | 7               | U-SOIL  | 1    |             | 5.00 |
| S-7         | R2-1        | RIGHT TURN LANE  | 30 x 30      | 7               | U-SOIL  | 1    |             | 6.25 |
|             |             | SPEED LIMIT 55   | 24 x 30      | 7               | U-SOIL  | 1    |             | 5.00 |
|             |             |                  |              |                 |         |      | TOTAL:      | 2 30 |

SPECIFIC NOTE(S):  
(1) U-CHANNEL 3# PER FOOT BLACK POST


## SIGNING LEGEND

- (1) FURNISH & INSTALL (4) REMOVE
- (2) INPLACE

## STRIPING LEGEND

|                                    |   |
|------------------------------------|---|
| 1ST DIGIT WIDTH<br>4", 6", 8", 24" | CIRCLE - MULTI COMP                     |
|                                    | SQUARE - PREF THERMO                    |
| 2ND DIGIT PATTERN                  | 3RD DIGIT COLOR                         |
| S = SOLID                          | W = WHITE                               |
| B = BROKEN                         | Y = YELLOW                              |
| D = DOUBLE                         | B = BLACK                               |
| T = DOTTED                         | ARROWS - PREF THERMO                    |
|                                    | CROSSWALK (3'X10' BLOCKS) - PREF THERMO |

## SIGNING &amp; STRIPING

MARKINGS FOR PEDESTRIAN CROSSWALKS

| (L)                     | (W)                       | (S)               |
|-------------------------|---------------------------|-------------------|
| WIDTH OF<br>INSIDE LANE | WIDTH OF<br>PAINTED AREAS | WIDTH OF<br>SPACE |
| 9'                      | 2.0'                      | 2.5'              |
| 10'                     | 2.5'                      | 2.5'              |
| 11'                     | 2.5'                      | 3.0'              |
| 12'                     | 3.0'                      | 3.0'              |
| 13'                     | 3.0'                      | 3.5'              |

## NOTES: CROSSWALKS:



- 1.) PAINTED AREAS ARE TO BE CENTERED ON CENTER AND LANE LINES, EVEN IF INTERSECTION IS NOT ALIGNED.
- 2.) LOCATION OF ZEBRA CROSSWALKS AND STOP BARS, SIGNAL LOOPS AND PED RAMPS ARE APPROXIMATE. FINAL LOCATIONS ARE TO BE DETERMINED AND FIELD VERIFIED DURING CONSTRUCTION BY THE FIELD ENGR.
- 3.) ZEBRA CROSSWALKS ARE TO BE PARALLEL TO THE DRIVING LANE OR LANES. EVEN IF THE STREET IS ON AN ANGLE TO THE INTERSECTION.
- 4.) A MIN. OF 1.5' (450mm) CLEAR DISTANCE MUST BE LEFT ADJACENT TO THE CURB. IF LAST PAINTED AREA FALLS INTO THIS AREA, IT MUST BE OMITTED.
- 5.) ON TWO LANE STREETS, USE SPACING SHOWN FOR AN 11' (3.3m) INSIDE LANE.

| REVISIONS | DESCRIPTION |
|-----------|-------------|
| NO. DATE  |             |

HEREBY CERTIFY THAT THIS PLAN SPECIFICATION,  
DIRECT SUPERVISION AND THAT I AM A DULY  
LICENSED PROFESSIONAL ENGINEER UNDER THE  
LAWS OF THE STATE OF MINNESOTA.

DATE: 7/29/2022 LIC. NO: 40845

PLOTTED/REVISED: 7/29/2022 12:24:46 PM




LOOP DETECTOR  
DETAIL 'A'  
(LOOP PHASING FOR  
SINGLE CONNECTION)


LOOP CONNECTIONS SHALL BE  
LABELED AND SPLICED IN THE  
HANDHOLE AS FOLLOWS:

L1 TO 1A  
1B TO 2A  
2B TO L2

LOOP DETECTOR  
DETAIL 'B'  
(LOOP PHASING FOR  
SERIES CONNECTION)



LOOP RETURN CONDUITS  
MAY BE PLACED IN COMMON  
TRENCH (TYP)






LOOP CONNECTIONS SHALL BE LABELED AND SPLICED  
IN THE HANDHOLE AS FOLLOWS:

L1 TO 1A  
1B TO 2A  
2B TO 3A  
3B TO 4A

SPLICE CONTROL CABLE TO L1 & L2 IN HANDHOLE.  
ALL CONDUCTORS SHALL BE TAGGED IN HANDHOLE  
(1A, 1B, ETC)

LOOP DETECTOR  
DETAIL 'C'  
(LOOP PHASING FOR  
SERIES CONNECTION)



#### LOOP DETECTOR WIRING

- 1) ALL CORNERS SHALL BE 90° CONDUIT BENDS.
- 2) CONNECT WIRES IN HANDHOLES USING SPLICING KIT METHOD DESCRIBED IN THE SPECIAL PROVISIONS.
- 3) LOOP DETECTOR WIRES SHALL BE #12 AWG CROSSED LINKED POLYETHYLENE (XLP). SEE SPECIAL PROVISIONS.
- 4) LOOP LEAD IN WIRES SHALL BE TWISTED A MIN. OF (5) TURNS PER FOOT THROUGH THE CONDUIT TO THE HANDHOLE.
- 5) NMC DESIGNATES NON-METALLIC CONDUIT (SPEC. 3803)
- 6) LOOPS 6' x 6' THRU 6' x 14' SHALL HAVE (4) TURNS.
- 7) LOOPS 6' x 15' AND LARGER SHALL HAVE (2) TURNS.

#### LEGEND OF SYMBOLS

|   |     |
|---|-----|
| CONTROLLER AND SERVICE EQUIP. NO's          | (A) |
| SIGNAL BASE NO.                             | (1) |
| SIGNAL FACE NO.                             | (1) |
| LUMINAIRE NO.                               | (1) |
| CONTROLLER AND CABINET                      | (1) |
| CONTROLLER AND CABINET - IN PLACE           | (1) |
| HANDHOLE                                    | (1) |
| HANDHOLE - IN PLACE                         | (1) |
| RIGID STEEL CONDUIT (RSC)                   | (1) |
| RIGID STEEL CONDUIT (RSC) - IN PLACE        | (1) |
| SIGNAL FACE WITH BACKGROUND SHIELD          | (1) |
| SIGNAL FACE W/O BACKGROUND SHIELD           | (1) |
| SIGNAL FACE - IN PLACE                      | (1) |
| PEDESTRIAN INDICATORS                       | (1) |
| PEDESTRIAN INDICATORS - IN PLACE            | (1) |
| PEDESTRIAN PUSH BUTTONS ON PEDESTAL OR POLE | (1) |
| PEDESTRIAN PUSH BUTTON STATION              | (1) |
| TRAFFIC SIGNAL PEDESTAL                     | (1) |
| TRAFFIC SIGNAL PEDESTAL - INPLACE           | (1) |
| TRAFFIC SIGNAL POLE AND MAST ARM            | (1) |
| TRAFFIC SIGNAL POLE AND MAST ARM - IN PLACE | (1) |
| STREET LIGHT POLE AND LUMINAIRE             | (1) |
| STREET LIGHT POLE AND LUMINAIRE - IN PLACE  | (1) |
| MAST ARM AND LUMINAIRE                      | (1) |
| MAST ARM AND LUMINAIRE - INPLACE            | (1) |
| WOOD POLE                                   | (1) |
| WOOD POLE - IN PLACE                        | (1) |
| SOURCE OF POWER                             | (1) |
| RAILROAD SIGNAL - IN PLACE                  | (1) |
| RIGHT OF WAY LINE                           | (1) |
| CENTERLINE                                  | (1) |
| EDGE OF ROADWAY                             | (1) |
| SHOULDERLINE                                | (1) |
| CURB LINE                                   | (1) |
| STOP BAR                                    | (1) |
| EMERGENCY VEHICLE PREEMPTION DETECTOR       | (1) |

#### ABBREVIATIONS

|          |                                |           |                                    |
|----------|--------------------------------|-----------|------------------------------------|
| 3-1(EG)  | SIGNAL HEAD PHASE "3" - NO "1" | P2-1(EG)  | PED INDICATION PHASE "2" - NO. "1" |
| BR. GR.  | BARE GROUND                    | PB        | PUSH BUTTON                        |
| CH. SW.  | CHECK SWITCH                   | PB2-1(EG) | PUSH BUTTON PHASE "2" - NO. "1"    |
| CLR      | CLEAR                          | PEC       | PHOTOELECTRIC CELL                 |
| D2-1(EG) | DETECTOR PHASE "2" - NO. "1"   | PED       | PEDESTRIAN                         |
| DWK      | DON'T WALK                     | R         | RED                                |
| EQG      | EQUIPMENT GROUND               | R&S       | REMOVE AND SALVAGE                 |
| EVP      | EMERGENCY VEHICLE PRE-EMPTION  | RLTA      | RED LEFT TURN ARROW                |
| F&I      | FURNISH AND INSTALL            | RRTA      | RED RIGHT TURN ARROW               |
| FL       | FLASH/FLASHING                 | RSC       | RIGID STEEL CONDUIT                |
| G        | GREEN                          | SOP       | SOURCE OF POWER                    |
| GLTA     | GREEN LEFT TURN ARROW          | SPR       | SPARE                              |
| GRN      | GREEN                          | ST. LHT   | STREET LIGHT                       |
| GR. R    | GROUND ROD                     | STA       | STATION                            |
| GRTA     | GREEN RIGHT TURN ARROW         | SW        | SWITCH                             |
| GTHA     | GREEN THRU ARROW               | SWD       | SWITCHED                           |
| HH       | HANDHOLE                       | S&R       | SALVAGE AND REINSTALL              |
| HPS      | HIGH PRESSURE SODIUM           | TDW       | TELEPHONE DROP WIRE                |
| JB       | JUNCTION BOX                   | WLK       | WALK                               |
| LUM      | LUMINAIRE                      | YEL       | YELLOW                             |
| NEU      | NEUTRAL                        | YLTA      | YELLOW LEFT TURN ARROW             |
| NMC      | NONMETALLIC CONDUIT            | YRTA      | YELLOW RIGHT TURN ARROW            |
|          |                                | YTHA      | YELLOW THRU ARROW                  |

#### CONDUCTOR COLOR CODE

|        |                          |
|--------|--------------------------|
| R      | RED                      |
| O      | ORANGE                   |
| BL     | BLUE                     |
| WH     | WHITE                    |
| R/BLK  | RED WITH BLACK TRACER    |
| O/BLK  | ORANGE WITH BLACK TRACER |
| BL/BLK | BLUE WITH BLACK TRACER   |
| WH/BLK | WHITE WITH BLACK TRACER  |
| BLK    | BLACK                    |
| BLK/WH | BLACK WITH WHITE TRACER  |
| G/BLK  | GREEN WITH BLACK TRACER  |
| G      | GREEN                    |

#### STANDARD PLATES - SIGNAL SYSTEMS

THE FOLLOWING STANDARD PLATES, APPROVED BY THE FEDERAL HIGHWAY ADMINISTRATION, SHALL APPLY ON THIS PROJECT

| PLATE NO.                                    | DESCRIPTION                                  | PLATE NO. | DESCRIPTION                               |
|--|--|-----------|---|
| ► 7038 A                                     | DETECTABLE WARNING SURFACE TRUNCATED DOMES   | ► 8123 G  | POLE AND MAST ARM                         |
| ► 7113 A                                     | CONCRETE APPROACH NOSE DETAIL                | ► 8126 L  | POLE FOUNDATION (PA90 AND PA100)          |
| ► 8111 E                                     | TRAFFIC SIGNAL BRACKETING (PEDESTAL MOUNTED) | ► 8127 E  | LIGHTING FOUNDATION E (PEDESTAL)          |
| ► 8117 G                                     | PRECAST CONCRETE HAND HOLE                   | ► 8129 A  | SHIM AND WASHER                           |
| ► 8118 D                                     | SERVICE EQUIPMENT AND POLE                   | ► 8130 E  | SAW CUT LOOP DETECTORS                    |
| ► 8119 C                                     | GROUND MOUNTED CABINET FOUNDATION            | ► 8132 B  | PREFORMED RIGID PVC CONDUIT LOOP DETECTOR |
| ► 8120 O                                     | POLE FOUNDATION (PA-85)                      |           |   |
| ► 8121 H                                     | TRANSFORMER BASE AND POLE BASE PLATE         |           |   |
| ► STANDARD PLATES APPLICABLE TO THIS PROJECT |  |           |   |

#### TRAFFIC CONTROL SIGNAL SYSTEM

SIGN DETAILS

PLOTTED/REVISED: 7/29/2022 12:24:47 PM

PATH &amp; FILENAME: K:\019869-000\Cad\Plan019869-000\_si02.dgn

| SIGN PANELS ON SIGNALS               |     |                |         |  |          |                 |
|--------------------------------------|-----|----------------|---------|--|----------|-----------------|
| "A"<br>DISTANCE<br>(FEET)<br>OR POLE | QTY | CODE<br>NUMBER | PANEL   |  |          | AREA<br>(SQ FT) |
|                                      |     |                | LEGEND  | SIZE<br>(INCHES)                         |          |                 |
| 1                                    | 18  | 1              | D-1     | LEXINGTON AVE                            | 114 x 24 | 19.00           |
| 1                                    | 0   | 1              | R10-X12 | LEFT TURN YIELD ON FLASHING YELLOW ARROW | 42 x 48  | 14.00           |
| 3                                    | 21  | 1              | D-2     | 131ST AVE                                | 78 x 24  | 13.00           |
| 3                                    | 0   | 1              | R10-X12 | LEFT TURN YIELD ON FLASHING YELLOW ARROW | 42 x 48  | 14.00           |
| 5                                    | 18  | 1              | D-1     | LEXINGTON AVE                            | 114 x 24 | 19.00           |
| 5                                    | 0   | 1              | R10-X12 | LEFT TURN YIELD ON FLASHING YELLOW ARROW | 42 x 48  | 14.00           |
| 6                                    | 32  | 1              | D-2     | 131ST AVE                                | 78 x 24  | 13.00           |
| 6                                    | 0   | 1              | R10-X12 | LEFT TURN YIELD ON FLASHING YELLOW ARROW | 42 x 48  | 14.00           |

D-1

3.0" Radius, 1.0" Border, White on, Green;  
"Lexington Ave", D 2K;

D-2

3.0" Radius, 1.0" Border, White on, Green;  
"131st Ave", D 2K;

GENERAL NOTES:

- SEE THE CURRENT MnDOT STANDARD SIGNS AND MARKINGS MANUAL FOR STANDARD SIGN DESIGNS, ARROW DETAILS AND SPLICE PLATE DETAILS.
- FOR NON STANDARD SIGN DESIGNS, LAYOUTS ARE INCLUDED. SIGN PANEL DIMENSIONS ARE IN INCHES.
- SEE STANDARD PLAN 5-297.731 FOR SIGN MOUNTING TO MAST ARM.
- SEE STANDARD PLAN 5-297.730 FOR SIGN MOUNTING TO ROUND POST.
- MOUNTING HEIGHT OF POLE MOUNTED SIGN PANELS MUST BE 7 FOOT MINIMUM.  
MOUNTING HEIGHT IS MEASURED FROM BOTTOM OF SIGN PANEL TO SURFACE IMMEDIATELY BELOW THE SIGN PANEL.
- "A" DISTANCE = DISTANCE FROM THE END OF THE MAST ARM TO THE EDGE OF EACH SIGN PANEL.
- SEE INTERSECTION LAYOUT FOR SIGN PLACEMENT.

| NO. | DATE | DESCRIPTION |
|-----|------|-------------|
|     |      |             |



**CITY OF BLAINE, MN**  
**LEXINGTON AVENUE NE**  
**131ST AVENUE NE**  
**INTERSECTION IMPROVEMENTS**

**TRAFFIC  
CONTROL  
SIGNAL  
SYSTEM**



PLOTTED/REVISED: 7/29/2022 12:24:51 PM

**TYPICAL PAD WITH CONTROLLER CABINET AND SERVICE CABINET**


SEE INTERSECTION LAYOUT FOR CABLE INFORMATION (NOT TO SCALE)

**SIDE VIEW****FRONT VIEW**

**CONTROLLER CABINET**  
**TYPE "P" & "R"**  
**BOLT PATTERN**

**PLAN VIEW**LEXINGTON AVENUE NE  
AT 131ST AVENUE NE

PATH &amp; FILENAME: K:\019869-000\019869-000\Cad\Plan019869-000\_si03.dgn



- THE PUSH BUTTON STATION FOUNDATION IS MONOLITHIC (POURED AT ONE TIME) WITH THE SIDEWALK. PROVIDE A 1:2 (V:H) SLOPE GRADE WHERE THE 6" MIN SIDEWALK DEPTH TRANSITIONS TO THE 12" MIN FOUNDATION DEPTH. MAINTAIN THE COMPACTED AGGREGATE BEDDING AND THICKNESS USED FOR THE SIDEWALK THROUGHOUT THE SLOPE AND FOUNDATION GRADING. PROVIDE 1:2 (V:H) SLOPE GRADING 360 DEGREES FOR THE TRANSITION FROM THE SIDEWALK TO THE FOUNDATION WHEN THE FOUNDATION IS NOT LOCATED NEAR EDGE OF SIDEWALK AND IS SURROUNDED BY CONCRETE WALK.
- ENSURE CONCRETE CONTROL JOINTS AND EDGE OF CONCRETE WALK ARE A MINIMUM 9" FROM THE CENTER OF THE PUSH BUTTON FOUNDATION.
- INSTALL THE MANUFACTURER PROVIDED CABLE TETHER ASSEMBLY IN ACCORDANCE WITH THE MANUFACTURER'S INSTALLATION INSTRUCTIONS.

### ANCHOR ROD PLACEMENT



ANCHOR RODS

### TYPICAL APS PEDESTRIAN PUSH BUTTON LOCATION

THIS IS A GENERAL DETAIL INTENDED TO SHOW THE REQUIREMENTS OF APS PUSH BUTTON LOCATION. FOR PROJECT SPECIFIC INFORMATION REGARDING PEDESTRIAN RAMP LAYOUT AND PUSH BUTTON LOCATIONS, SEE THE PLAN.


#### SUPPLEMENTAL GUIDANCE FOR CONSTRUCTING COMPLIANT APS PUSH BUTTONS:

- THE FACE OF THE BUTTON SHALL BE PARALLEL WITH THE OUTSIDE EDGE OF CROSSWALK.
- A MINIMUM 4 FT X 4 FT LANDING AREA SHALL BE PROVIDED ADJACENT TO EACH BUTTON, WITH A 2 PERCENT MAXIMUM SLOPE IN ALL DIRECTIONS.
- BUTTONS SHALL BE WITHIN 5 FT OF THE OUTSIDE EDGE OF THE CROSSWALK.
- BUTTONS SHALL BE BETWEEN 1.5 FT AND 10 FT FROM THE BACK OF CURB OR EDGE OF ROADWAY, MEASURED IN THE DIRECTION OF TRAVEL. STANDALONE PUSH BUTTON STATIONS SHOULD BE 4' MINIMUM FROM THE BACK OF CURB TO AVOID KNOCKDOWNS.
- BUTTONS SHALL BE AT LEAST 10 FT APART.
- PROVIDE A MAINTENANCE ACCESS ROUTE (MAR) WHEREVER POSSIBLE FOR SNOW REMOVAL PURPOSES. A MAR REQUIRES A 6 FT MINIMUM CLEAR DISTANCE BETWEEN A PUSH BUTTON AND ANY OBSTRUCTIONS, INCLUDING BUILDINGS, V-CURB, ELECTRICAL FOUNDATIONS, SIGNAL CABINETS, OR ANOTHER PUSH BUTTON.
- BUTTON SHOULD BE 2 FT MINIMUM FROM RAMP GRADE BREAK AND BACK OF WALK.




CONTRACTOR MUST USE OPTION 1 OR 2 WHEN THE APS PUSH BUTTON IS SHOWN AT THE EDGE OF WALK. OPTION USED (OR SELECTED) MUST BE THE SAME THROUGHOUT THE ENTIRE PROJECT.

#### OPTION 1



#### OPTION 2






| SIGNAL CONTROL POINTS |  | DISTANCE TO FRONT OF LANDING (FT) | DISTANCE TO BACK OF LANDING (FT) |
|-----------------------|--|-----------------------------------|----------------------------------|
| SIGNAL NO.            |  | X                                 | Y                                |
| PB2-1                 |  | -                                 | A                                |
| PB4-2                 |  | -                                 | C                                |

A - DISTANCE MEASURED FROM THE PUSH BUTTON TO THE FRONT OF LANDING/TOP OF RAMP

B - CLEAR DISTANCE MEASURED FROM THE PUSH BUTTON TO THE BACK OF LANDING/EDGE OF WALK




C - CLEAR DISTANCE MEASURED FROM THE PUSH BUTTON TO THE OUTSIDE EDGE OF DOMES IN THE DIRECTION OF TRAVEL

D - CLEAR DISTANCE FROM THE PUSH BUTTON TO THE BACK OF LANDING MEASURED IN THE OPPOSITE DIRECTION OF TRAVEL




**NOTES:**

1. ALL THREADED SURFACES TO BE COATED WITH ANTI-SEIZE COMPOUND.
2. USE SIGNAL HEAD MOUNTED SPACERS FOR 4 SECTION POLY HEADS.
3. SEE STANDARD PLATE NUMBER 8123 FOR ADDITIONAL SIGNAL POLE DETAILS.
4. EXTENDED THREAD POLE ADAPTOR ONLY USED WITH 5 SECTION CLUSTER HEADS.



**NOTES:**

1. ALL THREADED SURFACES TO BE COATED WITH ANTI-SEIZE COMPOUND.
2. USE SIGNAL HEAD MOUNTED SPACERS FOR 4 SECTION POLY HEADS.
3. BLIND THREADED INSERTS (RIVET NUT) MUST BE INSERTED USING MANUFACTURERS SPECIFIC INSERTION TOOL. NO OTHER METHOD IS ACCEPTABLE.
4. SEE STANDARD PLATE NUMBER 8122 FOR ADDITIONAL PEDESTAL POLE DETAILS.



**CITY OF BLAINE, MN**  
**LEXINGTON AVENUE NE**  
**131ST AVENUE NE**  
**INTERSECTION IMPROVEMENTS**

CITY OF BLAINE, MN  
LEXINGTON AVENUE NE  
131ST AVENUE NE  
INTERSECTION IMPROVEMENTSTRAFFIC  
CONTROL  
SIGNAL  
SYSTEMSHEET  
41  
OF  
53  
SHEETS


| CONDUCTOR COLOR CODE     |                            |                  |
|--------------------------|----------------------------|------------------|
| FROM                     | TO DEVICE                  |                  |
| SIGNAL SERVICE           | 1/C 6 ECC                  | AS SHOWN ON PLAN |
| SOP                      | 3-1/C 2 R WH BLK           | SIGNAL SERVICE   |
| SIGNAL SERVICE           | 3-1/C 6 BLK WH G           | SIGNAL CABINET   |
| SIGNAL CABINET           | (6SM) CABLE                | SIGNAL CABINET   |
| SIGNAL CABINET TO DEVICE |                            |                  |
| 6PR 19                   |                            | AS SHOWN ON PLAN |
| COAXIAL CABLE            |                            | AS SHOWN ON PLAN |
| 4/C 18                   | R BLK WH G                 | AS SHOWN ON PLAN |
| 2/C 14                   | BLK WH OR CLR              | AS SHOWN ON PLAN |
| 3/C 20                   | R OR 0 WH OR YEL BLK OR BL | AS SHOWN ON PLAN |
| CAT 5                    |                            | AS SHOWN ON PLAN |

NOTES:  
ARRANGE AND TERMINATE CONDUCTORS AND CABLES AS SHOWN WITHOUT SPLICING.  
NUMBER ONLY MEANS AWG CONDUCTOR SIZE (e.g. 14=14AWG)  
1/C MEANS AN INDIVIDUAL CONDUCTOR NOT PART OF A CABLE ASSEMBLY

| WIRE COLOR CODE KEY |                          |
|---------------------|--------------------------|
| R                   | Red                      |
| O                   | Orange                   |
| BL                  | Blue                     |
| WH                  | White                    |
| BLK                 | Black                    |
| BRN                 | Brown                    |
| CL                  | Clear                    |
| G                   | Green                    |
| R/BLK               | Red with Black Stripe    |
| O/BLK               | Orange with Black Stripe |
| BL/BLK              | Blue with Black Stripe   |
| WH/BLK              | White with Black Stripe  |
| WH/R                | White with Red Stripe    |
| BLK/WH              | Black with White Stripe  |
| BLK/R               | Black with Red Stripe    |

| CONDUCTOR AND CABLE SPECIFICATION CHART |                               |                      |
|---|-------------------------------|----------------------|
| NUMBER OF CONDUCTORS & AWG SIZE         | TYPE                          | Specification Number |
| 1/C 2                                   | INDIVIDUAL SERVICE CONDUCTORS | 3815.2B.1            |
| 1/C 6                                   | FEEDER AND BRANCH CONDUCTORS  | 3815.2B.1            |
| 1/C 6 INS.GR.                           | Grounding Conductors          | 3815.2B.5            |
| 2/C 14                                  | Loop Detector Lead-In Cable   | 3815.2C.4            |
| 3/C 14                                  | Signal Control Cable          | 3815.2C.3            |
| 4/C 14                                  | Signal Control Cable          | 3815.2C.3            |
| 6/C 14                                  | Signal Control Cable          | 3815.2C.3            |
| 12/C 14                                 | Signal Control Cable          | 3815.2C.3            |
| 6PR 19                                  | Telephone Cables Outdoor      | 3815.2C.6.b          |
| 3/C 20                                  | EVP Detector Cable            | 3815.2C.5            |

## FIBER-OPTIC PULLING VAULT DETAIL



## CABLE LABELING ABBREVIATIONS

| ABBREVIATION | LABEL REFERENCE DSISSCRIPTION & EXAMPLE | COMPONENT         |
|--------------|---|-------------------|
| X-Y          | INDICATION NUMBER 2-1                   | SIGNAL HEAD       |
| X-Y          | LOOP NUMBER D2-1                        | DETECTOR          |
| X-Y          | PUSH BUTTON NUMBER PB2-1                | PUSH BUTTON       |
| X-Y          | PED INDICATION NUMBER P2-1              | PED INDICATION    |
| X-Y          | LUMINAIRE NUMBER L1                     | LUMINAIRE         |
| X-Y          | EVP PHASE NUMBER EVP 2+5                | EVP DETECTOR      |
| X-Y          | EVP LIGHT PHASE NUMBER EVPL 2+5         | EVP CON.LIGHT     |
| X-Y          | VIDEO DETECTION PHASE V2-1              | VIDEO DETECTION   |
| X-Y          | RADAR DETECTION PHASE RD2-1             | RADAR DETECTION   |
| SS           | SIGNAL SERVICE                          | SERVICE WIRE      |
| CC           | CABINET COMMS                           | COMMS CABLE       |
| FO           | FIBER OPTIC                             | FIBER CABLE       |
| SPARE Y      | SPARE WIRE TO POLE NUMB. SPARE1         | SPARE WIRE        |
| ELYZ *       | ENFORC.LIGHT POLE & DIRECTION           | ENFORCEMENT LIGHT |
| PTZ1         | PTZ CAMERA POLE NUMBER PTZ1             | PTZ CAMERA        |
| IC           | INTERCONNECT CABLE                      | INTERCONNECT      |
| ECC          | EQUIPMENT GROUNDING CONDUCTOR           | GROUND            |

X = SIGNAL SYSTEM PHASE NUMBER; REFER TO THE PLAN  
Y = SIGNAL SYSTEM ASSIGNED COMPONENT NUMBER; REFER TO THE PLAN  
Z \* = DIRECTION  
FURNISH AND INSTALL LABELS ON CABLES WITH ABBREVIATIONS SHOWN  
ON THIS TABLE AND IN ACCORDANCE WITH THE WIRING DIAGRAM.

NOTES:

1. REFER TO SHEETS FOR INPLACE SIGNAL COMPONENTS.
2. ENSURE THE EXACT LOCATION OF THE HANDHOLES, POLES, LOOP DETECTORS AND EQUIPMENT PAD ARE VERIFIED IN THE FIELD BY TRAFFIC OFFICE PERSONNEL.
3. THE CONTRACTOR IS RESPONSIBLE FOR COORDINATING THE CONNECTION OF THE POWER FOR THE TRAFFIC SIGNAL SYSTEM.
4. FOR SIGN PANELS ON SIGNAL SEE DETAIL SHEET. ALL SIGN PANELS REQUIRED ARE INCLUDED IN PAYMENT FOR THE TRAFFIC CONTROL SIGNAL SYSTEM PAY ITEM.
5. ALL PAVEMENT MARKINGS ARE INCLUDED IN PAVEMENT MARKING PLAN.
6. CONSTRUCTION OF PEDESTRIAN CURB RAMPS ARE PART OF THE CONSTRUCTION PLAN AND ARE NOT INCLUDED IN PAYMENT FOR THE SIGNAL SYSTEM.
7. THIS PLAN SPECIFIES CONDUIT SIZES, TYPES, AND GENERAL LOCATIONS. THE EXACT LOCATIONS WILL BE DETERMINED IN THE FIELD. CONDUITS UNDER THE ROADWAYS REQUIRE BORING.
8. USE PVC OR HDPE FOR ALL NEW CONDUIT.
9. CONDUIT SIZES ARE NOMINAL DIAMETER.
10. ALL WIRES LISTED ARE AWG (AMERICAN WIRE GAUGE).
11. ITEMS DENOTED WITH AN \* ARE INCLUDED IN PAYMENT FOR THE EVP SYSTEM PAY ITEM.

PLOTTED/REVISED: 7/29/2022 12:24:56 PM

PATH & FILENAME: K:\019869-000\Card\Plan\019869-000\_s107.dgn

**A**  
EQUIPMENT PAD (SEE DETAIL SHEET)  
SERVICE CABINET (SSB) BATTERY BACKUP SYSTEM  
(BATTERIES INCLUDED)  
CONTROLLER AND CABINET

3" CONDUIT TO INP HH 1: 3" CONDUIT TO HH 15:  
2-6/C 14 2-6/C 14  
4-4/C 14 5-4/C 14  
6-2/C 14 6-2/C 14  
\*1-3/C 14 (EVP) \*1-3/C 14 (EVP)  
\*1-3/C 20 (EVP) \*1-3/C 20 (EVP)  
1-1/C INS. GR. 1-1/C INS. GR.



3" CONDUIT TO INP HH 1: 3" CONDUIT TO HH 15:  
2-6/C 14 2-5/C 14  
5-4/C 14 4-4/C 14  
7-2/C 14 6-2/C 14  
\*1-3/C 14 (EVP) \*1-3/C 14 (EVP)  
\*1-3/C 20 (EVP) \*1-3/C 20 (EVP)  
1-1/C INS. GR. 1-1/C INS. GR.

1.5" CONDUIT  
12SM F/O

GROUND WIRE AND GROUND ROD - MIN 8' OUT FROM PAD  
2-2" AND 1-3" CONDUIT STUBBED OUT (CAPPED BOTH ENDS)  
CABINET TO SERVICE CABINET:

2" CONDUIT  
3-1/C 6  
SERVICE CABINET TO INP HH 1:  
2" CONDUIT  
2-3/C 14 (LUM)  
SERVICE CABINET TO HH 15:  
2" CONDUIT  
2-3/C 14 (LUM)  
SERVICE CABINET TO EXTERNAL GR. RD.  
1" CONDUIT  
1-1/C 6 INS. GR. (SEE EQUIPMENT PAD DETAIL)

**B**  
INP SOP (CONNEXUS)  
GROUND MOUNTED  
TRANSFORMER



**REVISIONS**

| NO. | DATE | DESCRIPTION |
|-----|------|-------------|
|     |      |             |
|     |      |             |
|     |      |             |

HEREBY CERTIFY THAT THIS PLAN SPECIFICATION,  
OR REPORT WAS PREPARED BY ME OR UNDER MY  
DIRECT SUPERVISION AND THAT I AM A DULY  
LICENSED PROFESSIONAL ENGINEER UNDER THE  
LAWS OF THE STATE OF MINNESOTA.

DATE: 7/29/2022 LIC. NO.:

**CITY OF BLAINE, MN**  
**LEXINGTON AVENUE AT**  
**131ST AVENUE NE**  
**INTERSECTION IMPROVEMENTS**

**WSB**  
WSB PROJECT NO.: 019869-000


SCALE: DESIGN BY:  
AS SHOWN

PLAN BY: CHECK BY:

**SCALE IN FEET**  
0 20 40

**SHEET 42 OF 53 SHEETS**

PATH & FILENAME: K:\019869-000\cad\plan\019869-000\_s\08.dgn



F&I:  
 PA90 POLE FOUNDATION  
 X=530605.1221 Y=150026.1606  
 TYPE PA90-A-30-D30-9 (DAVIT AT 350 DEG)  
 1-ANGLE MOUNT SIGNAL OVERHEAD AT 0'  
 1-STRAIGHT MOUNT SIGNAL OVERHEAD AT 12'  
 2-ANGLE MOUNT SIGNAL AT 90 & 180 DEG  
 1-ANGLE MOUNT C.D. PED IND AT 90 DEG  
 D SIGN (SEE DETAIL SHEET)  
 LED LUMINAIRE (FOR 40' MOUNTING HEIGHT)  
 EXTEND INTO INP HH 1:  
 2-6/C 14  
 3-4/C 14  
 \* 1-3/C 14 (EVP)  
 \* 1-3/C 20 (EVP)  
 1-3/C 14 (LUM)  
 1-1/C INS. GR.  
  
 INSTALL:  
 1-ONE WAY EVP DETECTOR AND CONFIRMATORY  
 LIGHT (PHASES 3 & 8) (ANOKA CO FURNISHED)

2 F&I:  
PEDESTAL FOUNDATION  
1-10' SIGNAL PEDESTAL PLUS BASE  
1-ANGLE MOUNT C.D. PED IND AT 180 DEG  
1-APS PUSH BUTTON AND SIGN  
(RT ARROW) (PB8-2)  
EXTEND INTO INP HH 1:  
1-4/C 14  
1-2/C 14  
1-1/C INS. GR.

③ F&I:  
PA90 POLE FOUNDATION  
X=530616.0176 Y=149935.0448  
TYPE PA90-A-30-D30-9 (DAVIT AT 350 DEG)  
1-ANGLE MOUNT SIGNAL OVERHEAD AT 0'  
2-STRAIGHT MOUNT SIGNAL OVERHEAD AT 12' & 24'  
2-ANGLE MOUNT SIGNAL AT 90 & 180 DEG  
1-ANGLE MOUNT C.D. PED IND AT 90 DEG  
D SIGN (SEE DETAIL SHEET)  
2-R6-11 SIGN PANELS - POLE MOUNTED 0 AND 180 DEG  
LED LUMINAIRE (FOR 40' MOUNTING HEIGHT)  
EXTEND INTO INP HH 5:  
2-6/C 14  
4-4/C 14  
\*1-3/C 14 (EVP)  
\*1-3/C 20 (EVP)  
1-3/C 14 (LUM)  
1-1/C INS. GR.  
  
INSTALL:  
1-ONE WAY EVP DETECTOR AND CONFIRMATORY  
LIGHT (PHASES 2 & 5) (ANOKA CO FURNISHED)

MATCHLINE A

4 F&I:  
PEDESTAL FOUNDATION  
1-10' SIGNAL PEDESTAL PLUS BASE  
1-ANGLE MOUNT C.D. PED IND AT 180 DEG  
1-APS PUSH BUTTON AND SIGN  
(RT ARROW) (PB2-2)  
EXTEND INTO HH 6:  
1-4/C 14  
1-2/C 14  
1-1/C INS. GR.

5  
F&I:  
PA90 POLE FOUNDATION  
X=530501.8090 Y=149926.8684  
TYPE PA90-A-30-D30-9 (DAVIT AT 350 DEG)  
1-ANGLE MOUNT SIGNAL OVERHEAD AT 0'  
1-STRAIGHT MOUNT SIGNAL OVERHEAD AT 12'  
2-ANGLE MOUNT SIGNAL AT 90 & 180 DEG  
2-ANGLE MOUNT C.D. PED IND'S AT 90 & 180 AND DEG  
D SIGN (SEE DETAIL SHEET)  
LED LUMINAIRE (FOR 40' MOUNTING HEIGHT)  
EXTEND INTO HH 8:  
2-6/C 14  
4-4/C 14  
\*1-3/C 14 (EVP)  
\*1-3/C 20 (EVP)  
1-3/C 14 (LUM)

1-ONE WAY EVP DETECTOR AND CONFIRMATORY  
LIGHT (PHASES 4 & 7) (ANOKA CO FURNISHED)

6  
F&I:  
PA100 POLE FOUNDATION  
X=526668.0246 Y=162896.1544  
TYPE PA100-A-45-030-9 (DAVIT AT 350 DEG)  
1-ANGLE MOUNT SIGNAL OVERHEAD AT 0'  
2-STRAIGHT MOUNT SIGNALS OVERHEAD AT 12' & 24'  
2-ANGLE MOUNT SIGNAL AT 90 & 180 DEG  
2-ANGLE MOUNT C.D. PED INDS AT 90 & 180 AND DEG  
D SIGN (SEE DETAIL SHEET)  
2-R6-1 SIGN PANELS - POLE MOUNTED 0 AND 180 DEG  
LED LUMINAIRE (FOR 40' MOUNTING HEIGHT)  
EXTEND INTO INP HH 12:  
2-6/C 14  
5-4/C 14  
\*1-3/C 14 (EVP)  
\*1-3/C 20 (EVP)  
1-3/C 14 (LUM)  
1-1/C INS. GR.

INSTALL:  
1-ONE WAY EVP DETECTOR AND CONFIRMATORY  
LIGHT (PHASES 1 & 6) (ANOKA CO FURNISHED)

1-1/C INS. GR.

INSTALL:  
1-ONE WAY EVP DETECTOR AND CONFIRMATORY  
LIGHT (PHASES 1 & 6) (ANOKA CO FURNISHED)

CSAH 17 (LEXINGTON AVE)  
(55 MPH)

D6-1

D6-2

MATCHLINE B



CSAH 17 (LEXINGTON AVE)  
(55 MPH)

11 of 11

**LEXINGTON AVENUE NE AT  
131ST AVENUE NE  
INTERSECTION IMPROVEMENTS**

# TRAFFIC CONTROL SIGNAL SYSTEM

# CABINET CONTROLLER



NOTES:

1. SIGNAL SYSTEM INCLUDES BATTERY- BACKUP SERVICE CABINET (BATTERIES INCLUDED).
2. FOR CONDUCTOR COLOR CODE SEE TRAFFIC SIGNAL COLOR CODE DETAIL.
3. ITEMS DENOTED WITH AN \* ARE INCLUDED IN PAYMENT FOR THE EVP SYSTEM PAY ITEM.
4. SPLICES ONLY ALLOWED IN LOOP DETECTOR CIRCUITS.
5. FOR EACH "SPARE" WIRE, COIL ENOUGH WIRE TO REACH THE END OF THE MAST ARM IN THE HANDHOLE NEAREST EACH POLE.
6. LEAVE ONE LOOP OF SLACK FOR EACH CABLE IN THE POLE BASE.

LEXINGTON PKWY & 131ST ST - WIRING DIAGRAM

**CITY OF BLAINE, MN**


**LEXINGTON AVENUE NE AT  
131ST AVENUE NE  
INTERSECTION IMPROVEMENTS**

I HEREBY CERTIFY THAT THIS PLAN, SPECIFICATION, OR REPORT WAS PREPARED BY ME OR UNDER MY DIRECT SUPERVISION AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MINNESOTA.


**SHEET  
44  
OF  
53  
SHEETS**

NOTES:

1. SIGNAL SYSTEM INCLUDES BATTERY- BACKUP SERVICE CABINET (BATTERIES INCLUDED).
2. FOR CONDUCTOR COLOR CODE SEE TRAFFIC SIGNAL COLOR CODE DETAIL.
3. ITEMS DENOTED WITH AN \* ARE INCLUDED IN PAYMENT FOR THE EVP SYSTEM PAY ITEM.
4. SPLICES ONLY ALLOWED IN LOOP DETECTOR CIRCUITS.
5. FOR EACH "SPARE" WIRE, COIL ENOUGH WIRE TO REACH THE END OF THE MAST ARM IN THE HANHOLE NEAREST EACH POLE.
6. LEAVE ONE LOOP OF SLACK FOR EACH CABLE IN THE POLE BASE.



## CABINET CONTROLLER



## REVISIONS

NO. DATE

DESCRIPTION

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_



\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_



PLOTTED/REV/SED: 7/29/2022 12:25:07 PM

PATH &amp; FILENAME: Invalid expression


CSAH 17 (LEXINGTON AVE)  
(55 MPH)F&I:  
1 1/2" CONDUIT  
12SM F/O

SCALE IN FEET

NOTES:  
 1. CONTRACTOR SHALL BORE UNDER ALL ROADWAYS. THIS  
 IS INCLUDED IN THE PAY ITEM "TRAFFIC CONTROL SIGNAL  
 SYSTEM".  
 2. SEE "SIGNAL PLAN LAYOUT" SHEET AND "FOR INFORMATION  
 ONLY" SHEET FOR EXISTING HANDHOLES AND CONDUIT.

CSAH 17 (LEXINGTON AVE)  
(55 MPH)F&I:  
1 1/2" CONDUIT  
12SM F/O

SCALE IN FEET




**CITY OF BLAINE, MN**  
**LEXINGTON AVENUE NE AT**  
**131ST AVENUE NE**  
**INTERSECTION IMPROVEMENTS**

TRAFFIC  
CONTROL  
SIGNAL  
SYSTEM

S.P. 002-617-018  
S.P. 106-020-029 & 197-020-002

**FOR INFORMATION ONLY**





# FOR INFORMATION ONLY

**CITY OF BLAINE, MN**

**LEXINGTON AVENUE NE AT  
131ST AVENUE NE  
INTERSECTION IMPROVEMENTS**

# TRAFFIC CONTROL SIGNAL SYSTEM

**SHEET  
49  
OF  
53  
SHEETS**



NOTE: THIS PLAN SHEET IS BEING PROVIDED  
FOR INFORMATIONAL PURPOSES ONLY.

COUNTY PROJ. 16-25-00

# FOR INFORMATION ONLY

TRAFFIC  
CONTROL  
SIGNAL  
SYSTEM

SHEET  
50  
OF  
53  
SHEETS

I HEREBY CERTIFY THAT THIS PLAN, SPECIFICATION,  
OR REPORT WAS PREPARED BY ME OR UNDER MY  
DIRECT SUPERVISION AND THAT I AM A DULY  
LICENSED PROFESSIONAL ENGINEER UNDER THE  
LAWS OF THE STATE OF MINNESOTA.

DATE: 7/29/2022


LIC. NO: 40845

CITY OF BLAINE, MN  
LEXINGTON AVENUE NE AT  
131ST AVENUE NE  
INTERSECTION IMPROVEMENTS


#### REVISIONS

NO. DATE DESCRIPTION

CITY OF BLAINE, MN  
LEXINGTON AVENUE NE AT  
131ST AVENUE NE  
INTERSECTION IMPROVEMENTS

TRAFFIC  
CONTROL  
SIGNAL  
SYSTEMSHEET  
51  
OF  
53  
SHEETS

NOTE: THIS PLAN SHEET IS BEING PROVIDED  
FOR INFORMATIONAL PURPOSES ONLY.



# FOR INFORMATION ONLY



CITY OF BLAINE, MN  
LEXINGTON AVENUE NE AT  
131ST AVENUE NE  
INTERSECTION IMPROVEMENTS

CSAH 17  
CROSS SECTIONS

