



# 2022 STREET SURFACE IMPROVEMENT PROJECT

## CONSTRUCTION PLANS FOR BITUMINOUS PAVEMENT RECLAMATION, AGGREGATE BASE, BITUMINOUS SURFACING, STORM SEWER, CURB AND GUTTER, GRADING AND MISCELLANEOUS CONSTRUCTION CITY OF ANOKA



THE SUBSURFACE UTILITY INFORMATION  
IN THIS PLAN IS UTILITY QUALITY LEVEL  
D. THIS QUALITY LEVEL WAS DETERMINED  
ACCORDING TO THE GUIDELINES OF  
CI/ASCE 38-2, ENTITLED "STANDARD  
GUIDELINES FOR THE COLLECTION AND  
DEPICTION OF EXISTING SUBSURFACE  
UTILITY DATA."

### GOVERNING SPECIFICATIONS

THE 2020 EDITION OF THE MINNESOTA DEPARTMENT OF TRANSPORTATION "STANDARD SPECIFICATIONS FOR CONSTRUCTION" AND THE 2018 EDITION OF THE CITY ENGINEER'S ASSOCIATION OF MINNESOTA "STANDARD SPECIFICATIONS" SHALL APPLY.

ALL FEDERAL, STATE AND LOCAL LAWS, REGULATIONS, AND ORDINANCES SHALL BE COMPLIED WITH IN THE CONSTRUCTION OF THIS PROJECT.

ALL TRAFFIC CONTROL DEVICES AND SIGNING SHALL CONFORM TO THE LATEST EDITION OF THE MINNESOTA MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES, INCLUDING THE LATEST FIELD MANUAL FOR TEMPORARY TRAFFIC CONTROL ZONE LAYOUTS.

ALL REQUIREMENTS OF THE PROJECT MANUAL FOR THE 2022 STREET SURFACE IMPROVEMENT PROJECT.


### SHEET INDEX

THIS PLAN CONTAINS 45 SHEETS

SHEET NO.	DESCRIPTION
1	TITLE SHEET
2	ESTIMATED QUANTITIES AND TABULATIONS
3	CONSTRUCTION NOTES AND PROJECT LEGEND
4	TYPICAL SECTIONS
5-6	DETAILS
7	STRUCTURE SUMMARY TABLE AND DETAILS
8	DETAILS
9	OVERALL TRAFFIC CONTROL PLAN
11	TRAFFIC CONTROL PLAN-PHASE 2-HIGHWAY 47 PROJECT AREA
10	TRAFFIC CONTROL PLAN-PHASE 1-HIGHWAY 47 PROJECT AREA
12	TRAFFIC CONTROL PLAN-RANDAL DRIVE
13	TRAFFIC CONTROL PLAN-GEORGE ENLOE PARK
14	TRAFFIC CONTROL PLAN-RUDY JOHNSON PARK
15	TRAFFIC CONTROL PLAN-FRONT AVENUE AND MARTIN STREET
16-20	CONSTRUCTION PLAN-HIGHWAY 47 PROJECT AREA
21	CONSTRUCTION PLAN-RANDAL DRIVE
22	CONSTRUCTION PLAN-GEORGE ENLOE PARK
23	CONSTRUCTION PLAN-RUDY JOHNSON PARK
24	EXISTING TOPOGRAPHY AND REMOVALS PLAN-FRONT AVENUE AND MARTIN STREET
25	CONSTRUCTION PLAN-FRONT AVENUE AND MARTIN STREET
26-32	STREET AND INTERSECTION DETAILS-HIGHWAY 47 PROJECT AREA
33	STREET AND INTERSECTION DETAILS-RANDAL DRIVE
C1	TYPICAL SECTIONS-COUNTY ROAD 30
C2	REMOVAL PLAN-COUNTY ROAD 30
C3	CONSTRUCTION PLAN-COUNTY ROAD 30
X1-X2	CROSS SECTIONS-FRONT AVENUE AND MARTIN STREET
RG1-RG7	TYPICAL RAIN GARDEN PLANS

  
APPROVED: GREG LEE  
ANOKA CITY MANAGER

I hereby certify that this plan, specification, or report was prepared by me or under my direct supervision and that I am a duly licensed Professional Engineer under the laws of the State of Minnesota.

  
CRAIG J. JOCHUM, P.E.  
HAKANSON ANDERSON  
DESIGN ENGINEER  
23461 DATE 3/3/22  
LIC. NO.

DATE	REVISION

ESTIMATED QUANTITIES												
ITEM NO.	REF. NOTES	Mn/DOT SPEC. NO.	DESCRIPTION	UNIT	TOTAL ESTIMATED QUANTITY	HIGHWAY 47 PROJECT AREA	RAIN GARDENS	RANDAL DRIVE PROJECT AREA	GEORGE ENLOE PARK PROJECT AREA	RUDY JOHNSON PARK PROJECT	FRONT AVENUE PROJECT AREA	COUNTY ROAD 30 TURN LANE
1		2021.501	MOBILIZATION	LUMP SUM	1.00	0.83	0.05	0.04	0.04	0.02	0.01	0.01
2		2102.503	PAVEMENT MARKING REMOVAL	LIN FT	31							31
3		2104.502	REMOVE MANHOLE OR CATCH BASIN	EACH	11	11						
4		2104.502	REMOVE CASTING	EACH	81	79		2				
5		2104.502	SALVAGE SIGN	EACH	1							1
6		2104.503	SAWING CONCRETE PAVEMENT - FULL DEPTH	LIN FT	1967	1774		104	70	4		15
7		2104.503	SAWING BITUMINOUS PAVEMENT - FULL DEPTH	LIN FT	944	358		101	10	60	52	363
8		2104.503	REMOVE CURB AND GUTTER	LIN FT	7494	6730		270	325	52		117
9		2104.504	REMOVE BITUMINOUS PAVEMENT	SQ YD	444	104		11	11	24		294
10	3	2104.518	REMOVE CONCRETE PAVEMENT	SQ FT	2676	1850		500	200			126
11		2106.507	EXCAVATION - COMMON	CU YD	444		250			108		86
12		2106.507	EXCAVATION - SUBGRADE	CU YD	6663	5823		406	434			
13		2106.507	SELECT GRANULAR EMBANKMENT (CV)	CU YD	22							22
14	5	2106.507	COMMON EMBANKMENT (CV)	CU YD	100					100		
15	12	2106.602	DEWATERING	EACH	4	4						
16	1	2106.607	HAUL AND STOCKPILE EXCESS MATERIAL (LV)	CU YD	8423	6986	325	487	521	104		
17		2108.604	SOIL STABILIZATION GEOGRID	SQ YD	1540			1540				
18		2112.519	SUBGRADE PREPARATION	ROAD STA	122.4	112.5		4.0				5.9
19		2112.604	SUBGRADE PREPARATION	SQ YD	2873				2403	470		
20		2123.610	STREET SWEEPER (WITH PICKUP BROOM)	HOUR	68	48		5	5	5		
21	11	2123.610	BACKHOE	HOUR	8			8				
22		2130.523	WATER	M GALLON	771	342	298	18	20	43	50	
23	10	2211.509	AGGREGATE BASE CLASS 5	TON	2832	2288		277	144	118		5
24		2215.504	FULL DEPTH RECLAMATION	SQ YD	43653	38116		1540	2403		1594	
25		2215.507	SAVAGE FULL DEPTH RECLAMATION (CV)	CU YD	5841	5293		214	334			
26		2215.507	HAUL AND DISPOSE FULL DEPTH RECLAMATION (LV)	CU YD	115						115	
27		2232.504	MILL BITUMINOUS SURFACE (1.5")	SQ YD	91	44		18		14	15	
28		2232.504	MILL BITUMINOUS SURFACE (2.0")	SQ YD	16							16
29		2357.506	BITUMINOUS MATERIAL FOR TACK COAT	GALLONS	3055	2669		108	168	26	45	39
30	6	2360.504	TYPE SP 9.5 WEARING COURSE MIXTURE (2,B) 2.5" THICK	SQ YD	115	104		11				
31		2360.509	TYPE SP 9.5 WEARING COURSE MIXTURE (2,B)	TON	4293	3617		146	228	35	267	
32		2360.509	TYPE SP 12.5 BITUMINOUS MIXTURE FOR PATCHING	TON	12							12
33		2360.509	TYPE SP 12.5 WEARING COURSE MIXTURE (4,B)	TON	90							90
34		2360.509	TYPE SP 12.5 NON WEARING COURSE MIXTURE (2,B)	TON	6710	6028		244	380	58		
35		2411.502	CONCRETE FLUME	EACH	5	4			1			
36	2	2411.618	MODULAR BLOCK RETAINING WALL	SQ FT	1250		1250					
37		2451.601	#3 WASHED CRUSHED STONE	CU YD	12		12					
38		2501.602	12" PIPE APRON	EACH	1				1			
39		2501.602	TRASH GUARD FOR 12" PIPE APRON	EACH	1				1			
40		2502.503	24" PERF PE PIPE DRAIN (SMOOTH)	LIN FT	20		20					
41		2503.503	4" PVC PIPE SEWER	LIN FT	20	20						
42		2503.503	12" RC PIPE SEWER DESIGN 3006 CLASS V	LIN FT	80	53				27		
43		2503.503	15" RC PIPE SEWER DESIGN 3006 CLASS V	LIN FT	40	40						
44		2503.503	18" RC PIPE SEWER DESIGN 3006 CLASS V	LIN FT	32	32						
45		2503.503	21" RC PIPE SEWER DESIGN 3006 CLASS III	LIN FT	8	8						
46		2503.602	CONNECT TO EXISTING STORM SEWER	EACH	14	12			2			
47		2504.602	CONNECT TO EXISTING WATERMAIN	EACH	23	23						
48		2504.602	6" GATE VALVE AND BOX	EACH	13	13						
49		2504.602	8" GATE VALVE AND BOX	EACH	10	10						
50		2506.502	CASTING ASSEMBLY	EACH	93	86	4	2		1		
51	8	2506.502	CONSTRUCT SANITARY STRUCTURE DESIGN 4007	EACH	8	7	1					
52		2506.503	CONSTRUCT DRAINAGE STRUCTURE DESIGN H	LIN FT	9.7	9.7						
53	9	2506.503	CONSTRUCT SANITARY STRUCTURE DESIGN 4007	LIN FT	4.5	4.5						
54		2506.503	CONSTRUCT DRAINAGE STRUCTURE DESIGN 4021	LIN FT	30.0	30.0						
55		2506.503	CONSTRUCT DRAINAGE STRUCTURE DESIGN 48-4020	LIN FT	9.7	4.2			5.5			
56		2506.602	GROUT CATCH BASIN OR MANHOLE	HOUR	29	29						
57		2506.602	MANHOLE SURFACE RESTORATION	LIN FT	120	120						
58		2511.507	RANDOM RIPRAP CLASS II	CU YD	5.4				5.4			
59		2521.518	4" CONCRETE WALK	SQ FT	657	216		200			241	
60		2521.518	6" CONCRETE WALK	SQ FT	320	63		103	80		74	

ESTIMATED QUANTITIES												
ITEM NO.	REF. NOTES	Mn/DOT SPEC. NO.	DESCRIPTION	UNIT	TOTAL ESTIMATED QUANTITY	HIGHWAY 47 PROJECT AREA	RAIN GARDENS	RANDAL DRIVE PROJECT AREA	GEORGE ENLOE PARK PROJECT AREA	RUDY JOHNSON PARK PROJECT	FRONT AVENUE PROJECT AREA	COUNTY ROAD 30 TURN LANE
61		2531.503	CONCRETE CURB AND GUTTER DESIGN B612	LIN FT	575					325	250	
62		2531.503	CONCRETE CURB AND GUTTER DESIGN B618	LIN FT	942	278				16		378
63		2531.503	CONCRETE CURB AND GUTTER DESIGN D418	LIN FT	6452	6452						
64		2531.504	6" CONCRETE DRIVEWAY PAVEMENT	SQ YD	261	205			56			
65	4	2531.504	8" CONCRETE DRIVEWAY PAVEMENT	SQ YD	67	47				20		
66		2531.618	TRUNCATED DOMES	SQ FT	76	16				24		16
67		2563.601	TRAFFIC CONTROL	LUMP SUM	1.00	0.83	0.05	0.04	0.04	0.02	0.01	0.01
68		2564.502	INSTALL SIGN	EACH	1							1
69		2565.602	RIGID PVC LOOP DETECTOR 6'X6'	EACH	1		</td					

GENERAL CONSTRUCTION AND SOILS NOTES:

- IN AREAS OF STREET CONSTRUCTION, THE EXPOSED SAND SHALL BE SURFACE COMPAKTED TO AT LEAST 100% OF THE STANDARD PROCTOR MAXIMUM DRY DENSITY, ASTM D698, IN AT LEAST THE UPPER THREE FEET.
- UNLESS OTHERWISE RECOMMENDED IN THESE PLANS, THE GRADING SUBGRADE SHALL BE CONSTRUCTED OF SUITABLE GRADING MATERIAL. THE FILL SHALL BE PLACED IN 8" TO 10" LOOSE LIFTS, AND COMPAKTED TO 100% OF THE STANDARD PROCTOR MAXIMUM DRY DENSITY.
- SUITABLE GRADING MATERIAL FOR THIS PROJECT SHALL CONSIST OF ALL SOILS ENCOUNTERED WITH THE EXCEPTION OF TOPSOIL, SILT, DEBRIS, ORGANIC MATERIAL AND OTHER UNSTABLE MATERIAL.
- WHEN PLACING NEW PAVEMENT ADJACENT TO INPLACE PAVEMENT CUT VERTICALLY TO THE BOTTOM OF INPLACE SURFACING OR TOP OF GRADING SUBGRADE, WHICHEVER IS DEEPER, AT A 1(V):2(H) TO THE BOTTOM OF EXCAVATION.
- PROVIDE A SAW CUT WHEN PLACING NEW PAVEMENT ADJACENT TO INPLACE PAVEMENT AND AT TERMINI OF CONSTRUCTION TO ENSURE A UNIFORM JOINT.
- BITUMINOUS AND CONCRETE ITEMS DISTURBED BY CONSTRUCTION SHALL BECOME THE PROPERTY OF THE CONTRACTOR AND SHALL BE DISPOSED OF IN ACCORDANCE WITH MN/DOT SPEC. 2104.
- USE TACK COAT BETWEEN ALL BITUMINOUS MIXTURES. THE BITUMINOUS TACK COAT MATERIAL SHALL BE APPLIED AT A UNIFORM RATE OF 0.04 GAL/SY TO 0.06 GAL/SY BETWEEN BITUMINOUS LAYERS. THE APPLICATION RATES ARE FOR UNDILUTED EMULSIONS.
- PERFORMANCE GRADED (PG) ASPHALT BINDER PG 58S-28, PER MN/DOT SPEC. 3151, SHALL BE USED FOR ALL BITUMINOUS MIXES ON THIS PROJECT.
- THE BITUMINOUS MIXTURES SHALL MEET THE REQUIREMENTS OF SPECIFICATIONS 2360 AND 3139.
- IF NECESSARY, THE UTILITY COMPANIES WILL RELOCATE THEIR FACILITIES CONCURRENTLY WITH THE CONSTRUCTION OPERATIONS UNDER THIS CONTRACT. CONTRACTOR SHALL SCHEDULE CONSTRUCTION IN COOPERATION WITH UTILITY RELOCATION.
- CONTRACTOR SHALL REMOVE AND TEMPORARILY PLACE ALL MAILBOXES AT AN ENGINEER APPROVED LOCATION AS NEEDED DURING CONSTRUCTION. THIS WORK SHALL BE INCIDENTAL.
- SAWCUT DRIVEWAYS AND SIDEWALKS AT THE DISCRETION OF THE ENGINEER.
- SUBCUT AREAS AND LIMITS SHALL BE DETERMINED IN THE FIELD BY THE ENGINEER.
- ALL BITUMINOUS PAVEMENT THAT NEEDS TO BE REMOVED, BUT CANNOT BE RECLAIMED, TO COMPLETE THE CONSTRUCTION SHALL BE INCIDENTAL, UNLESS OTHERWISE NOTED ON THE PLANS.
- CURB AND SIDEWALK REPLACEMENT AREAS WILL BE DETERMINED IN THE FIELD BY THE ENGINEER. CONTRACTOR WILL BE PAID TO SAWCUT SIDEWALK OR CONCRETE CURB AND GUTTER PER ITEM 2104-SAWING CONCRETE PAVEMENT-FULL DEPTH.
- SEE SECTION 01 35 00, SPECIAL PROJECT PROCEDURES, OF THE PROJECT MANUAL FOR ADDITIONAL INFORMATION REGARDING MEASUREMENT AND PAYMENT ITEMS.
- CONTRACTOR SHALL PREPARE SUBGRADE UNDER CONCRETE CURB AND GUTTER AND SIDEWALKS WITH SUITABLE GRADING MATERIAL. PREPARATION OF THE SUBGRADE SHALL BE INCIDENTAL.
- THE CONCRETE MIX DESIGNS FOR THIS PROJECT SHALL BE 3F52 FOR HAND-FORMED CONCRETE AND 3F32 FOR MACHINE FORMED CONCRETE. ENTRAINED AIR SHALL BE MAINTAINED BETWEEN 5% AND 7%. COARSE AGGREGATE SHALL BE CLASS A AGGREGATE.
- BITUMINOUS DRIVEWAYS SHALL BE CONSTRUCTED WITH A MINIMUM OF 2.5" BITUMINOUS WEAR COURSE (SPWEA240B) OVER 4" RECLAIMED AGGREGATE BASE. DRIVEWAY PAVEMENT SHALL BE PAID PER ITEM 2360-TYPE SP 9.5 WEARING COURSE MIXTURE (2,B) 2.5" THICK. PLACEMENT OF THE RECLAIMED AGGREGATE BASE SHALL BE INCIDENTAL. CONCRETE DRIVEWAYS SHALL BE CONSTRUCTED WITH A MINIMUM OF 6" OF CONCRETE DRIVEWAY PAVEMENT OVER 4" OF RECLAIMED AGGREGATE BASE.
- IN ALL DISTURBED AREAS, EXCEPT RUDY JOHNSON PARK, THE CONTRACTOR SHALL SALVAGE AND REPLACE ALL EXISTING TOPSOIL. ALL DISTURBED AREAS SHALL BE RESTORED WITH SEED MIXTURE 25-131 AT A RATE OF 220 LBS/ACRE, TYPE 3 FERTILIZER AT A RATE OF 400 LBS/ACRE AND HYDRAULIC BONDED FIBER MATRIX AT A RATE OF 3500 LBS/ACRE. ALL RESTORATION WORK SHALL BE MEASURED BY THE SQUARE YARD AND PAID PER ITEM 2575-SITE RESTORATION.
- IN RUDY JOHNSON PARK, CONTRACTOR SHALL PLACE 4 INCHES OF LOAM TOPSOIL BORROW OVER ALL DISTURBED AREAS. ALL DISTURBED AREAS, EXCEPT THE INFILTRATION BASIN, SHALL BE RESTORED WITH SEED MIXTURE 25-131 AT A RATE OF 220 LBS/ACRE, TYPE 3 FERTILIZER AT A RATE OF 400 LBS/ACRE AND HYDRAULIC BONDED FIBER MATRIX AT A RATE OF 3500 LBS/ACRE. ALL RESTORATION WORK SHALL BE MEASURED BY THE SQUARE YARD AND PAID PER ITEM 2575-SITE RESTORATION. THE INFILTRATION BASIN SHALL BE RESTORED AS DESCRIBED ON THE PLANS AND INCLUDE TYPE 3 FERTILIZER AS DESCRIBED ABOVE.

GENERAL EROSION CONTROL NOTES:

- EROSION CONTROL SHALL CONFORM TO THE MN/DOT EROSION CONTROL HANDBOOK.
- PRIOR TO ANY CONSTRUCTION ACTIVITIES, THE CONTRACTOR SHALL ACQUIRE THE MPCA NPDDES CONSTRUCTION STORMWATER GENERAL PERMIT.
- THE CONTRACTOR SHALL INSTALL EROSION AND SEDIMENT CONTROL FACILITIES (BMP'S) PRIOR TO GRADING AND REMOVAL ACTIVITIES. BMP'S SHALL BE MAINTAINED FOR THE DURATION OF CONSTRUCTION ACTIVITIES AND POTENTIAL FOR EROSION HAS PASSED.
- THE CONTRACTOR SHALL SCHEDULE THEIR OPERATIONS TO MINIMIZE THE AMOUNT OF DISTURBED AREA AT ANY GIVEN TIME.
- BMP'S SHALL BE INSPECTED DAILY BY THE CONTRACTOR. OBSERVATIONS SHALL BE RECORDED IN AN INSPECTION LOG.
- ALL EROSION AND SEDIMENT CONTROL MEASURES SHALL BE PROPERLY DISPOSED OF WITHIN THIRTY (30) DAYS AFTER FINAL SITE STABILIZATION.
- THE CONTRACTOR SHALL FILE A NOTICE OF TERMINATION WITH THE MPCA AFTER FINAL STABILIZATION HAS BEEN APPROVED.

LEGEND	
PROPERTY LINE/RIGHT-OF-WAY	—> —>
EXISTING STORM SEWER	—> —> —>
EXISTING SANITARY SEWER	—> —>
EXISTING WATERMAIN	—> —> —>
EXISTING WATER VALVE	—> —>
EXISTING CATCH BASIN	—> —>
EXISTING SANITARY SEWER MANHOLE	—> —>
EXISTING STORM SEWER MANHOLE	—> —>
HYDRANT	—> —>
EXISTING CONCRETE CURB & GUTTER	=====
DETAIL NUMBER	(X)
SHEET NUMBER	(X)
BITUMINOUS CORING LOCATION	(●)
SOIL BORING LOCATION	(●)

DATE	REVISION
I hereby certify that this plan, specification, or report was prepared by me or under my direct supervision and that I am a duly Licensed Professional Engineer under the laws of the State of Minnesota.	
CRAIG J. JOCHUM, P.E. Date 3/3/22	
Lic. No. 23461	

DESIGNED BY: TAE
DRAWN BY: TAE
CHECKED BY: CJJ




**Hakanson Anderson**  
Civil Engineers and Land Surveyors  
3601 Thurston Ave., Anoka, Minnesota 55303  
763-427-5860 FAX 763-427-0520  
www.hakanson-anderson.com

2022 STREET SURFACE  
IMPROVEMENT PROJECT

CONSTRUCTION NOTES AND  
PROJECT LEGEND  
CITY OF ANOKA, MINNESOTA

SHEET  
3  
OF  
33  
SHEETS  
AN393



REFERENCE NOTES:

- ① CONTRACTOR SHALL RECLAIM THE EXISTING BITUMINOUS PAVEMENT, AGGREGATE BASE AND SUBGRADE MATERIAL TO THE RECLAMATION DEPTH SHOWN ON THE STREET SUMMARY TABLE. ACTUAL DEPTH MAY NEED TO BE ADJUSTED BASED ON THE EXISTING DEPTHS OF THE BITUMINOUS AND AGGREGATE BASE. THIS WORK SHALL BE PAID PER ITEM 2215-FULL DEPTH RECLAMATION.
- ② IN THE HIGHWAY 47 PROJECT AREA, ON RANDAL DRIVE AND AT GEORGE ENLOE PARK, CONTRACTOR SHALL SALVAGE RECLAM MATERIAL AND EXCAVATE AND DISPOSE OF SUBGRADE MATERIAL TO THE SUBGRADE EXCAVATION DEPTH SHOWN ON THE STREET SUMMARY TABLE. SALVAGED RECLAM MATERIAL SHALL THEN BE PLACED AND COMPACTED TO THE RECLAMATION DEPTH SHOWN ON THE STREET SUMMARY TABLE. SALVAGING AND REPLACING THE RECLAM MATERIAL SHALL BE PAID PER ITEM 2215-SALVAGE FULL DEPTH RECLAMATION (CV), EXCAVATING THE SUBGRADE MATERIAL SHALL BE PAID PER ITEM 2106-EXCAVATION-SUBGRADE AND DISPOSING OF THE SUBGRADE MATERIAL AT SUNNY ACRES PARK SHALL BE PAID PER ITEM 2106-HAUL AND STOCKPILE EXCESS MATERIAL (LV).
- ③ ON FRONT AVENUE AND MARTIN STREET, CONTRACTOR SHALL SHAPE THE RECLAM MATERIAL SUCH THAT THE EDGE OF THE PROPOSED ROAD MATCHES THE EXISTING EDGE OF THE ROAD WITH A MAXIMUM CROSS SLOPE OF 4.50%. EXCESS RECLAM MATERIAL SHALL BECOME THE PROPERTY OF THE CONTRACTOR AND BE DISPOSED OF OFF SITE. SHAPING THE RECLAM MATERIAL SHALL BE PAID PER ITEM 2112-SUBGRADE PREPARATION AND DISPOSING OF THE RECLAM MATERIAL SHALL BE PAID PER ITEM 2215-HAUL AND DISPOSE FULL DEPTH RECLAMATION (LV).
- ④ COMPACT TO 100% STANDARD PROCTOR DENSITY.
- ⑤ A COMBINATION OF RECLAM MATERIAL AND CLASS 5 AGGREGATE BASE SHALL BE USED TO CONSTRUCT RANDAL DRIVE TO THE DEPTH SHOWN.
- ⑥ IN AREAS WHERE THE CROSS SLOPES CANNOT BE CONSTRUCTED, WITH THE CROWN AT THE CENTERLINE OF THE ROAD, BETWEEN 2.00% AND 4.00%, SPECIAL SECTIONS WILL HAVE TO BE CONSTRUCTED WITH THE CROWN SHIFTED AWAY FROM THE CENTERLINE OF THE ROAD. THE STREETS WITH SPECIAL SECTIONS ARE DETAILED IN THE PLANS.
- ⑦ SUBGRADE EXCAVATION DEPTH ASSUMES THAT THE CROWN IS NOT CONSISTENT THROUGHOUT THE PROJECT. MATERIAL SHALL BE EXCAVATED SUCH THAT THE PROPOSED SECTIONS SHOWN ON ④ AND ⑤ CAN BE CONSTRUCTED.
- ⑧ SUBGRADE EXCAVATION DEPTH ASSUMES THAT THE EXCAVATION DEPTH IS NOT CONSISTENT THROUGHOUT THE PARKING LOT. MATERIAL SHALL BE EXCAVATED SUCH THAT THE PROPOSED SECTION SHOWN ON ⑦ CAN BE CONSTRUCTED TO THE PROPOSED GRADES SHOWN ON SHEET 22.

DATE 3/8/22  
REVISION ADDENDUM NO. 1

I hereby certify that this plan, specification, or report was prepared by me or under my direct supervision and that I am a duly licensed Professional Engineer under the laws of the State of Minnesota.  
CRAIG J. JOCHUM, P.E.  
Date 3/3/22  
Lic. No. 23461

DESIGNED BY:  
TAE  
DRAWN BY:  
TAE  
CHECKED BY:  
CJJ







Hakanson Anderson  
Civil Engineers and Land Surveyors  
3601 Thurston Ave., Anoka, Minnesota 55303  
763-427-5860 FAX 763-427-0520  
www.hakanson-anderson.com

2022 STREET SURFACE  
IMPROVEMENT PROJECT

TYPICAL SECTIONS  
CITY OF ANOKA, MINNESOTA

SHEET 4 OF 33  
AN393





REFERENCE NOTES:

① HIGH DENSITY POLYETHYLENE ADJUSTMENT RINGS SHALL BE USED FOR ALL STORM SEWER MANHOLES WITH SOLID LIDS (NON-INLET TYPE). ALL INLET TYPE STORM SEWER CASTINGS SHALL USE CONCRETE ADJUSTMENT RINGS. THE CONTRACTOR SHALL USE STANDARD AVAILABLE RING THICKNESSES THAT MINIMIZE THE NUMBER OF RINGS REQUIRED. A MAXIMUM OF 3 RINGS SHALL BE USED FOR ADJUSTMENT. THE MINIMUM ADJUSTMENT HEIGHT SHALL BE 4 INCHES AND THE MAXIMUM ADJUSTMENT HEIGHT SHALL BE 8 INCHES.

DATE	REVISION	<p>I hereby certify that this plan, specification, or report          prepared by me or under my direct supervision and I          am a duly Licensed Professional Engineer under the laws          of the State of Minnesota.</p> <p><i>[Signature]</i>          CRAIG J. JOCHUM, P.E.          Date 3/3/22      Lic. No. 2345</p>	
------	----------	---	--



**Hakanson Anderson**  
Civil Engineers and Land Surveyors  
3601 Thurston Ave., Anoka, Minnesota 55303  
763-427-5860 FAX 763-427-0520  
[www.hakanson-anderson.com](http://www.hakanson-anderson.com)

## 2022 STREET SURFACE IMPROVEMENT PROJECT


## DETAILS


SHEET  
6  
OF  
33  
SHEETS



EXISTING STRUCTURE SUMMARY TABLE						
STRUCTURE NO.	REF. NOTES	STREET	STRUCTURE TYPE	APPROXIMATE ADJUSTMENT RING HEIGHT (INCHES)	PROPOSED NEENAH CASTING	PROPOSED RING TYPE
16-1	2,4	MCKINLEY STREET	STM/MH	14	R-1733	HDPE
16-2	3	MCKINLEY STREET	SAN/MH	11	R-1733	HDPE
16-3	2,9	MCKINLEY STREET	CB	N/A	N/A	N/A
16-4	2,4	MCKINLEY STREET	STM/MH	10	R-1733	HDPE
16-5	2,9	MCKINLEY STREET	CB	N/A	N/A	N/A
16-6	3,11	MCKINLEY STREET	SAN/MH	7	R-1733	HDPE
16-7	2,5,9	MCKINLEY STREET	CB	6	R-3250-DVSP	CONCRETE
16-8	2,4	MCKINLEY STREET	STM/MH	10	R-1733	HDPE
16-9	2,5,9	MCKINLEY STREET	CB	6	R-3250-DVSP	CONCRETE
16-10	3	MCKINLEY CIRCLE	SAN/MH	11	R-1733	HDPE
16-11	2,5,9	MCKINLEY STREET	CB	4	R-3250-DVSP	CONCRETE
16-12	3,11	MCKINLEY STREET	SAN/MH	12	R-1733	HDPE
16-13	2,4	MCKINLEY STREET	STM/MH	15	R-1733	HDPE
16-14	3,11	MCKINLEY STREET	SAN/MH	6	R-1733	HDPE
16-15	2,4,13	MCKINLEY STREET	STM/MH	8	R-1733	HDPE
16-16	2,5,9	MCKINLEY STREET	CB	4	R-3250-DVSP	CONCRETE
16-17	2,4	MCKINLEY STREET	STM/MH	12	R-1733	HDPE
16-18	2,5,9	MCKINLEY STREET	CB	5	R-3250-DVSP	CONCRETE
16-19	3,11	MCKINLEY STREET	SAN/MH	10	R-1733	HDPE
16-20	3,11	MCCANN AVENUE	SAN/MH	13	R-1733	HDPE
16-21	3,11,12	MCCANN AVENUE	SAN/MH	15 - EXISTING 3 - PROPOSED	R-1733	HDPE
16-22	3,16	MCCANN AVENUE	SAN/MH	6	R-1733	HDPE
16-23	3,11	MCCANN AVENUE	SAN/MH	9	R-1733	HDPE
16-24	3,11	MCCANN AVENUE	SAN/MH	9	R-1733	HDPE
16-25	3,11	MCCANN AVENUE	SAN/MH	9	R-1733	HDPE
16-26	3	RUM RIVER DRIVE	SAN/MH	11	R-1733	HDPE
17-1	2,4	MCKINLEY STREET	STM/MH	8	R-1733	HDPE
17-2	3,11,12	MCKINLEY STREET	SAN/MH	18 - EXISTING 6 - PROPOSED	R-1733	HDPE
17-3	2,5,9	BAILEY LANE	CB	3	R-3250-DVSP	CONCRETE
17-4	6,9,14,15	BAILEY LANE	CB	N/A	MN/DOT 790-2 MN/DOT 716	N/A
17-5	6,9,14,15	BAILEY LANE	CB	N/A	MN/DOT 790-2 MN/DOT 716	N/A
17-6	2,4	BAILEY LANE	STM/MH	20	R-1733	HDPE
17-7	2,4	RUM RIVER DRIVE	STM/MH	3 - EXISTING 6 - PROPOSED	R-1733-1	HDPE
17-8	3,11	RUM RIVER DRIVE	SAN/MH	11	R-1733	HDPE
17-9	3,11	RUM RIVER DRIVE	SAN/MH	6	R-1733	HDPE
17-10	3,11	RUM RIVER DRIVE	SAN/MH	7	R-1733	HDPE
17-11	3,11	RUM RIVER DRIVE	SAN/MH	8	R-1733	HDPE
17-12	3,11	BAILEY LANE	SAN/MH	6	R-1733	HDPE
17-13	5,6,7,9	RUM RIVER DRIVE	CB/MH	6	R-3250-DVSP	CONCRETE
17-14	5,6,7,9	RUM RIVER DRIVE	CB	6	R-3250-DVSP	CONCRETE
17-15	3,11	RUM RIVER DRIVE	SAN/MH	0 - EXISTING 3 - PROPOSED	R-1733-1	HDPE
17-16	3,16	RUM RIVER DRIVE	SAN/MH	11	R-1733	HDPE
18-1	3,11	RUM RIVER DRIVE	SAN/MH	4	R-1733	HDPE
18-2	6,9,14	RUM RIVER DRIVE	CB	N/A	MN/DOT 790-2 MN/DOT 716	N/A
18-3	3	RUM RIVER DRIVE	SAN/MH	6	R-1733	HDPE
18-4	6,9,14	RUM RIVER DRIVE	CB/MH	N/A	MN/DOT 790-2 MN/DOT 716	N/A
18-5	3	RUM RIVER DRIVE	SAN/MH	10	R-1733	HDPE
18-6	3,11	RUM RIVER DRIVE	SAN/MH	9	R-1733	HDPE
18-7	3,16	RUM RIVER DRIVE	SAN/MH	4	R-1733	HDPE

CASTING ASSEMBLY SUMMARY					
STRUCTURE TYPE	MN/DOT RING CASTING NUMBER	MN/DOT CURB BOX CASTING NUMBER	MN/DOT GRATE OR COVER CASTING NUMBER	NEENAH CASTING NUMBER	CASTING QUANTITY
SANITARY SEWER MANHOLE	700-7	N/A	N/A	R-1733	48
SANITARY SEWER MANHOLE	700-4	N/A	N/A	R-1733-1	3
STORM SEWER MANHOLE	700-7	N/A	N/A	R-1733	14
STORM SEWER MANHOLE	700-4	N/A	N/A	R-1733-1	2
CATCH BASIN	N/A	823A	816	R-3250-DVSP	13
CATCH BASIN	N/A	823A	816	R-3250-DVSP (4" FRAME)	2
CATCH BASIN	790-2	N/A	716	N/A	7
FRENCH DRAIN	N/A	N/A	N/A	R-2501-A	5
				TOTAL	94

EXISTING STRUCTURE SUMMARY TABLE						
STRUCTURE NO.	REF. NOTES	STREET	STRUCTURE TYPE	APPROXIMATE ADJUSTMENT RING HEIGHT (INCHES)	PROPOSED NEENAH CASTING	PROPOSED RING TYPE
19-1	3,16	RUM RIVER DRIVE	SAN/MH	5	R-1733	HDPE
19-2	3	RUM RIVER DRIVE	SAN/MH	4	R-1733	HDPE
19-3	3,12	RUM RIVER DRIVE	SAN/MH	24 - EXISTING 6 - PROPOSED	R-1733	HDPE
19-4	3	DUNHAM DRIVE	SAN/MH	9	R-1733	HDPE
19-5	3,11	DUNHAM DRIVE	SAN/MH	6	R-1733	HDPE
19-6	3,11	DUNHAM DRIVE	SAN/MH	9	R-1733	HDPE
19-7	2,5,9	RUM RIVER DRIVE	CB	3	R-3250-DVSP	CONCRETE
19-8	2,5,9	RUM RIVER DRIVE	CB	5	R-3250-DVSP	CONCRETE
19-9	2,4	RUM RIVER DRIVE	STM/MH	10	R-1733	HDPE
19-10	2,4	RUM RIVER DRIVE	STM/MH	16	R-1733	HDPE
19-11	3,11	RUM RIVER DRIVE	SAN/MH	7	R-1733	HDPE
19-12	2,4	WILSON STREET	STM/MH	10	R-1733	HDPE
19-13	2,5,9	WILSON STREET	CB	5	R-3250-DVSP	CONCRETE
19-14	3,11	WILSON STREET	SAN/MH	6	R-1733	HDPE
19-15	5,6,7,9	WILSON STREET	CB	7	R-3250-DVSP (4" FRAME)	CONCRETE
19-16	2,4	WILSON STREET	STM/MH	4	R-1733-1	HDPE
19-17	5,6,7,9	WILSON STREET	CB	6	R-3250-DVSP (4" FRAME)	CONCRETE
19-18	2,4	WILSON STREET	STM/MH	5	R-1733	HDPE
19-19	3,16	WILSON STREET	SAN/MH	4	R-1733	HDPE
20-1	2,5,9	RUM RIVER DRIVE	CB	4	R-3250-DVSP	CONCRETE
20-2	2,4	RUM RIVER DRIVE	STM/MH	9	R-1733	HDPE
20-3	3	RUM RIVER DRIVE	SAN/MH	7	R-1733	HDPE
20-4	2,5,9	RUM RIVER DRIVE	CB	5	R-3250-DVSP	CONCRETE
20-5	3,11	RUM RIVER DRIVE	SAN/MH	8	R-1733	HDPE
20-6	3	RUM RIVER DRIVE	SAN/MH	8	R-1733	HDPE
20-7	3	RUM RIVER DRIVE	SAN/MH	5	R-1733	HDPE
20-8	3,16	COOLIDGE STREET	SAN/MH	8	R-1733	HDPE
20-9	3,11	COOLIDGE STREET	SAN/MH	9	R-1733	HDPE
20-10	6,9,14	COOLIDGE STREET	CB/MH	N/A	MN/DOT 790-2 MN/DOT 716	N/A
20-11	6,9,14	ROSEBERRY PLACE	CB/MH	N/A	MN/DOT 790-2 MN/DOT 716	N/A
20-12	6,9,14	ROSEBERRY PLACE	CB	N/A	MN/DOT 790-2 MN/DOT 716	N/A
20-13	3,11	COOLIDGE STREET	SAN/MH	5	R-1733	HDPE
20-14	3,11	COOLIDGE STREET	SAN/MH	14	R-1733	HDPE
20-15	3,11,12	COOLIDGE STREET	SAN/MH	15 - EXISTING 3 - PROPOSED	R-1733	HDPE
20-16	2,9	COOLIDGE STREET	CB/MH	N/A	N/A	N/A
20-17	3,11	COOLIDGE STREET	SAN/MH	9	R-1733	HDPE
20-18	3,11	ROSEBERRY PLACE	SAN/MH	5	R-1733	HDPE
20-19	3,11	ROSEBERRY PLACE	SAN/MH	3	R-1733	HDPE
20-20	3,16	RUM RIVER DRIVE	SAN/MH	6	R-1733	HDPE
20-21	3	RUM RIVER DRIVE	SAN/MH	2	R-1733-1	HDPE
21-1	3	RANDAL DRIVE	SAN/MH	9	R-1733	HDPE</







REFERENCE NOTES:

- ① PAVEMENT SHALL REMAIN UNTIL THE BITUMINOUS NON WEARING COURSE IS CONSTRUCTED IN PHASE 1.
- ② ANY WORK REQUIRED IN THE RIGHT-OF-WAY OF HIGHWAY 47 WILL REQUIRE A PERMIT FROM MN/DOT. IF ANY LANE CLOSURES ARE REQUIRED, THEY WILL ONLY BE ALLOWED DURING THE HOURS OF 9:00 A.M. AND 2:30 P.M. THE CONTRACTOR SHALL COMPLETELY REMOVE ALL TRAFFIC CONTROL, FOR THE LANE CLOSURE, IN THE MN/DOT RIGHT-OF-WAY BETWEEN THE HOURS OF 2:30 P.M. AND 9:00 A.M. NO ADDITIONAL PAYMENT WILL BE MADE IF TRAFFIC CONTROL LAYOUTS ARE NEEDED TO COMPLETE THE WORK.
- ③ AS PART OF THE MN/DOT HIGHWAY 10 PROJECT, MN/DOT WILL BE PLACING A TEMPORARY TRAFFIC SIGNAL AT THE INTERSECTION OF HIGHWAY 47 AND MCKINLEY STREET. IN ADDITION TO THE TRAFFIC SIGNAL, DUNHAM DRIVE AND MCCANN AVENUE WILL BE CLOSED AT HIGHWAY 47. THE SIGNAL AND THE CLOSURES ARE EXPECTED TO BE IN PLACE BY MAY 1, 2022.

200 0 200 400  
SCALE IN FEET




Hakanson Anderson  
Civil Engineers and Land Surveyors  
3601 Thurston Ave., Anoka, Minnesota 55303  
763-427-5860 FAX 763-427-0520  
www.hakanson-anderson.com


2022 STREET SURFACE  
IMPROVEMENT PROJECT

TRAFFIC CONTROL PLAN-PHASE 1  
HIGHWAY 47 PROJECT AREA  
CITY OF ANOKA, MINNESOTA

SHEET 10  
OF  
33  
SHEETS  
AN393




LEGEND




REFERENCE NOTES:

- ① PAVEMENT SHALL NOT BE RECLAIMED IN THE PHASE 2 WORK ZONE UNTIL THE BITUMINOUS NON WEARING COURSE HAS BEEN CONSTRUCTED IN THE PHASE 1 WORK ZONE SHOWN ON SHEET 10.
- ② ANY WORK REQUIRED IN THE RIGHT-OF-WAY OF HIGHWAY 47 WILL REQUIRE A PERMIT FROM MN/DOT. IF ANY LANE CLOSURES ARE REQUIRED, THEY WILL ONLY BE ALLOWED DURING THE HOURS OF 9:00 A.M. AND 2:30 P.M. THE CONTRACTOR SHALL COMPLETELY REMOVE ALL TRAFFIC CONTROL, FOR THE LANE CLOSURE, IN THE MN/DOT RIGHT-OF-WAY BETWEEN THE HOURS OF 2:30 P.M. AND 9:00 A.M. NO ADDITIONAL PAYMENT WILL BE MADE IF TRAFFIC CONTROL LAYOUTS ARE NEEDED TO COMPLETE THE WORK.
- ③ AS PART OF THE MN/DOT HIGHWAY 10 PROJECT, MN/DOT WILL BE PLACING A TEMPORARY TRAFFIC SIGNAL AT THE INTERSECTION OF HIGHWAY 47 AND MCKINLEY STREET. IN ADDITION TO THE TRAFFIC SIGNAL, DUNHAM DRIVE AND MCCANN AVENUE WILL BE CLOSED AT HIGHWAY 47. THE SIGNAL AND THE CLOSURES ARE EXPECTED TO BE IN PLACE BY MAY 1, 2022.



DATE	REVISION
	I hereby certify that this plan, specification, or report was prepared by me or under my direct supervision and that I am a duly Licensed Professional Engineer under the laws of the State of Minnesota.
CRAIG J. JOCHUM, P.E.	DESIGNED BY: TAE DRAWN BY: TAE CHECKED BY: CJJ
Date 3/3/22	Lic. No. 23461




**Hakanson Anderson**  
Civil Engineers and Land Surveyors  
3601 Thurston Ave., Anoka, Minnesota 55303  
763-427-5860 FAX 763-427-0520  
www.hakanson-anderson.com

2022 STREET SURFACE  
IMPROVEMENT PROJECT

TRAFFIC CONTROL PLAN  
RANDAL DRIVE  
CITY OF ANOKA, MINNESOTA

SHEET 12 OF 33  
AN393




LEGEND



50 0 50 100  
SCALE IN FEET

DATE	REVISION	I hereby certify that this plan, specification, or report was prepared by me or under my direct supervision and that I am a duly Licensed Professional Engineer under the laws of the State of Minnesota.		
		CRAIG J. JOCHUM, P.E.	DESIGNED BY: TAE	
		Date 3/3/22	DRAWN BY: TAE	
			CHECKED BY: CJJ	
		Lic. No. 23461		




**Hakanson Anderson**  
Civil Engineers and Land Surveyors  
3601 Thurston Ave., Anoka, Minnesota 55303  
763-427-5860 FAX 763-427-0520  
[www.hakanson-anderson.com](http://www.hakanson-anderson.com)

3601 Thurston Ave., Anoka, Minnesota 55303  
763-427-5860 FAX 763-427-0520  
[www.hakanson-anderson.com](http://www.hakanson-anderson.com)


2022 STREET SURFACE  
IMPROVEMENT PROJECT

TRAFFIC CONTROL PLAN  
GEORGE ENLOE PARK  
CITY OF ANOKA, MINNESOTA

SHEET  
13  
OF  
33  
SHEETS



LEGEND



50 0 50 100  
SCALE IN FEET

DATE	REVISION	I hereby certify that this plan, specification, or report was prepared by me or under my direct supervision and that I am a duly Licensed Professional Engineer under the laws of the State of Minnesota.		
		CRAIG J. JOCHUM, P.E.	DESIGNED BY: TAE	
		Lic. No. 23461	DRAWN BY: TAE	

Date 3/3/22




**Hakanson Anderson**  
Civil Engineers and Land Surveyors  
3601 Thurston Ave., Anoka, Minnesota 55303  
763-427-5860 FAX 763-427-0520  
[www.hakanson-anderson.com](http://www.hakanson-anderson.com)

2022 STREET SURFACE  
IMPROVEMENT PROJECT

TRAFFIC CONTROL PLAN  
RUDY JOHNSON PARK  
CITY OF ANOKA, MINNESOTA

SHEET  
14  
OF  
33  
SHEETS



Mar 04, 2022 - 8:37 am  
:\MUNICIPAL\AN393\ENGINEERING\AN393\_TRAFFIC.dwg

DATE	REVISION	I hereby certify that this plan, specification, or report prepared by me or under my direct supervision and I am a duly Licensed Professional Engineer under the laws of the State of Minnesota.  Craig J. Jochum, P.E. Date 3/3/22      Lic. No. 2345
------	----------	--

61



**Hakanson Anderson**  
Civil Engineers and Land Surveyors  
3601 Thurston Ave., Anoka, Minnesota 55301  
763-427-5860 FAX 763-427-0520  
[www.hakanson-anderson.com](http://www.hakanson-anderson.com)

## 2022 STREET SURFACE IMPROVEMENT PROJECT

TRAFFIC CONTROL PLAN  
FRONT AVENUE AND MARTIN STREET  
CITY OF ANOKA, MINNESOTA

15  
OF  
33  
SHEETS

A scale bar with four tick marks. The first and third tick marks are labeled '100' above the bar. The second tick mark is labeled '0' above the bar. The fourth tick mark is labeled '200' above the bar. Below the bar, the word 'SCALE' is on the left, 'IN' is in the middle, and 'FEET' is on the right.

## LEGEND

AN393



Mar 04, 2022 - 3:53pm  
C:\MUNICIPAL\AN393\ENGINEERING\AN393\_CONSTRUCTION\_HWY47.dwg

SEE SHEET 28 FOR STORM SEWER DETAILS

SEE SHEET 18

SEE SHEET 16

SEE NOTE ③

RUM RIVER DRIVE

40+00

39+00

17-13

17-15

17-16

36+00

37+00

6" GATE VALVE ①②

8" GATE VALVE ①②

3523

3519

3440

3441

3447

3448

3449

3450

3455

3515

211

201

3433

3533

RG-4

12+00 B-10 13+00

MCCANN AVENUE

14+00

14+28

6" GATE VALVE ①②

SEE SHEET 27 FOR INTERSECTION DETAILS

3420

3430

3432

3423

3424

3417

3418

210

211

3413

3403

17-12

17-10

17-11

25+00

26+00

27+00

28+00

29+00

23+00

24+00

21+00

20+00

22+00

23+00

24+00

RUM RIVER DRIVE

RUM RIVER

BAILEY LANE

5+00

6+00

7+00

8+00

9+00

10+00

11+00

12+00

13+00

14+00

15+00

16+00

17+00

18+00

19+00

20+00

21+00

22+00

23+00

24+00

25+00

26+00

27+00

28+00

29+00

30+00

31+00

32+00

33+00

34+00

35+00

36+00

37+00

38+00

39+00

40+00

17-3

17-4

17-5

17-6

17-7

17-8

17-9

17-10

17-11

17-12

17-13

17-14

17-15

17-16

17-17

17-18

17-19

17-20

17-21

17-22

17-23

17-24

17-25

17-26

17-27

17-28

17-29

17-30

17-31

17-32

17-33

17-34

17-35

17-36

17-37

17-38

17-39

17-40

17-41

17-42

17-43

17-44

17-45

17-46

17-47

17-48

17-49

17-50

17-51

17-52

17-53

17-54

17-55

17-56

17-57

17-58

17-59

17-60

17-61

17-62

17-63

17-64

17-65

17-66

17-67

17-68

17-69

17-70

17-71

17-72

17-73

17-74

17-75

17-76

17-77

17-78

17-79

17-80

17-81

17-82

17-83

17-84

17-85

17-86

17-87

17-88

17-89

17-90

17-91

17-92

17-93

17-94

17-95

17-96

17-97

17-98

17-99

17-100

17-101

17-102

17-103

17-104

17-105

17-106

17-107

17-108

17-109

17-110

17-111

17-112

17-113

17-114

17-115

17-116

17-117

17-118

17-119

17-120

17-121

17-122

17-123

17-124

17-125

17-126

17-127

17-128

17-129

17-130

17-131

17-132

17-133

17-134

17-135

17-136

17-137

17-138

17-139

17-140

17-141

17-142

17-143

17-144

17-145

17-146

17-147

17-148

17-149

17-150

17-151

17-152

17-153

17-154

17-155

17-156

17-157

17-158

17-159

17-160

17-161

17-162

17-163

17-164

17-165

17-166

17-167

17-168

17-169

17-170

17-171

17-172

17-173

17-174

17-175

17-176

17-177

17-178

17-179

17-180

17-181

17-182

17-183

17-184

17-185

17-186

17-187

17-188

17-189

17-190

17-191

17-192

17-193

17-194

17-195

17-196

17-197

17-198

17-199

17-200

17-201

17-202

17-203

17-204

17-205

17-206

17-207

17-208

17-209

17-210

17-211

17-212

17-213

17-214

17-215

17-216

17-217

17-218

17-219

17-220

17-221

17-222

17-223

17-224

17-225

17-226

17-227

17-228

17-229

17-230

17-231

17-232

17-233

17-234

17-235

17-236

17-237

17-238

17-239

17-240

17-241

17-242

17-243

17-244

17-245

17-246

17-247

17-248

17-249

17-250

17-251

17-252

17-253

17-254

17-255

17-256

17-257

17-258

17-259

17-260

17-261

17-262

17-263

17-264

17-265

17-266

17-267

17-268

17-269

17-270

17-271

17-272

17-273

17-274

17-275

17-276

17-277

17-278

17-279

17-280

17-281

17-282

17-283

17-284

17-285

17-286

17-287

17-288

17-289

17-290

17-291

17-292

17-293

17-294

17-295

17-296

17-297

17-298

17-299

17-300

17-301

17-302

17-303

17-304

17-305

17-306

17-307

17-308

17-309

17-310

17-311

17-312

17-313

17-314

17-315

17-316

17-317

17-318

17-319

17-320

17-321

17-322

17-323

17-324

17-325

17-326

17-327

17-328

17-329

17-330

17-331

17-332

17-333

17-334

17-335

17-336

17-337

17-338

17-339

17-340

17-341

17-342

17-343

17-344

17-345

17-346

17-347

17-348

17-349

17-350

17-351

17-352

17-353

17-354

17-355

17-356

17-357

17-358

17-359

17-360

17-361

17-362

17-363

17-364

17-365

17-366

17-367

17-368

17-369

17-370

17-371

17-372

17-373

17-374

17-375

17-376

17-377

17-378

17-379

17-380

17-381

17-382

17-383

17-384

17-385

17-386

17-387

17-388

17-389

17-390

17-391

17-392

17-393

17-394

17-395

17-396

17-397

17-398

17-399

17-400

17-401

17-402

17-403

17-404

17-405

17-406

17-407

17-408

17-409

17-410

17-411

17-412

17-413

17-414

17-415

17-416

17-417

17-418

17-419

17-420

17-421

17-422

17-423

17-424

17-425

17-426

17-427

17-428

17-429

17-430

17-431

17-432

17-433

17-434

17-435

17-436

17-437

17-438

17-439

17-440

17-441

17-442

17-443

17-444

17-445

17-446

17-447

17-448

17-449

17-450

17-451

17-452

17-453

17-454

17-455

17-456

17-457

17-458

17-459

17-460

17-461

17-462

17-463

17-464

17-465

17-466

17-467

17-468

17-469

17-470

17-471

17-472

17-473

17-474

17-475

17-476

17-477

17-478

17-479

17-480

17-481

17-482

17-483

17-484

17-485

17-486

17-487

17-488

17-489

17-490

17-491

17-492

17-493

17-494

17-495

17-496

17-497

17-498

17-499

17-500

17-501

17-502

17-503

17-504

17-505

17-506

17-507

17-508

17-509

17-510

17-511

17-512

17-513

17-514

17-515

17-516

17-517

17-518

17-519

17-520

17-521

17-522

17-523

17-524

17-525

17-526

17-527

17-528

17-529

17-530

17-531

17-532

17-533

17-534

17-535

17-536

17-537

17-538

17-539

17-540

17-541

17-542

17-543

17-544

17-545

17-546

17-547

17-548

17-549

17-550

17-551

17-552

17-553

17-554

17-555

17-556

17-557

17-558

17-559

17-560

17-561

17-562

17-563

17-564

17-565

17-566

17-567

17-568

17-569

17-570

17-571

17-572

17-573

17-574

17-575

17-576

17-577

17-578

17-579

17-580

17-581

17-582

17-583

17-584

17-585

17-586

17-587

17-588

17-589

17-590

17-591

17-592

17-593

17-594

17-595

17-596

17-597

17-598

17-599

17-600

17-601

17-602

17-603

17-604

17-605

17-606

17-607

17-608

17-609

17-610

17-611

17-612

17-613

17-614

17-615

17-616

17-617

17-618

17-619

17-620

17-621

17-622

17-623

17-624

17-625

17-626

17-627

17-628

17-629

17-630

17-631

17-632

17-633

17-634

17-635

17-636

17-637

17-638

17-639

17-640

17-641

17-642

17-643

17-644

17-645

17-646

17-647

17-648

17-649

17-650

17-651

17-652

17-653

17-654

17-655

17-656

17-657

17-658

17-659

17-660

17-661

17-662

17-663

17-664

17-665

17-666

17-667

17-668

17-669

17-670

17-671

17-672

17-673

17-674

17-675

17-676

17-677

17-678

17-679

17-680

17-681

17-682

17-683

17-684

17-685

17-686

17-687

17-688

17-689

17-690

17-691

17-692

17-693

17-694

17-695

17-696

17-697

17-698

17-699

17-700

17-701

17-702

17-703

17-704

17-705

17-706

17-707

17-708

17-709

17-710

17-711

17-712

17-713

17-714

17-715

17-716

17-717

17-718

17-719

17-720

17-721

17-722

17-723

17-724

17-725

17-726

17-727

17-728

17-729

17-730

17-731

17-732

17-733

17-734

17-735

17-736

17-737

17-738

17-739

17-740

17-741

17-742

17-743

17-744

17-745

17-746

17-747

17-748

17-749

17-750

17-751

17-752

17-753

17-754

17-755

17-756

17-757

17-758

17-759

17-760

17-761

17-762

17-763

17-764

17-765

17-766

17-767

17-768

17-769

17-770

17-771

17-772

17-773

17-774

17-775

17-776

17-777

17-778

17-779

17-780

17-781

17-782

17-783

17-784

17-785

17-786

17-787

17-788

17-789

17-790

17-791

17-792

17-793

17-794

17-795

17-796

17-797

17-798

17-799

17-800

17-801

17-802

17-803

17-804

17-805

17-806

17-807

17-808

17-809

17-810

17-811

17-812

17-813

17-814

17-815

17-816

17-817

17-818

17-819

17-820

17-821

17-822

17-823

17-824

17-825

17-826

17-827

17-828

17-829

17-830

17-831

17-832

17-833

17-834

17-835

17-836

17-837

17-838

17-839

17-840

17-841

17-842

17-843

17-844

17-845

17-846

17-847

17-848

17-849

17-850

17-851

<

GENERAL NOTES:

1. EXISTING WATERMAIN MATERIAL IS DUCTILE IRON.

REFERENCE NOTES:

- ① REMOVE VALVE AND VALVE BOX. THIS WORK SHALL BE INCIDENTAL.
- ② CONTRACTOR SHALL FURNISH AND INSTALL A NEW VALVE AND VALVE BOX PER (2)  $\frac{8}{8}$ . THIS WORK SHALL BE PAID PER ITEM 2504-\_\_" GATE VALVE AND BOX. CONNECTING TO THE WATERMAIN ADJACENT TO THE VALVE SHALL BE PAID PER ITEM 2504-CONNECT TO EXISTING WATERMAIN. EACH VALVE WILL ONLY INCLUDE PAYMENT FOR ONE "CONNECT TO EXISTING WATERMAIN". DUCTILE IRON PIPE AND FITTINGS NEEDED TO MAKE THE CONNECTION SHALL BE INCIDENTAL.
- ③ SAWING AND MILLING BITUMINOUS PAVEMENT SHALL BE PER (3)  $\frac{8}{8}$ .
- ④ SEE SHEETS RG-1 THROUGH RG-7 FOR TYPICAL RAIN GARDEN CONSTRUCTION.

LEGEND

	BITUMINOUS PAVEMENT RECLAMATION AREA
	STRUCTURE NUMBER. SEE SHEET 7 FOR RECONSTRUCTION REQUIREMENTS.
	PROPOSED LANDING AREA-MAXIMUM SLOPE OF 2% IN ALL DIRECTIONS
	PROPOSED RAIN GARDEN LOCATION ④

RG-X

REMOVALS PLAN

CONSTRUCTION PLAN

PEDESTRIAN RAMP CONSTRUCTION DETAILS



**Hakanson Anderson**  
Civil Engineers and Land Surveyors  
3601 Thurston Ave., Anoka, Minnesota 55303  
763-427-5860 FAX 763-427-0520  
[www.hakanson-anderson.com](http://www.hakanson-anderson.com)

## 2022 STREET SURFACE IMPROVEMENT PROJECT

**CONSTRUCTION PLAN**

**HIGHWAY 47 PROJECT AREA**


**CITY OF ANOKA, MINNESOTA**

SHEET  
17  
OF  
33  
SHEETS

GENERAL NOTES:  
1. EXISTING WATERMAIN MATERIAL IS DUCTILE IRON.  
REFERENCE NOTES:  
① SPECIAL SECTION FROM STA 37+62 TO STA 48+50  
ON RUM RIVER DRIVE. SEE SHEET 28 FOR  
ADDITIONAL DETAILS.


### LEGEND

BITUMINOUS PAVEMENT RECLAMATION AREA  
X-X STRUCTURE NUMBER. SEE SHEET 7 FOR RECONSTRUCTION REQUIREMENTS.



Mar 04, 2022 - 8:44am  
k:\MUNICIPAL\AN393\ENGINEERING\AN393\_CONSTRUCTION\_HWY47.dwg

DATE	REVISION	<p>I hereby certify that this plan, specification, or report          prepared by me or under my direct supervision and I          am a duly Licensed Professional Engineer under the laws          of the State of Minnesota.</p> <p><i>[Handwritten signature]</i></p> <p>CRAIG J. JOCHUM, P.E.          Date 3/3/22      Lic. No. 2345</p>	
------	----------	---	--



**Hakanson Anderson**  
Civil Engineers and Land Surveyors  
3601 Thurston Ave., Anoka, Minnesota 55301  
763-427-5860 FAX 763-427-0520  
[www.hakanson-anderson.com](http://www.hakanson-anderson.com)

## 2022 STREET SURFACE IMPROVEMENT PROJECT

**CONSTRUCTION PLAN**  
**HIGHWAY 47 PROJECT AREA**  
**CITY OF ANOKA, MINNESOTA**

SHEET  
18  
OF  
33  
SHEETS

AN393




DATE	REVISION
I hereby certify that this plan, specification, or report was prepared by me or under my direct supervision and that I am a duly Licensed Professional Engineer under the laws of the State of Minnesota.	
CRAIG J. JOCHUM, P.E. Date 3/3/22	
Lic. No. 23461	
DESIGNED BY: TAE	
DRAWN BY: TAE	
CHECKED BY: CJJ	

**Hakanson Anderson**  
Civil Engineers and Land Surveyors  
3601 Thurston Ave., Anoka, Minnesota 55303  
763-427-5860 FAX 763-427-0520  
www.hakanson-anderson.com

2022 STREET SURFACE  
IMPROVEMENT PROJECT


CONSTRUCTION PLAN  
HIGHWAY 47 PROJECT AREA  
CITY OF ANOKA, MINNESOTA

SCALE  
50 0 50 100  
IN FEET  
SHEET  
19  
OF  
33  
SHEETS



REFERENCE NOTES:  
① SAWING AND MILLING BITUMINOUS PAVEMENT  
SHALL BE PER <sup>3</sup><sub>8</sub>.





#### GENERAL NOTE

GENERAL NOTES.  
1. ALL STRIPING MATERIAL SHALL BE MULTI-COMPONENT  
LIQUID PER MN/DOT SPECIFICATION 3590.

## REFERENCE NOTES


① HANDICAP SYMBOL SHALL BE PAID PER ITEM

② 2582-PAVEMENT MESSAGE-MULTI COMPONENT.  
② PEDESTRIAN RAMP SHALL MEET CURRENT ADA STANDARDS

10

A horizontal scale bar with four tick marks. The first and third tick marks are labeled '20' and the second and fourth are labeled '0'. To the right of the fourth tick mark is the label '40'. Below the scale bar, the word 'SCALE' is written above 'FEET' and 'IN' is written between the '0' and '40' labels.

DATE	REVISION	I hereby certify that this plan, specification, or report prepared by me or under my direct supervision and I am a duly Licensed Professional Engineer under the laws of the State of Minnesota.	
12-15-2023	3/3/22	 <b>CRAIG J. JOCHUM, P.E.</b>	



**Hakanson Anderson**  
Civil Engineers and Land Surveyors  
3601 Thurston Ave., Anoka, Minnesota 55371  
763-427-5860 FAX 763-427-0520  
[www.hakanson-anderson.com](http://www.hakanson-anderson.com)




## 2022 STREET SURFACE IMPROVEMENT PROJECT

# CONSTRUCTION PLAN

## GEORGE ENLOE PARK

### CITY OF ANOKA, MINNESOTA

SHEET  
22  
OF  
33  
SHEETS



**GENERAL NOTES:**

1. ALL STRIPING MATERIAL SHALL BE MULTI-COMPONENT LIQUID, COLOR WHITE, PER MN/DOT SPECIFICATION 3590.
2. EXCEPT FOR THE INFILTRATION BASIN, ALL DISTURBED PERVIOUS AREAS SHALL BE RESTORED WITH 4" LOAM TOPSOIL, TYPE 1 FERTILIZER, SEED MIX 25-131 AND HYDRAULIC MULCH MATRIX. THESE ITEMS SHALL BE PAID PER THE INDIVIDUAL PAY ITEMS ON THE BID FORM. SEE ⑥ FOR INFILTRATION BASIN RESTORATION REQUIREMENTS.

3. PEDESTRIAN RAMPS SHALL BE 6" CONCRETE WALK.

4. PROVIDE STORM DRAIN INLET PROTECTION ON THE NORTH CATCH BASIN, APPROXIMATELY 100 FEET EAST OF THE SITE.

**REFERENCE NOTES:**

① HANDICAP SYMBOL SHALL BE PAID PER ITEM 2582-PAVEMENT MESSAGE MULTI-COMPONENT.

② SAWING AND MILLING BITUMINOUS PAVEMENT SHALL BE PER ③ (8).

③ TIE ALL PIPE JOINTS. THIS WORK SHALL BE INCIDENTAL.

④ THIS WORK SHALL BE INCIDENTAL.

⑤ CONSTRUCT MANHOLE PER ① (6).

⑥ GEOTEXTILE FILTER SHALL BE INCIDENTAL.

⑦ CONSTRUCT INFILTRATION BASIN PER ⑥ (5).

DATE	REVISION
I hereby certify that this plan, specification, or report was prepared by me or under my direct supervision and that I am a duly Licensed Professional Engineer under the laws of the State of Minnesota.	
CRAIG J. JOCHUM, P.E. Date 3/3/22	
Lic. No. 23461	
DESIGNED BY: TAE	DRAWN BY: TAE
DRAINED BY: TAE	CHECKED BY: CJJ




**Hakanson Anderson**  
Civil Engineers and Land Surveyors  
3601 Thurston Ave., Anoka, Minnesota 55303  
763-427-5860 FAX 763-427-0520  
www.hakanson-anderson.com

**2022 STREET SURFACE IMPROVEMENT PROJECT**


**CONSTRUCTION PLAN**  
RUDY JOHNSON PARK  
CITY OF ANOKA, MINNESOTA

**SHEET 23 OF 33 SHEETS**  
AN393



Mar 04, 2022 - 8:51 am : MUNICIPAL\AN393\ENGINEERING\AN393\_REMOVEALS\_FRONT.dwg

DATE	REVISION	I hereby certify that this plan, specification, or report prepared by me or under my direct supervision and I am a duly Licensed Professional Engineer under the laws of the State of Minnesota.  CRAIG J. JOCHUM, P.E. Date 3/3/22      Lic. No. 2345
------	----------	--




**Hakanson Anderson**  
Civil Engineers and Land Surveyors  
3601 Thurston Ave., Anoka, Minnesota 55371  
763-427-5860 FAX 763-427-0520  
[www.hakanson-anderson.com](http://www.hakanson-anderson.com)

## 2022 STREET SURFACE IMPROVEMENT PROJECT


EXISTING TOPOGRAPHY AND REMOVALS PL


SHEET  
24  
OF  
33  
SHEETS

A scale bar with four numerical markers: 30, 0, 30, and 60. Below the bar, the word 'SCALE' is on the left, 'IN' is in the middle, and 'FEET' is on the right.



LEGEND  
 PROPOSED BITUMINOUS PAVEMENT





DATE	REVISION	I hereby certify that this plan, specification, or report was prepared by me or under my direct supervision and that I am a duly Licensed Professional Engineer under the laws of the State of Minnesota.		
		TAE		
		DRAWN BY: TAE		
		CHECKED BY: CJJ		

CRAIG J. JOCHUM, P.E.  
Date 3/3/22  
Lic. No. 23461







**Hakanson Anderson**  
Civil Engineers and Land Surveyors  
3601 Thurston Ave., Anoka, Minnesota 55303  
763-427-5860 FAX 763-427-0520  
[www.hakanson-anderson.com](http://www.hakanson-anderson.com)




2022 STREET SURFACE  
IMPROVEMENT PROJECT

STREET AND INTERSECTION DETAILS  
HIGHWAY 47 PROJECT AREA  
CITY OF ANOKA, MINNESOTA

SHEET  
26  
OF  
33  
SHEETS  
AN393




DATE	REVISION	I hereby certify that this plan, specification, or report was prepared by me or under my direct supervision and that I am a duly Licensed Professional Engineer under the laws of the State of Minnesota.			DESIGNED BY:	Hakanson Anderson		2022 STREET SURFACE IMPROVEMENT PROJECT		STREET AND INTERSECTION DETAILS		SHEET
Mar 04, 2022	8:56am	K:\\MUNICIPAL\\AN393\\ENGINEERING\\AN393-INTERSECTION.dwg			TAE	Civil Engineers and Land Surveyors		3601 Thurston Ave., Anoka, Minnesota 55303		HIGHWAY 47 PROJECT AREA		27
		CRAIG J. JOCHUM, P.E. Date 3/3/22			DRAWN BY: TAE	763-427-5860 FAX 763-427-0520		CITY OF ANOKA, MINNESOTA		SHEET OF 33 SHEETS		AN393
		Lic. No. 23461			checked by: CJJ	www.hakanson-anderson.com						



Mar 04, 2022 - 9:03am  
K:\MUNICIPAL\AN393\ENGINEERING\AN393\_INTERSECTION.dwg

DATE	REVISION	I hereby certify that this plan, specification, or report prepared by me or under my direct supervision and am a duly Licensed Professional Engineer under the of the State of Minnesota.  _____ CRAIG J. JOCHUM, P.E. Date 3/3/22 Lic. No. 23
------	----------	--



**Hakanson Anderson**  
Civil Engineers and Land Surveyors  
3601 Thurston Ave., Anoka, Minnesota 55371  
763-427-5860 FAX 763-427-0520  
[www.hakanson-anderson.com](http://www.hakanson-anderson.com)


## 2022 STREET SURFACE IMPROVEMENT PROJECT

**STREET AND INTERSECTION DETAILS**



**HIGHWAY 47 PROJECT AREA**




**CITY OF ANOKA, MINNESOTA**


SHEET  
28  
OF  
33  
SHEETS



REFERENCE NOTES:  
 ① STRUCTURE SHALL BE CONSTRUCTED PER 3 <sub>6</sub>. REMOVE CURB AS NECESSARY TO COMPLETE CONSTRUCTION.  
 ② CONTRACTOR SHALL REMOVE STORM SEWER AS NECESSARY TO COMPLETE CONNECTION. STORM SEWER REQUIRED TO COMPLETE THE CONNECTION SHALL BE PAID PER ITEM 2503-12" RC PIPE SEWER DESIGN 3006 CLASS V. STORM SEWER REMOVAL SHALL BE INCIDENTAL.  
 ③ CASTING SHALL HAVE A 4" FRAME.








RUM RIVER DRIVE AND COOLIDGE STREET

15 0 15 30  
SCALE IN FEET




REFERENCE NOTES:

- ① CONCRETE VALLEY GUTTERS SHALL BE CONSTRUCTED IN TWO PHASES TO ALLOW FOR TRAFFIC TO PASS. CONTRACTOR SHALL PROTECT THE CONCRETE WITH BARRICADES AND FLASHERS AS NECESSARY FOR A MINIMUM OF 7 DAYS PRIOR TO ALLOWING TRAFFIC ON THE NEW CONCRETE.
- ② TAPER BITUMINOUS IN THE SHADED AREA TO MATCH INTO THE CONCRETE VALLEY GUTTER.
- ③ SAWCUTTING CURB AND GUTTER SHALL BE PAID PER ITEM 2104-SAWING CONCRETE PAVEMENT-FULL DEPTH.




RUM RIVER DRIVE AND COOLIDGE STREET



2022 STREET SURFACE  
IMPROVEMENT PROJECT


STREET AND INTERSECTION DETAILS  
HIGHWAY 47 PROJECT AREA  
CITY OF ANOKA, MINNESOTA

DATE	REVISION	I hereby certify that this plan, specification, or report was prepared by me or under my direct supervision and that I am a duly Licensed Professional Engineer under the laws of the State of Minnesota.		
Mar 04, 2022		CRAIG J. JOCHUM, P.E.	DESIGNED BY: TAE	
Date 3/3/22		Lic. No. 23461	DRAWN BY: TAE	






Hakanson Anderson  
Civil Engineers and Land Surveyors  
3601 Thurston Ave., Anoka, Minnesota 55303  
763-427-5860 FAX 763-427-0520  
www.hakanson-anderson.com

32  
33  
SHEETS  
OF  
AN393



REFERENCE NOTES:  
 ① SAWCUTTING CURB AND GUTTER SHALL BE PAID PER ITEM  
 2104-SAWING CONCRETE PAVEMENT-FULL DEPTH.



**Hakanson Anderson**  
 Civil Engineers and Land Surveyors  
 3601 Thurston Ave., Anoka, Minnesota 55303  
 763-427-5860 FAX 763-427-0520  
[www.hakanson-anderson.com](http://www.hakanson-anderson.com)

2022 STREET SURFACE  
 IMPROVEMENT PROJECT

STREET AND INTERSECTION DETAILS  
 RANDAL DRIVE  
 CITY OF ANOKA, MINNESOTA

DATE	REVISION	I hereby certify that this plan, specification, or report was prepared by me or under my direct supervision and that I am a duly Licensed Professional Engineer under the laws of the State of Minnesota.			
		DESIGNED BY:	TAE		
		DRAWN BY:	TAE		
		CHECKED BY:	CJJ		


CRAIG J. JOCHUM, P.E.  
 Date 3/3/22  
 Lic. No. 23461



33  
SHEET  
33  
OF  
33  
SHEETS  
AN393


# CSAH 30 (PLEASANT AVE.) - EXISTING

STA. 11+59.01 - 12+25.40




# CSAH 30 (PLEASANT AVE.) - EXISTING

STA. 12+25.40 - 14+44.78




# CSAH 30 (PLEASANT AVE.) - PROPOSED

STA. 11+59.01 - 12+24.78



2" MILL JOINT  
SAWCUT LOCATION


## DESIGN "A" RIGHT TURN LANE



2.0" BITUMINOUS WEAR(SPWEB440E)  
2.0" BITUMINOUS WEAR(SPWEB440E)  
6" AGGREGATE BASE, CLASS 5

# CSAH 30 (PLEASANT AVE.) - PROPOSED

STA. 12+24.78 - 14+44.78



2.0" BITUMINOUS WEAR(SPWEB440E)  
2.0" BITUMINOUS WEAR(SPWEB440E)  
6" AGGREGATE BASE, CLASS 5  
6" SELECT GRANULAR EMBANKMENT

### NOTES

① PROVIDE MINIMAL CROSS SLOPE


② HEIGHT OF CURB TO MATCH EXISTING SIDEWALK ELEVATION.  
CURB SHALL BE PAID AS B618 CURB & GUTTER.

### TYPICAL SECTIONS


Sheet C1 of C3 Sheets


I HEREBY CERTIFY THAT THIS PLAN WAS PREPARED BY ME  
OR UNDER MY DIRECT SUPERVISION AND THAT I AM A DULY  
LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF  
THE STATE OF MINNESOTA.  
PRINT NAME: NICHOLAS DUDDA  
SIGNATURE: Nicholas Dudda  
DATE: 3/8/22 LICENSE NO. 49046











DRAWN BY MP DATE 02/16/22  
DESIGN BY MP DATE 02/16/22  
CHECKED BY JF DATE 02/16/22



ANOKA COUNTY  
HIGHWAY DEPT.
















**Hakanson Anderson**  
Civil Engineers and Land Surveyors  
3601 Thurston Ave., Anoka, Minnesota 55303  
763-427-5860 FAX 763-427-0520  
[www.hakanson-anderson.com](http://www.hakanson-anderson.com)

## 2022 STREET SURFACE IMPROVEMENT PROJECT

**CROSS SECTIONS**

**FRONT AVENUE AND MARTIN STREET**  
**CITY OF ANOKA, MINNESOTA**

SHEET  
X1  
OF  
X2  
SHEETS



**Hakanson Anderson**  
Civil Engineers and Land Surveyors  
3601 Thurston Ave., Anoka, Minnesota 55303  
763-427-5860 FAX 763-427-0520  
[www.hakanson-anderson.com](http://www.hakanson-anderson.com)

## 2022 STREET SURFACE IMPROVEMENT PROJECT

## CROSS SECTIONS

SHEET  
X2  
OF  
X2  
SHEETS

# CITY OF ANOKA RAIN GARDEN PROJECTS

## 4 BIOINFILTRATION BASINS

### ANOKA, MN



1318 MCKAY DR. NE, SUITE 300  
HAM LAKE, MN 55304  
763-434-2030  
[www.AnokaSWCD.org](http://www.AnokaSWCD.org)

PROJECT: TYPICAL RAIN GARDEN  
LOCATION:  
PROPERTY ADDRESS  
ANOKA, MN 55303

CLIENT: LANDOWNER

DESIGNER: MITCH HAUSTEIN  
DATE: 03/03/2022

REVISION:

REVISION:

REVISION:

REVISION:

REVISION:

REVISION:

CHECKED BY:


NOTES:

1. Contact Gopher One at least 48 hours prior to digging at 651-454-0002 to have utilities marked.
2. Follow design details. If there are issues or questions, contact the Anoka Conservation District (763-434-2030) prior to making any changes.

SCALE: VARIABLE

TYPICAL RAIN GARDEN  
PROJECT LOCATIONS

SHEET RG1/RG7




PROJECT LOCATIONS

#### PROJECT SUMMARY

Curb-cut bioinfiltration basins (4) will improve water quality in the Rum River.


SHEET INDEX	
SHEET NUMBER	SHEET TITLE
RG1	PROJECT LOCATIONS MAP
RG2	INLET DETAIL
RG3	RAIN GUARDIAN BUNKER PRETREATMENT CHAMBER DETAIL
RG4	EXISTING/PROPOSED CONDITIONS
RG5	FRENCH DRAIN INSTALLATION DETAIL
RG6	PLANTING PLAN
RG7	ESTIMATED SCHEDULES AND QUANTITIES

## ELEVATION VIEW



**SEE RAIN GUARDIAN BUNKER  
PRETREATMENT CHAMBER  
DETAIL SHEET FOR INSTALLATION  
DETAILS**

## PLAN VIEW



**SEE RAIN GUARDIAN BUNKER  
PRETREATMENT CHAMBER  
DETAIL SHEET FOR INSTALLATION  
DETAILS**

**ANOKA  
CONSERVATION  
DISTRICT**  
1318 MCKAY DR. NE, SUITE 300  
HAM LAKE, MN 55304  
763-434-2030  
www.AnokaSWCD.org

PROJECT: TYPICAL RAIN GARDEN  
LOCATION:  
PROPERTY ADDRESS  
ANOKA, MN 55303

CLIENT: LANDOWNER

DESIGNER: MITCH HAUSTEIN  
DATE: 03/03/2022  
REVISION:  
REVISION:  
REVISION:  
REVISION:  
REVISION:  
REVISION:  
CHECKED BY:

NOTES:  
1. Contact Gopher One at least 48 hours prior to digging at 651-454-0002 to have utilities marked.  
2. Follow design details. If there are issues or questions, contact the Anoka Conservation District (763-434-2030) prior to making any changes.

SCALE: VARIABLE

TYPICAL RAIN GARDEN  
INLET DETAIL

SHEET RG2/RG7

PROJECT: TYPICAL RAIN GARDEN  
LOCATION:  
PROPERTY ADDRESS  
ANOKA, MN 55303


CLIENT: LANDOWNER

DESIGNER: MITCH HAUSTEIN  
DATE: 03/03/2022  
REVISION:  
REVISION:  
REVISION:  
REVISION:  
REVISION:  
REVISION:  
CHECKED BY:

NOTES:  
1. Contact Gopher One at least 48 hours prior to digging at 651-454-0002 to have utilities marked.  
2. Follow design details. If there are issues or questions, contact the Anoka Conservation District (763-434-2030) prior to making any changes.

SCALE: VARIABLE


TYPICAL RAIN GARDEN  
RAIN GUARDIAN  
BUNKER  
PRETREATMENT  
CHAMBER  
BIORETENTION PONDING DEPTH: 1'



#### PLAN VIEW NOTES

1. INLET WIDTH AND DISTANCE BETWEEN BACK OF CURB AND RAIN GUARDIAN BUNKER MAY VARY WITH SITE CONDITIONS. INSTALLATION FLUSH WITH THE BACK OF THE CURB CAN ALSO BE COMPLETED WITH THE RAIN GUARDIAN BUNKER.
2. CONCRETE PAD EXTENDS BEYOND THE FILTER WALL OF THE RAIN GUARDIAN BUNKER TO SERVE AS A SPLASH DISSIPATOR.

#### INSTALLED VIEWS



#### CROSS-SECTION VIEW NOTES

1. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.
2. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

9. WRAP CABLE THROUGH TOP METAL GRATE AND SECURE WITH PROVIDED CLAMP. ENSURE SUFFICIENT SLACK EXISTS IN CABLE TO ALLOW FOR GRATE REMOVAL AND PLACEMENT IN CONCRETE INLET DURING CLEANING. REMOVABLE FILTER WALL SHOULD BE INSTALLED WITH FILTER FABRIC FACING THE RAIN GUARDIAN BUNKER INLET.

10. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

11. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

12. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

13. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

14. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

15. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

16. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

17. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

18. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

19. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

20. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

21. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

22. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

23. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

24. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

25. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

26. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

27. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

28. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

29. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

30. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

31. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

32. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

33. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

34. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

35. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

36. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

37. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

38. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

39. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

40. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

41. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

42. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

43. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

44. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

45. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

46. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

47. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

48. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

49. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

50. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

51. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

52. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

53. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

54. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

55. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

56. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

57. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

58. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

59. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

60. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

61. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

62. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

63. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

64. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

65. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

66. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

67. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

68. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

69. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

70. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

71. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

72. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

73. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

74. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

75. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

76. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

77. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

78. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

79. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

80. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

81. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

82. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

83. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

84. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

85. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

86. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

87. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

88. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

89. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

90. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

91. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

92. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

93. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

94. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

95. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.




96. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

97. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

98. THE TOP OF THE CLASS 5 BASE (COMPACTED TO 95% STANDARD PROCTOR) IS PRECISELY 1 1/4" BELOW THE GUTTERLINE ELEVATION.

99. THE TOP OF THE CONCRETE PAD IS PRECISELY 1' BELOW THE GUTTERLINE.

100.



## PROJECT NOTES

1. All elevations are relative to gutter at curb-cut. It is critical that the top of the concrete pretreatment chamber pad be precisely 1' below the curb gutter.
2. Limit non-tracked equipment over BMP area. Use backhoe with tooth bucket for cell excavation to avoid compacting or smearing soils. Use excavator bucket to loosely place materials. Leveling and final grading within the cell must be completed by hand. Do not use skid steer for excavation or to place or spread materials within cell. Avoid equipment traffic on driveways and walkways.
3. Level basin bottom represents finished elevation with compost. Over excavate basin by 2" to accommodate compost. Rip subsoils after excavation to maximum depth possible. Remove soils with reduced infiltration if found during ripping.
4. Amend soils with 2" of compost and incorporate to a depth of 12".
5. Side slopes should be 3H:1V up to ground level. Slope behind retaining wall not to exceed 4H:1V.
6. Cover rain garden area with no more than 2" of double shredded hardwood mulch.
7. Contractor shall repair any damage to the curb that occurs during construction. Plywood or other protection must be used under ramps, tracks, and outriggers. Contractor is not to damage existing roadway section for necessary curb work.

# TYPICAL RAIN GARDEN EXISTING/PROPOSED CONDITIONS

## SHEET RG4/RG7

PROJECT: TYPICAL RAIN GARDEN  
LOCATION:  
PROPERTY ADDRESS  
ANOKA, MN 55303

**CLIENT: LANDOWNER**

DESIGNER: MITCH HAUSTEIN  
DATE: 03/03/2022

## REVISION:

## REVISION:

## REVIEW

## REVISION:

## REVISION:

REVISION.  
CHECKED BY

SEARCHED BY

## NOTES:

## 1. Contact G

1. Contact Cogger One at least 10 hours prior to digging at 651-454-0002 to have utilities marked.
2. Follow design details. If there are issues or questions, contact the Anoka Conservation District (763-434-2030) prior to making any changes.

## SCALE· VARIABLE



1318 MCKAY DR. NE, SUITE 300  
HAM LAKE, MN 55304  
763-434-2030  
[www.AnokaSWCD.org](http://www.AnokaSWCD.org)

PROJECT: TYPICAL RAIN GARDEN  
LOCATION:  
PROPERTY ADDRESS  
ANOKA, MN 55303

**CLIENT: LANDOWNER**

DESIGNER: MITCH HAUSTEIN  
DATE: 03/03/2022  
REVISION:  
REVISION:  
REVISION:  
REVISION:  
REVISION:  
REVISION:  
CHECKED BY:

**NOTES:**

1. Contact Gopher One at least 48 hours prior to digging at 651-454-0002 to have utilities marked.
2. Follow design details. If there are issues or questions, contact the Anoka Conservation District (763-434-2030) prior to making any changes.

### SCALE: VARIAB

# TYPICAL RAIN GARDEN

## FRENCH DRAIN

### INSTALLATION DETAIL

## INSTALLATION NOTES

1. Limit non-tracked equipment over BMP area as directed by engineer. If possible, auger french drain hole from outside of BMP area.
2. Auger 36" diameter hole to 5' below basin bottom (elevation 94.00')
3. Fill with #3 washed crushed stone to 94.75'. Place 4.5' fabric wrapped, perforated HDPE. Back fill sides with washed rock.
4. Place top of manhole frame flanged base level with basin bottom
5. Cover disturbed area with 2" of double shredded hardwood mulch.

## SHEET RG5/RG7

Plant List				
	Qty	Common Name	Botanical Name	Symbol
<b>Perennials</b>				
15	Blueflag Iris	Iris versicolor		
20	Butterfly Weed	Asclepias tuberosa		
22	Fox Sedge	Carex vulpinoidea		
12	Little Bluestem	Schizachyrium scoparium		
20	Little Joe Pye Weed	Eupatorium dubium 'Little Joe'		
16	Prairie Blazing Star	Liatris pycnostachya		
12	Prairie Dropseed	Sporobolus heterolepis		
20	Swamp Milkweed	Asclepias incarnata		
<b>Shrubs</b>				
3	Bailey Compact American Cranberrybush	Viburnum trilobum 'Bailey Compact'		
2	Black Chokeberry	Aronia melanocarpa		
6	Dwarf Bush Honeysuckle	Diervilla lonicera		
4	Isanti Red-Osier Dogwood	Cornus sericea 'Isanti'		
<b>TOTAL</b>	<b>152</b>			

0 5 10 15 20 FT

**ANOKA**  
**CONSERVATION**  
**DISTRICT**  
1318 MCKAY DR. NE, SUITE 300  
HAM LAKE, MN 55304  
763-434-2030  
www.AnokaSWCD.org

PROJECT: TYPICAL RAIN GARDEN  
LOCATION:  
PROPERTY ADDRESS  
ANOKA, MN 55303

CLIENT: LANDOWNER

DESIGNER: MITCH HAUSTEIN  
DATE: 03/03/2022  
REVISION:  
REVISION:  
REVISION:  
REVISION:  
REVISION:  
REVISION:  
CHECKED BY:


NOTES:  
1. Contact Gopher One at least 48 hours prior to digging at 651-454-0002 to have utilities marked.  
2. Follow design details. If there are issues or questions, contact the Anoka Conservation District (763-434-2030) prior to making any changes.

SCALE: VARIABLE

TYPICAL RAIN GARDEN

PLANTING PLAN

SHEET RG6/RG7



PLANT SPECIES, SIZES, AND QUANTITIES (QUANTITIES SHOWN ARE FOR ONE RAIN GARDEN)

SPECIES		PLANT SIZE AND QUANTITY			
COMMON NAME	SCIENTIFIC NAME	1" PLUG	4" POT	1-GALLON POT	GRAND TOTAL
Bailey Compact American Cranberrybush	Viburnum trilobum 'Bailey Compact'			3	3
Black Chokeberry	Aronia melanocarpa			2	2
Isanti Red-Osier Dogwood	Cornus sericea 'Isanti'			4	4
Blueflag Iris	Iris versicolor		15		15
Dwarf Bush Honeysuckle	Diervilla lonicera		6		6
Butterfly Weed	Asclepias tuberosa	20			20
Fox Sedge	Carex vulpinoidea	22			22
Little Bluestem	Schizachyrium scoparium	12			12
Little Joe Pye Weed	Eupatorium dubium 'Little Joe'	20			20
Prairie Blazing Star	Liatris pycnostachya	16			16
Prairie Dropseed	Sporobolus heterolepis	12			12
Swamp Milkweed	Asclepias incarnata	20			20
	<b>GRAND TOTAL</b>	<b>122</b>	<b>21</b>	<b>9</b>	<b>152</b>



1318 MCKAY DR. NE, SUITE 300  
HAM LAKE, MN 55304  
763-434-2030  
www.AnokaSWCD.org

PROJECT: TYPICAL RAIN GARDEN

LOCATION:

PROPERTY ADDRESS  
ANOKA, MN 55303

CLIENT: LANDOWNER

DESIGNER: MITCH HAUSTEIN

DATE: 03/03/2022

REVISION:

REVISION:

REVISION:

REVISION:

REVISION:

CHECKED BY:

NOTES:

1. Contact Gopher One at least 48 hours prior to digging at 651-454-0002 to have utilities marked.
2. Follow design details. If there are issues or questions, contact the Anoka Conservation District (763-434-2030) prior to making any changes.

SCALE: VARIABLE

TYPICAL RAIN GARDEN  
ESTIMATED QUANTITIES AND SCHEDULES

SHEET RG7/RG7