DocuSign Envelo	pe ID: 154151DD-D10C-4B05-8AFB-14BB2593CDDE
	ANOKA COUNTY TRANSPORTATION DIVISION
	1440 BUNKER LAKE BLVD NW

NOT VALID UNLESS SIGNED BY ANOKA COUNTY PERMIT NUMBER

Anoka County MINNESOTA ectful. Innovative. Fiscally Responsible

RIGHT OF WAY X

COMMERCIAL ACCESS

APPLICATION FOR PERMIT FOR INSTALLATION OF UTILITIES OR PLACING OBSTRUCTIONS ON THE COUNTY HIGHWAY SYSTEM ALL APPLICANTS MUST BE REGISTERED PRIOR TO PERMIT APPROVAL

ANDOVER, MN 55304

763-324-3176

highwaypermits@anokacountymn.gov

APPLICANT NAME Utilisource LLC	CONTACT PERSON Arna Wade
ADDRESS 313 N Gladstone Ave	CITY Jonesburg
PHONE NUMBER 3143231569	EMAIL arna.wade@utilisource.us
COMPANY OR INDIVIDUAL PERFORMING WORK Gateway	Fiber
CONTACT PERSON Gateway Fiber	EMAIL kirk.thoelke@gatewayfiber.com
	PHONE NUMBER 3144956318
PERMIT WORK TO START 02/26/2024	
PERMIT WORK TO BE COMPLETED 05/27/2024	
DURATION OF JOB 90 Days	
ARE YOU BEING ASKED TO RELOCATE DUE TO A COUNTY P	ROJECT? No

ANOKA COUNTY PROJECT NUMBER

WORK SITE ADDRESS University Ave NW, and 121st Ave NW

METHOD OF INSTALLATION/CONSTRUCTION Directional Drilling

NATURE OF WORK Place fiber optic cable via directional drilling in the Anoka County ROW for Gateway Fiber on roads mentioned above. The proposed work in the ROW to be in accordance with the Anoka County Govt requirements to work in the County ROW.

SURFACE TO BE DISTURBED

SITE PLAN IF THE ROADWAY IS ENCROACHED, YOU MUST ATTACH A TRAFFIC CONTROL PLAN AND/OR REFERENCE THE MOST CURRENT VERSION OF THE MN TEMPORARY TRAFFIC CONTROL FIELD MANUAL (3+ DAYS REQUIRES PLANS TO BE SIGNED BY A LICENSED PE).

DITCH/BLVD

BITUMINOUS

CONCRETE

GRAVEL



IS SIGNING AND STRIPING REQUIRED? Yes

Layout 33 RTL is encroached, 9am-3pm Layout 8 if shoulder is encroached.

No parking or working on trail/sidewalk wotipit approval from city.

X NONE

DEPTH FROM SURFACE 60" (60" minimum under county roads)

SIZE AND KIND OF PIPE/CABLE 1.25" Duct/Fiber Optic Cable

NUMBER OF EXCAVATIONS 1

SIZE OF EXCAVATIONS 2'X4' (Length, width, and depth)

LOCATION OF EXCAVATIONS ALL EXCAVATIONS ARE TO BE PROTECTED AT ALL TIMES AND THEN BACKFILLED WHEN UNATTENDED AND/OR OVERNIGHT Specific written descriptions of excavations - if shown on attached drawing, drawing shall be specific with depth and distance from centerline, curb, or other distinguishable location. Traffic control plans cannot be approved without specific excavation descriptions.

Placing fiber optic cable via directional drill at a depth of 36" inside the UE, at a depth of 60" when crossing University Ave NW in the Anoka County ROW for Gateway Fiber on roads mentioned above. The proposed work in the ROW to be in accordance with Anoka County Govt requirements to work in the County ROW.

THIS PERMIT COVERS THE RIGHT OF WAY IN ANOKA COUNTY ONLY

ACTD reserves the right to make changes to these special conditions.

CITY Coon Rapids



ANOKA COUNTY TRANSPORTATION DIVISION 1440 BUNKER LAKE BLVD NW ANDOVER, MN 55304 PERMIT PHONE: 763-324-3176 highwaypermits@anokacountymn.gov

GENERAL INFORMATION

One permit must be approved for each county road on which work will be performed prior to any work within the right of way by any utility/contractor. Emergency conditions which threaten the safety of the public and require immediate repair are exceptions to this rule. Under those circumstances, the utility/contractor is permitted to begin and/or complete the necessary repairs. The Anoka County Transportation Division (ACTD) shall be notified of emergency repairs as soon as feasible and a written permit is to be completed within two business days of occurrence.

A license-permit bond is generally required of the contractor as part of the registration process, the amount of which will be determined by the nature of the utility work.

A sketch or drawing shall accompany each permit application which will show the location of the proposed work/utility with reference to the county highway center line and right of way line. A complete set of plans is required for all sewer/water projects.

It shall be the responsibility of the applicant to determine which of the special conditions apply to each permit.

ACTD reserves the right to revoke any utility permit and halt work, if, upon inspection of any job site, the special conditions are not met, and/or a hazard exists for the applicant or public safety is threatened. The failure to comply with the terms and conditions of any applicable Federal, State, Regional, and local laws, rules and regulations, including any provision of Anoka County's Right-of-Way Ordinance shall be cause for immediate revocation of a permit.

The applicant shall notify ACTD immediately upon completion of project so that the ACTD can inspect the site to determine if restoration has been satisfactorily completed.

The undersigned hereby accepts the terms and conditions of this permit and the regulations of Anoka County, and agrees to fully comply therewith to the satisfaction of the ACTD. The county of Anoka, its officials, employees, and agents, shall be held harmless, by the applicant/permittee, from any demands, claims, lawsuits, or damages relating to the work described in this permit.

APPLICANT'S SIGNATURE

ana Wade

2D82E227D6144E2

DATE

DATE 2/19/2024

AUTHORIZATION OF PERMIT

In consideration of the applicant's agreement to comply in all respects with the regulations of the ACTD covering such operations, permission is hereby granted for the work to be done as described in the above application. Said work to be done in accordance with the general conditions listed above and the special conditions required as hereby stated. It is expressly understood that this permit is conditioned upon replacement or restoration of the county highway and its right of way to their original or to a satisfactory condition. It is further understood that this permit is issued subject to the approval of local city or township authorities having joint supervision over said street or highway.

APPROVED BY:

TITLE: Traffic Technician

NOT VALID UNLESS SIGNED BY ANOKA COUNTY

ANOKA COUNTY TRANSPORTATION DIVISION

1440 BUNKER LAKE BLVD NW

ANDOVER, MN 55304

PERMIT PHONE: 763-324-3176

highwaypermits@anokacountymn.gov

SPECIAL CONDITIONS

TRAFFIC CONTROL

cally Respo

1) Detours

Anoka Countv

MINNESOTA

- a) Detailed detour layouts shall be submitted to the traffic engineer for approval.
- b) No detours shall be permitted without prior approval of the Anoka county traffic engineer.
- c) A ten day notice must be given prior to the installation of any detour.
- d) It shall be the responsibility of the applicant to notify Anoka county central communications, local government bodies, and any affected bus companies ten days prior to any road closures/detours.
- e) Immediately upon completion of work and/or detours, all posts, barricades, and signs shall be removed from the right of way.

2) Traffic control devices

a) All traffic control devices, barricades, flashers, etc., shall be furnished by the applicant and shall be in accordance with the most recent edition of the Minnesota manual on uniform traffic control devices and temporary traffic control zone layouts – field manual of the same manual.

CONSTRUCTION REQUIREMENTS

- 1) Open cutting of bituminous or concrete surfaced roads will be allowed only at the discretion of the county engineer.
- 2) Neither supplies nor excavation materials shall be placed on the bituminous or concrete surface at any time.
- 3) No trenches will be allowed to remain open overnight.
- 4) Materials removed from the trench shall be used as backfill insofar as they are suitable. All backfill material shall conform to MNDOT specifications for compaction. The use of heavy equipment on top of trench, slapping with backhoe bucket and/or back casting to achieve compaction is prohibited. Any additional material required to back fill to the original grade shall be furnished by the applicant at no expense to the ACTD. All the base and surface courses damaged during construction operations shall be restored to a condition equal to or better than before operations began. The applicant shall be responsible for and restore any settlement.
- 5) All culverts, ditches, shoulders, and backslopes shall be restored to their original condition unless otherwise directed by the ACTD. Shoulders which have been previously constructed or reconstructed with special materials shall be replaced in kind. Restoration of signs, guardrails, guard posts, etc., are the sole responsibility of the applicant and shall be restored to their original condition.
- 6) All roadway maintenance required within the limits of the utility project that is related to the applicant's activities shall be the sole responsibility of the applicant for one year after completion of the project. Upon completion of the restoration work, the applicant shall request a final inspection by the ACTD. The ACTD's approved completion date shall be the starting date of the applicant's one-year responsibility.

HORIZONTAL BORING AND JACKING

- 1) All hard surface roadways shall be jacked or bored.
- 2) All crossings of Anoka County maintained roadbeds, shall be made by boring inside a casing or carrier pipe, or by jacking unless otherwise directed by the Anoka County Engineer. The auger shall lead the casing or carrier pipe by at least six inches whenever possible and never lead the carrier pipe by more than one inch.
- 3) The use of pneumatic devices to facilitate the roadbed crossings will be allowed in most cases with prior approval. In the event approval is not granted and applicant uses a pneumatic device to cross a roadbed and encounters an obstruction and/or unstable subbase material which makes forward or reverse motion of pneumatic device impossible, said pneumatic device then becomes part of the roadway subbase and permission to excavate to retrieve device will not be granted.
- 4) If a pneumatic device is used for the work permitted herein, the installation must be kept to a minimum of four feet below the surface of the roadway if the pneumatic device is less than two inches in diameter, and a minimum of five feet below the surface of the roadway if the pneumatic device is two inches in diameter or larger.

BITUMINOUS RESTORATION

- 1) The locations and dimensions of all openings to be made in the bituminous surface shall be approved by the ACTD prior to any cutting or any surface opening operations.
- 2) All openings in bituminous surfaces shall be cut in a straight line with the sides smooth and vertical. No ragged edges will be permitted. Cutting shall be done with a concrete saw.
- 3) All necessary dust control operations shall be carried out by the applicant at no expense to Anoka County.
- 4) The minimum requirement for subgrade replacement shall be the upper twelve inches of material and shall meet MNDOT specifications for class five placed in six inch layers compacted to one hundred percent of optimum density.
- 5) All manhole casings, gate valves, and other utility structures shall be set one quarter inch below the top of the finished surface.
- 6) Bituminous tack coat materials and application thereof shall conform to MNDOT specification 2357.
- 7) All bituminous surfacing shall be replaced as soon as practicable after the base construction. All bituminous surfacing shall be machine laid. Any exceptions must be approved by the ACTD. Bituminous surfacing shall be replaced to original pavement depth or to a minimum of six inches of bituminous mixture (2360), whichever is greater. Bituminous mixtures must be placed in lifts not exceeding three inches in thickness for base and binder courses and not exceeding two inches for the wear course.
- 8) All surface restoration regardless of size shall conform to existing grades.
- 9) Any unnecessary or negligent damage to bituminous surface in conjunction with the installation and/or repair of a utility shall be cut out and replaced in kind as directed by the ACTD.

Anoka County

Respectful, Innovative, Fiscally Responsible

MINNESOTA

ANOKA COUNTY TRANSPORTATION DIVISION


1440 BUNKER LAKE BLVD NW

ANDOVER, MN 55304

PERMIT PHONE: 763-324-3176

highwaypermits@anokacountymn.gov

CONCRETE RESTORATION
1) Curb and gutter, sidewalks, and driveways shall be restored in accordance with MNDOT specifications 2531 and 2521
UTILITY LINES
 There shall be only a single pole line on the county right of way on either side of the center line thereof. Exact locations of longitudinal installations on county highways shall be located as directed by the ACTD.
SECTION CORNER MONUMENTS
1) Utility locations shall not interfere with the location of any section, quarter, witness, or right of way monuments. For assistance locations, contact the Anoka County Surveyor's Office.
 2) The applicant shall be responsible for replacement of any existing property irons disturbed during construction. 3) The applicant shall notify the Anoka County Surveyor's Office three working days in advance of any anticipated disturbance
any section, quarter, witness, or right of way monuments.
4) Any monument disturbed during the course of construction, shall be reset by the Anoka County Surveyor's Office at the expension of the applicant.
ATTACHING TO BRIDGES/STRUCTURES
 No utility is permitted to be hung from, or otherwise attached to, any bridge or structure without having detailed plans approve by the Anoka County Engineer. These plans are to show approaches to the structure, method of installation, type, and dimension of housing for the utility.
ADDITIONAL PROVISIONS
 All subcontractors, installers, and crew shall possess a physical or electronic copy of all documents in relation to the approved permit prior to the commencement of work and be kept on site. This includes, but it not limited to the following: a) Approved permit b) Any/all traffic control plans and/or layouts
2) Shall notify Anoka County Permits at 763-324-3176 or highwaypermits@anokacountymn.gov
a) At least 36 hours prior to the commencement of workb) With time frame of proposed of work
c) Anticipated traffic control
d) When work is complete - including restorations - to request a final inspection
3) No work during inclement weather or when plows are out in any capacity
4) All traffic control shall be in accordance with the most current version of the MnDOT Temporary Traffic Control Field Manual
5) For staking of right-of way or proposed infrastructure, contact Chris Osterhus at 763-324-3189 a minimum of 48 hours prior to the commencement of work.
INITIAL $\mu \psi$



gatewayfiber


Fiberhood: BLAN-MN-1-15









Sheet Index <dyn type="page" property="attribute" field="Project" domainlookup="true"/>




Sources: Earl, HERE, Garmin, USGS, Intermap, INCREMENT P, NRCan, Earl Japan, METI, Earl China (Hong Kong), Earl Korea, Earl (Thailand), NGCC, (c) OpenStreetMap contributors, and the GIS User Community



DocuSign Envelope ID: 154151DD-D10C-4B05-8AFB-14BB2593CDDE



```
DocuSign Envelope ID: 154151DD-D10C-4B05-8AFB-14BB2593CDDE
```



	Gateway Fiber
	Sheet: 3 of 8
	Anoka
	BLAN-MN-1-15
	As Of: 12/28/2023
	Legend
	Path Access
	Subtype, Type
	FlowerPot
	HandHole (HH)
	田 HH UHF(14x19x12)
	HH UHF(24x36x24)
	Path
	Status, Subtype
	Proposed, Reference Only Duct
	Do Not Build, BM60(1)(1.25)
	Proposed, BM60(1)(1.25)
	Proposed, BM60(2)(1.25)
	Proposed, BM60(3)(1.25)
	Anoka County, MN
	1 inch = 110 feet
IF(24x36	N 123rd Av
	ources: Esri, HERE, Garmin,
	JSGS, Intermap,
12064 3	
12054	
	Engineered by
12048	
ng), Es <mark>ri Korea</mark> ,	

4





Sources: Earl, HERE, Garmin, USGS, Intermap, INCREMENT P, NRCan, Earl Japan, METI, Earl China (Hong Kong), Earl Korea, Earl (Thailand), NGCC, (c) OpenStreetMap contributors, and the GIS User Community



Gateway Fiber

Sheet: 4 of 8

Anoka

BLAN-MN-1-15

As Of: 12/28/2023

Legend


Path Access Subtype, Type

	FlowerPot
H	HandHole (HH)
Η	HH UHF(14x19x12)
Path	


Status, Subtype

- Proposed, BM60(1)(1.25)
- Proposed, BM60(2)(1.25)
 - Anoka County, MN

1 inch = 110 feet







429 123RD AVE NW 12311 HOLLY ST NW 419 123RD AVE NW

428 123RD AVE NW416 123RD AVI




5

0


440 123 RD AVE NW

: Esri, HERE, Carmin, USGS, Intermap, INCREMENT P, NRCan, Esri Japan, METI, Esri China (H ailand), NGCC, (d) OpenStreetMap contributors, and the GIS User Community Sourc Esri (


	1
	Gateway Fiber
UHF(14x19x12	Sheet: 5 of 8
0 124TH AVE NW	Anoka
	BLAN-MN-1-15
	As Of: 12/28/2023
	Legend
61 123RD CIR NW	-
	Path Access Subtype, Type
	 FlowerPot
367 123RD CIR NW	
	HandHole (HH)
	☐ HH UHF(14x19x12) Path
	Status, Subtype
362 123RD CIR NW	Proposed, Reference Only Duct
	1 10p00000, Diff00(1)(1.20)
358 123RD CIR NW	Proposed, BM60(2)(1.25)Anoka County, MN
123RD AVE NW	
) <u>- 167 ft.</u> <u>- H-</u>	
355 • NW	1 inch = 110 feet
	Main St NW
	N 8 0
_DENROD CIR NW	St MW
ENW	
	Sources: Esri, HERE, Garmin,
	JSGS, Intermap,
_DENROD CIR NW	
	Engineered by
ng); Estikorea, NW	












CITY AREA

00

Sources: Esrl, HERE, Carmin, USCS, Interma Esrl (Thailand), NGCC, (6) OpenStreetMap col

5

INCREMENIPELNRCany 12371 HOLLY ST NW 390 124TH AVE NW INCREMENIPELNRCany Esri Japan, METL, Esri Chinas(Hong, Kong), Nesri Koreal



DocuSign

Certificate Of Completion

Envelope Id: 154151DDD10C4B058AFB14BB2593CDDE Subject: Arna Wade - ROW Permit Application Source Envelope: Document Pages: 14 Signatures: 1 Certificate Pages: 4 Initials: 1 AutoNav: Enabled EnvelopeId Stamping: Enabled Time Zone: (UTC-06:00) Central Time (US & Canada)

Record Tracking

Status: Original 2/19/2024 12:40:22 PM Security Appliance Status: Connected Storage Appliance Status: Connected

Signer Events

Arna Wade arna.wade@utilisource.us Security Level: DocuSign.email ID: 1 2/19/2024 12:40:24 PM

Electronic Record and Signature Disclosure: Accepted: 2/19/2024 11:26:47 AM

ID: f0d27715-bc3c-41a5-9aff-7b21908b132d

Susan Burgmeier Susan.Burgmeier@co.anoka.mn.us

Associate Traffic Technician

Anoka County

Signing Group: Highway Permits Security Level: Email, Account Authentication (Optional)

Electronic Record and Signature Disclosure: Accepted: 1/10/2024 8:33:18 AM

ID: 918806bc-10b8-4722-9380-473245a1689f

Holder: Highway Permits HighwayPermits@co.anoka.mn.us Pool: StateLocal Pool: Anoka County

Signature

DocuSigned by: Ama Wade 2082E227D6144F2...

Signature Adoption: Pre-selected Style Using IP Address: 96.45.17.44

Status: Sent

Envelope Originator: Highway Permits Anoka County Government Center 2100 3rd Avenue Anoka, MN 55303 HighwayPermits@co.anoka.mn.us IP Address: 96.45.17.44

Location: DocuSign

Location: DocuSign

Timestamp

Sent: 2/19/2024 12:40:23 PM Viewed: 2/19/2024 12:40:33 PM Signed: 2/19/2024 12:50:56 PM

Sent: 2/19/2024 12:51:00 PM Viewed: 2/22/2024 12:20:10 PM

Editor Delivery EventsStatusTimestampAgent Delivery EventsStatusTimestampIntermediary Delivery EventsStatusTimestampCertified Delivery EventsStatusTimestamp	gner Events S	Signature	Timestamp
Intermediary Delivery Events Status Timestamp	ery Events S	Status	Timestamp
	ery Events S	Status	Timestamp
Certified Delivery Events Status Timestamp	v Delivery Events S	Status	Timestamp
	ivery Events S	Status	Timestamp
Carbon Copy Events Status Timestamp Arna Wade	y Events S	Status	Timestamp

arna.wade@utilisource.us

Security Level: Email, Account Authentication (Optional)

Electronic Record and Signature Disclosure:

Carbon Copy Events	Status	Timestamp
Not Offered via DocuSign		
Witness Events	Signature	Timestamp
Notary Events	Signature	Timestamp
	-	
Envelope Summary Events	Status	Timestamps
Envelope Summary Events Envelope Sent	Status Hashed/Encrypted	Timestamps 2/19/2024 12:40:23 PM
		•
Envelope Sent	Hashed/Encrypted	2/19/2024 12:40:23 PM
Envelope Sent Envelope Updated	Hashed/Encrypted Security Checked	2/19/2024 12:40:23 PM 2/19/2024 12:50:56 PM

ELECTRONIC RECORD AND SIGNATURE DISCLOSURE

The following information constitutes Anoka County's (we, us or Company) written notices or disclosures relating to your use of DocuSign in relation to Anoka County's license. Described below are the terms and conditions for providing notices and disclosures electronically through the DocuSign system. Please read the information below carefully and thoroughly, and if you agree to this Electronic Record and Signature Disclosure (ERSD), please confirm your agreement by selecting the check-box next to 'I agree to use electronic records and signatures' before clicking 'CONTINUE' within the DocuSign system.

Getting paper copies

At any time, you may request from us a paper copy of any record provided or made available electronically to you by us. You will have the ability to download and print documents we send to you through the DocuSign system during and immediately after the signing session and, if you elect to create a DocuSign account, you may access the documents for a limited period of time (30 days) after the documents are first sent to you. At any time, if you request paper copies of any documents, you may be charged a fee. You may request paper copies from us by following the procedure described below.

Withdrawing your consent

If you decide to receive notices, disclosures and documents from us electronically, you may change your mind and tell us that going forward you want to receive documents only in paper format. Please note, processing time will be slowed down dramatically as we will be required to print and send the document through the mail and await your return of the documents. The process to change the method of receipt is described below.

All notices and disclosures will be sent to you electronically

Upon your acceptance to receive electronic notifications, all required notices, disclosures, authorizations, acknowledgements, and other documents that are required to be provided or made available to you during the course of our relationship with you will be provided electronically through the DocuSign system. All of the required documents will be provided to you at the address that you have given us.

How to contact Anoka County:

You may change your preferred method of contact whether electronically, or paper copies, or change your email address. You may also request paper copies of certain information from us, or withdraw your prior consent to receive documents. Please use the contact information below for your request and in the body of your correspondence, identify your desired action. If you are

changing an email address, please include your prior email address as well as your new address. If you no longer wish to receive future documents in electronic format, please include that request in the body of your email.

Email: helpdesk@co.anoka.mn.us Phone: (763)-324-4110 Address: Anoka County Government Center Attn: Information Technology, #300 2100 3rd Avenue Anoka, MN 55303

Required hardware and software

The minimum system requirements for using the DocuSign system may change over time. The current system requirements are found here: <u>https://support.docusign.com/guides/signer-guide-signing-system-requirements</u>.

ACKNOWLEDGEMENT

To confirm your access to the electronic notices and disclosures, which will be similar to other electronic notices and disclosures that we may provide to you, please acknowledge that you have read this ERSD by selecting the check-box next to 'I agree to use electronic records and signatures' before clicking 'CONTINUE' within the DocuSign system.

By selecting the check-box next to 'I agree to use electronic records and signatures', you confirm that:

- You can access and read this Electronic Record and Signature Disclosure; and
- You can print this Electronic Record and Signature Disclosure, or save or send this Electronic Record and Disclosure to a location where you can print it, for future reference and access; and
- Until or unless you notify Anoka County as described above, you consent to receive exclusively through electronic means all notices, disclosures, authorizations, acknowledgements, and other documents that are required to be provided or made available to you by Anoka County during the course of your relationship with Anoka County.