

**CSAH 11 @ Redwood St. - SIGNAL CODE 7119 - BY PHASE TIMING
PROPOSED - 02/01/2016**

BY PHASE TIMING DATA

PHASE	ø1	ø2	ø3	ø4	ø5	ø6	ø7	ø8
DIRECTION	WBLT	EBT	NBLT	SBT	EBLT	WBT	SBLT	NBT
MINIMUM GREEN	7	15		10	7	15		10
BK MIN GREEN								
CS MIN GREEN								
DELAY GREEN								
WALK		7		7		7		7
WALK 2								
PED CLEAR		22		21		18		20
PED CLEAR 2								
VEHICLE EXT	2.1	3.6		2.0	2.1	3.6		2.0
VEHICLE EXT 2								
MAX 1	25	40		20	20	40		20
MAX 2								
MAX 3								
DYM MAX								30
DYM STP								10
YELLOW	3.0	3.6		3.2	3.0	3.9		3.2
RED CLEAR	2.0	1.7		3.0	2.1	1.7		3.0
RED MAX								
RED REVERT	6.0	6.0		6.0	6.0	6.0		6.0
ACT B4								
SEC/ACT		2.0				2.0		
MAX INT		18				18		
TIME B4		14				14		
CARS WT								
STPT DUC								
TIME TO REDUCE		14				14		
MIN GAP		2.0				2.0		

Detector Extend/Delay

D1-2 delay - 2.0 sec.

D4-1 stretch - 1.0 sec.

D4-2 delay - 10.0 sec.

D4-3 delay - 2.0 sec., accounts for false calls from ø5 FYA operation

D5-2 delay - 2.0 sec.

D8-1 stretch - 1.0 sec.

D8-2 delay - 10.0 sec.

D8-4 delay - 2.0 sec., accounts for false calls from ø1 FYA operation

ø1 and ø5 left turn phases will operate in protected only mode Monday-Friday from 3 PM - 7 PM, and in FYA mode all other hours