

CSAH 116 @ Rose St- SIGNAL CODE 7142 - BY PHASE TIMING

PROPOSED - 06/12/2025

BY PHASE TIMING DATA

PHASE	ø1	ø2	ø3	ø4	ø5	ø6	ø7	ø8
DIRECTION	WBLT	EBT	NBLT	SBT	EBLT	WBT	SBLT	NBT
MINIMUM GREEN	7	15	7	10	7	15	7	10
BK MIN GREEN								
CS MIN GREEN								
DELAY GREEN								
WALK		7		7		7		7
WALK 2								
PED CLEAR		15		32		13		31
PED CLEAR 2								
VEHICLE EXT	2.1	4.6	2.1	2.1	2.1	4.6	2.1	2.1
VEHICLE EXT 2								
MAX 1	15	60	15	20	15	60	15	20
MAX 2								
MAX 3								
DYM MAX								
DYM STP								
YELLOW	3.0	4.3	3.0	3.2	3.0	4.3	3.0	3.2
RED CLEAR	2.9	1.5	2.2	2.8	2.8	1.5	2.2	2.8
RED MAX								
RED REVERT	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0
ACT B4								
SEC/ACT		1.5				1.5		
MAX INT		28				28		
TIME B4		20				20		
CARS WT								
STPT DUC								
TIME TO REDUCE		20				20		
MIN GAP		2.0				2.0		

Detector Extend/Delay

D3-2 delay - 2.0 sec.

D4-1 delay - 5.0 sec.

D4-2 delay - 5.0 sec.

D7-2 delay - 2.0 sec.

D8-1 delay - 5.0 sec.

D8-2 delay - 5.0 sec.

ø1 and ø5 left turn phases will operate in protected only mode Monday-Friday from 7 - 8 AM, 2 -6 PM, and in FYA mode all other hours

ø3 and ø7 left turn phases will operate in FYA mode for all hours daily