

**CSAH 17 @ CSAH 116 - SIGNAL CODE 7348 - BY PHASE TIMING
PROPOSED - 10/09/2019**

BY PHASE TIMING DATA

PHASE	ø1	ø2	ø3	ø4	ø5	ø6	ø7	ø8
DIRECTION		NBT		EB	NBLT	SBT		
MINIMUM GREEN		20		10	7	20		
BK MIN GREEN								
CS MIN GREEN								
DELAY GREEN								
WALK				7		7		
WALK 2								
PED CLEAR				24		22		
PED CLEAR 2								
VEHICLE EXT		6.0		1.9	2.1	5.9		
VEHICLE EXT 2								
MAX 1		40		20	20	40		
MAX 2								
MAX 3								
DYM MAX								
DYM STP								
YELLOW		5.0		5.0	3.0	5.0		
RED CLEAR		1.3		2.5	2.6	1.3		
RED MAX								
RED REVERT		6.0		6.0	6.0	6.0		
ACT B4								
SEC/ACT								
MAX INT								
TIME B4		14				14		
CARS WT								
STPT DUC								
TIME TO REDUCE		14				14		
MIN GAP		3.0				3.0		

Detector Extend/Delay

D4-1 stretch - 1.0 sec.

D4-2 & D4-3 stretch - 2.0 sec.

D4-4 delay- 10.0 sec.

D4-5 delay- 2.0 sec.

ø5 left turn phase will operate in protected only mode for all hours daily