

**CSAH 10 @ Jefferson St. - SIGNAL CODE 7506 - BY PHASE TIMING  
PROPOSED - 12/14/2017**

**BY PHASE TIMING DATA**

PHASE	ø1	ø2	ø3	ø4	ø5	ø6	ø7	ø8
DIRECTION	WBLT	EBT	NBLT	SBT	EBLT	WBT	SBLT	NBT
MINIMUM GREEN	7	15	5	10	7	15	5	10
BK MIN GREEN								
CS MIN GREEN								
DELAY GREEN								
WALK		7		7		7		
WALK 2								
PED CLEAR		29		41		25		
PED CLEAR 2								
VEHICLE EXT	2.5	5.2	2.1	2.5	2.5	5.2	2.1	2.5
VEHICLE EXT 2								
MAX 1	30	65	20	20	20	65	15	20
MAX 2								
MAX 3								
DYM MAX								
DYM STP								
YELLOW	3.0	5.0	3.0	3.3	3.0	4.9	3.0	3.4
RED CLEAR	3.5	2.0	4.3	4.2	3.5	2.1	4.3	4.1
RED MAX								
RED REVERT	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0
ACT B4								
SEC/ACT		1.5				1.5		
MAX INT		35				35		
TIME B4		22				22		
CARS WT								
STPT DUC								
TIME TO REDUCE		22				22		
MIN GAP		3.0				3.0		

**Detector Extend/Delay**

NO delay or extend on any detectors

Added Logic Statements to controller (MM1-8-2) omitting phase 8 for a portion of the phase 4 pedestrian clearance interval to reduce conflict between pedestrians and permitted phase 8 left turning vehicles