



SEC. 6, T.33, R.25
MARCH, 1963

Used Old Distance
of 77.00 chains (5140.07)

Sec. 6, T.33, R.25 (Burns)
MAR 63

(20A) Iron Bridge Spike and Nail
50,054.84 - 12,337.07

(2) Fence Corner
50,023.51 - 12,344.67

(2) Spk. Approx. SW
50,043.11 - 12,341.77

(17) Fence Corner
50,024.90 - 14,866.13

(16) Spk. - R.L. Int.
50,069.68 - 14,871.29

(18) Sec. Cor. 23
50,070.20 - 14,934.12

(18A) Fence Corner
50,070.20 - 14,934.12
S.E. Corn. Sec. 6, T.33, R.25

(19 to 20A)
50,070.20 - 14,934.12

(4) Spk., R.L. - R.L. Int.
55,278.48 - 19,400.00
in E. Dir. Rd.

(14A) 6" Sp. Cast Iron Man.
H.W. Cor. Sec. 6
55,167.21 - 19,004.82

(13) Spk. R.L. - R.L. Int.
55,212.45 - 14,774.97

(14) H.W. Cor. to Fence Corner which
is Set. Cor. Per Wayne Ridge
55,198.45 - 14,775.28

(3) Spk. on R.L. Approx.
W. 1/4 Cor. Sec. 6
52,677.85 - 10,000.00
in E. Dir. Rd.

(15) Temporary W. 1/4 Cor.
52,699.89 - 10,002.47

(12) I.P. over rotted Wood Post.
Approx. E. 1/4 Cor.
52,673.60 - 14,831.09
in E. Dir. Rd.



10,000.00

11,000.00

12,000.00

13,000.00

14,000.00

15,000.00

16,000.00

17,000.00